


FCC Test Report

Equipment : 802.11abgn, USB module
Brand Name : SparkLAN
Model No. : WUBR-508N
FCC ID : RYK-WUBR508N
Standard : 47 CFR FCC Part 15.407
Operating Band : 5150 MHz – 5250 MHz
5725 MHz – 5850 MHz
FCC Classification : NII
Applicant / Manufacturer : SparkLAN Communications, Inc.
8F., No. 257, Sec. 2, Tiding Blvd., Neihu District,
Taipei City 11493, Taiwan
Function : ☐ Outdoor AP; ☐ Indoor AP;
☐ Fixed P2P AP ☒ Mobile Client

The product sample received on Mar. 29, 2012 and completely tested on May 18, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Kevin Liang / Assistant Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Support Equipment.....	8
1.3	Testing Applied Standards	8
1.4	Testing Location Information	9
1.5	Measurement Uncertainty	9
2	TEST CONFIGURATION OF EUT.....	10
2.1	The Worst Case Modulation Configuration	10
2.2	The Worst Case Power Setting Parameter	10
2.3	The Worst Case Measurement Configuration.....	11
2.4	Test Setup Diagram	12
3	TRANSMITTER TEST RESULT	14
3.1	AC Power-line Conducted Emissions	14
3.2	Emission Bandwidth	17
3.3	RF Output Power.....	20
3.4	Peak Power Spectral Density.....	25
3.5	Transmitter Bandedge Emissions	29
3.6	Transmitter Unwanted Emissions.....	33
3.7	Frequency Stability.....	70
4	TEST EQUIPMENT AND CALIBRATION DATA	72
APPENDIX A. TEST PHOTOS		
APPENDIX B. PHOTOGRAPHS OF EUT		

Summary of Test Result

Conformance Test Specifications			
Report Clause	Ref. Std. Clause	Description	Result
1.1.2	15.203	Antenna Requirement	Complied
3.1	15.207	AC Power-line Conducted Emissions	Complied
3.2	15.407(a)	Emission Bandwidth	Complied
3.3	15.407(a)	RF Output Power (Maximum Conducted Output Power)	Complied
3.4	15.407(a)	Peak Power Spectral Density	Complied
3.5	15.407(b)	Transmitter Bandedge Emissions	Complied
3.6	15.407(b)	Transmitter Unwanted Emissions	Complied
3.7	15.407(g)	Frequency Stability	Complied



SPORTON INTERNATIONAL INC.
TEL : 886-3-327-3456
FAX : 886-3-327-0973

1 General Description

1.1 Information

1.1.1 RF General Information

RF General Information (5150-5250MHz band)					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	RF Output Power (dBm)
5150-5250	a	5180-5240	36-48 [4]	1	12.85
5150-5250	n (HT20)	5180-5240	36-48 [4]	2	12.38
5150-5250	n (HT40)	5190-5230	38-46 [2]	2	15.21
Note 1: RF output power specifies that Maximum Conducted Output Power. Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.					

RF General Information (5725-5850MHz band)					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	RF Output Power (dBm)
5725-5850	a	5745-5825	149-165 [5]	1	18.67
5725-5850	n (HT20)	5745-5825	149-165 [5]	2	18.57
5725-5850	n (HT40)	5755-5795	151-159 [2]	2	21.78
Note 1: RF output power specifies that Maximum Conducted Output Power. Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.					

1.1.2 Antenna Information

Antenna Category	
☒	Integral antenna (antenna permanently attached)
☐	Temporary RF connector provided
☒	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.

Antenna General Information			
No.	Ant. Cat.	Ant. Type	Gain (dBi)
1	Integral	Printed	6.64
2	Integral	Printed	6.64

Remark:

- In modulation mode 11a, this EUT supports diversity. EUT was pre-tested Antenna Port 1 and Antenna Port 2 for single chain, and the worst case was Antenna Port 1. Therefore only the test data (Port 1) was recorded in this report.
- In modulation mode 11n, this EUT only supports 2TX.

1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	☒ Production ; ☐ Pre-Production ; ☐ Prototype
Type of EUT	
☒	Stand-alone
☐	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
☐	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
☐	Other:

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle		
☐ Operated normally mode for worst duty cycle		
☒ Operated test mode for worst duty cycle		
Test Signal Duty Cycle (x)	N _{TX}	Power Duty Factor [dB] – (10 log 1/x)
☒ 100.00% - IEEE 802.11a	1	0.00
☒ 100.00% - IEEE 802.11n (HT20)	2	0.00
☒ 100.00% - IEEE 802.11n (HT40)	2	0.00

1.1.5 EUT Operational Condition

Supply Voltage	☐ AC mains	☒ DC	
Type of DC Source	☐ Internal DC supply	☒ From system	☐ External DC adapter
Test Voltage	☒ Vnom (5 V)	☒ Vmax (5.75 V)	☒ Vmin (4.25 V)
Test Climatic	☒ Tnom (20°C)	☒ Tmax (50°C)	☒ Tmin (-20°C)

1.2 Support Equipment

Support Equipment - RF Conducted			
No.	Equipment	Brand Name	Model Name
1	Notebook	DELL	E5540
2	Adapter for NB	DELL	HA65NM130

Support Equipment - AC Conduction and Radiated Emission			
No.	Equipment	Brand Name	Model Name
1	Notebook	DELL	E5540
2	AC adaptor	DELL	LA65NS2-01
3	USB Cable	-	-
		0.69 meter, non-shielded cable	

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ FCC KDB 789033 D02 v01r02
- ♦ FCC-16-24-UNII
- ♦ FCC KDB 662911 D01 v02r01

1.4 Testing Location Information

Testing Location			
☒	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan, R.O.C.	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test Condition	Test Site No.	Test Engineer	Test Environment
AC Conduction	CO04-HY	Anthony	23°C / 58%
RF Conducted	TH01-HY	Jeremy	20.1°C / 63%
Radiated Emission	03CH09-HY	Joe	22.2°C / 51.8%

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty		
Test Item		Uncertainty
AC power-line conducted emissions		±2.3 dB
Emission bandwidth, 26dB bandwidth		±0.5%
RF output power, conducted		±0.1 dB
Power density, conducted		±0.5 dB
Unwanted emissions, conducted	9 – 150 kHz	±0.4 dB
	0.15 – 30 MHz	±0.4 dB
	30 – 1000 MHz	±0.6 dB
	1 – 18 GHz	±0.5 dB
	18 – 40 GHz	±0.5 dB
	40 – 200 GHz	N/A
All emissions, radiated	9 – 150 kHz	±2.5 dB
	0.15 – 30 MHz	±2.3 dB
	30 – 1000 MHz	±2.6 dB
	1 – 18 GHz	±3.6 dB
	18 – 40 GHz	±3.8 dB
	40 – 200 GHz	N/A
Temperature		±0.8 °C
Humidity		±5 %
DC and low frequency voltages		±0.9%
Time		±1.4 %
Duty Cycle		±0.5 %

2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS
11a	1	6-54Mbps	6 Mbps
HT20	2	M8-16	M8
HT40	2	M8-16	M8

2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (5150-5250MHz band)						
Test Software Version	RT5x7x QA_V1.0.5.9					
Modulation Mode	N _{TX}	Test Frequency (MHz)				
		NCB: 20MHz			NCB: 40MHz	
		5180	5200	5240	5190	5230
11a	1	0C	0F	10	-	-
HT20	2	08,0A	0B,0C	0B,0C	-	-
HT40	2	-	-	-	0F,10	0F,10

The Worst Case Power Setting Parameter (5725-5850MHz band)						
Test Software Version	RT5x7x QA_V1.0.5.9					
Modulation Mode	N _{TX}	Test Frequency (MHz)				
		NCB: 20MHz			NCB: 40MHz	
		5745	5785	5825	5755	5795
11a	1	20	23	22	-	-
HT20	2	1E,1E	22,22	21,21	-	-
HT40	2	-	-	-	2B,2B	2B,2B


2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Operating Mode Description
1	EUT with Notebook and transmit


The Worst Case Mode for Following Conformance Tests	
Tests Item	RF Output Power, Peak Power Spectral Density, Emission Bandwidth, Transmitter Conducted Unwanted Emissions Transmitter Conducted Bandedge Emissions
Test Condition	Conducted measurement at transmit chains
Modulation Mode	11a, HT20, HT40

The Worst Case Mode for Following Conformance Tests			
Tests Item	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
User Position	☐ EUT will be placed in fixed position.		
	☒ EUT will be placed in mobile position and operating multiple positions.		
	☐ EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed three orthogonal planes.		
Operating Mode	Operating Mode Description		
Radiated Emissions	EUT with Notebook and transmit		
Modulation Mode	11a, HT20, HT40		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT	V		


2.4 Test Setup Diagram



Test Setup Diagram - Radiated Below 1GHz Test



Test Setup Diagram - Radiated Above 1GHz Test



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


3.1.3 Test Procedures

Test Method
☒ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup




3.1.5 Test Result of AC Power-line Conducted Emissions



AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	EUT with Notebook via USB Cable		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1556680	49.87	-15.82	65.69	49.47	0.05	0.35	QP
2	0.1556680	29.11	-26.58	55.69	28.71	0.05	0.35	Average
3	0.1844300	45.18	-19.10	64.28	44.67	0.06	0.45	QP
4	0.1844300	27.19	-27.09	54.28	26.68	0.06	0.45	Average
5	0.5581450	33.68	-22.32	56.00	32.94	0.07	0.67	QP
6	0.5581450	16.12	-29.88	46.00	15.38	0.07	0.67	Average
7	0.7430230	35.17	-20.83	56.00	34.36	0.08	0.73	QP
8	0.7430230	17.92	-28.08	46.00	17.11	0.08	0.73	Average
9	2.350	32.45	-23.55	56.00	31.56	0.11	0.78	QP
10	2.350	23.59	-22.41	46.00	22.70	0.11	0.78	Average
11	17.660	35.81	-24.19	60.00	34.73	0.34	0.74	QP
12	17.660	29.07	-20.93	50.00	27.99	0.34	0.74	Average

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

3.2 Emission Bandwidth

3.2.1 Emission Bandwidth Limit

Emission Bandwidth Limit	
UNII Devices	
☒	For the 5.15-5.25 GHz band, N/A
☐	For the 5.25-5.35 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz.
☐	For the 5.47-5.725 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz.
☒	For the 5.725-5.85 GHz band, 6 dB emission bandwidth $\geq$ 500kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
☒	For the emission bandwidth shall be measured using one of the options below:
☒	Refer as FCC KDB 789033 D02 v01r02, clause C for EBW and clause D for OBW measurement.
☐	Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
☐	Refer as IC RSS-Gen, clause 6.6 for bandwidth testing.
☒	For conducted measurement.
☐	The EUT supports single transmit chain and measurements performed on this transmit chain 2.
☒	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
☒	The EUT supports multiple transmit chains using options given below:
☐	Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 2.
☒	Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.

3.2.4 Test Setup




3.2.5 Test Result of Emission Bandwidth


UNII Emission Bandwidth Result (5150-5250MHz band)						
Condition			Emission Bandwidth (MHz)			
Modulation Mode	N _{TX}	Freq. (MHz)	99% Bandwidth		26dB Bandwidth	
			Chain Port 1	Chain Port 2	Chain Port 1	Chain Port 2
11a	1	5180	16.34	-	19.15	-
11a	1	5200	16.36	-	18.75	-
11a	1	5240	16.34	-	18.75	-
HT20	2	5180	17.46	17.39	19.37	20.07
HT20	2	5200	17.36	17.44	19.57	19.07
HT20	2	5240	17.41	17.44	19.27	19.32
HT40	2	5190	35.94	36.54	38.84	39.96
HT40	2	5230	36.02	35.94	39.56	39.24
Result			Complied			

UNII Emission Bandwidth Result (5725-5850MHz band)						
Condition			Emission Bandwidth (MHz)			
Modulation Mode	N _{TX}	Freq. (MHz)	99% Bandwidth		6dB Bandwidth	
			Chain Port 1	Chain Port 2	Chain Port 1	Chain Port 2
11a	1	5745	16.37	-	16.38	-
11a	1	5785	16.55	-	16.44	-
11a	1	5825	16.43	-	16.41	-
HT20	2	5745	17.46	17.45	17.31	17.26
HT20	2	5785	17.48	17.39	17.53	16.80
HT20	2	5825	17.46	17.43	17.56	16.90
HT40	2	5755	36.30	36.30	36.32	35.96
HT40	2	5795	36.34	36.26	36.08	35.44
Limit			-		≥ 500 kHz	
Result			Complied			

5150-5250MHz - Worst Emission 26Bandwidth Plots



5725-5850MHz - Worst Emission 6Bandwidth Plots



Date: 19.MAY.2016 20:43:50

3.3 RF Output Power

3.3.1 RF Output Power Limit

Maximum Conducted Output Power Limit	
UNII Devices	
☒ For the 5.15-5.25 GHz band:	
☐	Outdoor AP: the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W. If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$. e.i.r.p. at any elevation angle above 30 degrees ≤ 125 mW [21dBm]
☐	Indoor AP: the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W. If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$
☐	Point-to-point AP: the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W. If $G_{TX} > 23$ dBi, then $P_{Out} = 30 - (G_{TX} - 23)$.
☒	Mobile or Portable Client: the maximum conducted output power (P_{Out}) shall not exceed the lesser of 250 mW. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$.
☐	For the 5.25-5.35 GHz band, the maximum conducted output power (P_{Out}) shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$.
☐	For the 5.47-5.725 GHz band, the maximum conducted output power (P_{Out}) shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$.
☒ For the 5.725-5.85 GHz band:	
☒	Point-to-multipoint systems (P2M): the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W. If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$.
☐	Point-to-point systems (P2P): the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W.
P_{Out} = maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
☒	Maximum Conducted Output Power
	[duty cycle $\geq 98\%$ or external video / power trigger]
☒	Refer as FCC KDB 789033 D02 v01r02, clause E Method SA-1 (spectral trace averaging).
☐	Refer as FCC KDB 789033 D02 v01r02, clause E Method SA-1 Alt. (RMS detection with slow sweep speed)
	duty cycle $< 98\%$ and average over on/off periods with duty factor
☐	Refer as FCC KDB 789033 D02 v01r02, clause E Method SA-2 (spectral trace averaging).
☐	Refer as FCC KDB 789033 D02 v01r02, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)
	Wideband RF power meter and average over on/off periods with duty factor
☐	Refer as FCC KDB 789033 D02 v01r02, clause E Method PM (using an RF average power meter).
☒	For conducted measurement.
☐	The EUT supports single transmit chain and measurements performed on this transmit chain.
☒	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
☒	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
☐	If multiple transmit chains, EIRP calculation could be following as methods: $P_{\text{total}} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $\text{EIRP}_{\text{total}} = P_{\text{total}} + \text{DG}$

3.3.4 Test Setup



3.3.5 Directional Gain for Power Measurement


Directional Gain (DG) Result					
Transmit Chains No.		1	2	-	-
Maximum G_{ANT} (dBi)		6.64	6.64	-	-
Modulation Mode	DG (dBi)	N_{TX}	N_{SS} (Min.)	STBC	Array Gain (dB)
11a	6.64	1	1	-	0.00
HT20,M0-15	9.65	2	1	-	3.01
HT40,M0-15	9.65	2	1	-	3.01
Note 1: For all transmitter outputs with equal antenna gains, directional gain is to be computed as follows: Any transmit signals are correlated, Directional Gain = $G_{ANT} + 10 \log(N_{TX})$ All transmit signals are completely uncorrelated, Directional Gain = G_{ANT} Note 2: For all transmitter outputs with unequal antenna gains, directional gain is to be computed as follows: Any transmit signals are correlated, Directional Gain = $10 \log[(10^{G_{1/20}} + \dots + 10^{G_{N/20}})^2 / N_{TX}]$ All transmit signals are completely uncorrelated, Directional Gain = $10 \log[(10^{G_{1/10}} + \dots + 10^{G_{N/10}}) / N_{TX}]$ Note 3: For Spatial Multiplexing, Directional Gain (DG) = $G_{ANT} + 10 \log(N_{TX}/N_{SS})$, where N_{SS} = the number of independent spatial streams data. Note 4: For CDD transmissions, directional gain is calculated as power measurements: Directional Gain (DG) = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows: Array Gain = 0 dB (i.e., no array gain) for $N_{TX} \leq 4$; Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{TX}; Note 5: Array Gain = $10 \log(N_{TX})$					

3.3.6 Test Result of Maximum Conducted Average Output Power


Maximum Conducted Average Output Power (5150-5250MHz band)							
Modulation Mode	N _{TX}	Freq. (MHz)	Output Power (dBm)			Antenna Gain (dBi)	Power Limit
			Chain Port 1	Chain Port 2	Sum Chain		
11a	1	5180	12.85	-	12.85	6.64	23.36
11a	1	5200	12.71	-	12.71	6.64	23.36
11a	1	5240	12.46	-	12.46	6.64	23.36
HT20	2	5180	9.22	8.77	12.01	9.65	20.35
HT20	2	5200	9.26	9.48	12.38	9.65	20.35
HT20	2	5240	8.67	9.57	12.15	9.65	20.35
HT40	2	5190	12.12	12.27	15.21	9.65	20.35
HT40	2	5230	11.09	11.95	14.55	9.65	20.35
Result			Complied				

Maximum Conducted Average Output Power (5725-5850MHz band)							
Modulation Mode	N _{TX}	Freq. (MHz)	Output Power (dBm)			Antenna Gain (dBi)	Power Limit
			Chain Port 1	Chain Port 2	Sum Chain		
11a	1	5745	18.00	-	18.00	6.64	29.36
11a	1	5785	18.67	-	18.67	6.64	29.36
11a	1	5825	17.84	-	17.84	6.64	29.36
HT20	2	5745	15.65	15.47	18.57	9.65	26.35
HT20	2	5785	14.58	14.24	17.42	9.65	26.35
HT20	2	5825	14.30	13.86	17.10	9.65	26.35
HT40	2	5755	18.76	18.64	21.71	9.65	26.35
HT40	2	5795	19.07	18.44	21.78	9.65	26.35
Result			Complied				

5150-5250MHz - Worst RF Output Power Plots



5725-5850MHz - Worst RF Output Power Plots



3.4 Peak Power Spectral Density

3.4.1 Peak Power Spectral Density Limit

Peak Power Spectral Density Limit	
UNII Devices	
☒ For the 5.15-5.25 GHz band:	
☐	Outdoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 17 - (G_{TX} - 6)$.
☐	Indoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 17 - (G_{TX} - 6)$.
☐	Point-to-point AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If $G_{TX} > 23$ dBi, then $P_{Out} = 17 - (G_{TX} - 23)$.
☒	Mobile or Portable Client: the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$.
☐ For the 5.25-5.35 GHz band, the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$.	
☐ For the 5.47-5.725 GHz band, the peak power spectral density (PPSD) ≤ 11 dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$.	
☒ For the 5.725-5.85 GHz band:	
☒	Point-to-multipoint systems (P2M): the peak power spectral density (PPSD) ≤ 30 dBm/500kHz. If $G_{TX} > 6$ dBi, then $PPSD = 30 - (G_{TX} - 6)$.
☐	Point-to-point systems (P2P): the peak power spectral density (PPSD) ≤ 30 dBm/500kHz.
PPSD = peak power spectral density that he same method as used to determine the conducted output power shall be used to determine the power spectral density. And power spectral density in dBm/MHz G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
☒	Peak power spectral density procedures that the same method as used to determine the conducted output power shall be used to determine the peak power spectral density and use the peak search function on the spectrum analyzer to find the peak of the spectrum. For the peak power spectral density shall be measured using below options:
☒	Refer as FCC KDB 789033 D02 v01r02, F5) power spectral density can be measured using resolution bandwidths < 1 MHz provided that the results are integrated over 1 MHz bandwidth [duty cycle ≥ 98% or external video / power trigger]
☐	Refer as FCC KDB 789033 D02 v01r02, clause E Method SA-1 (spectral trace averaging).
☐	Refer as FCC KDB 789033 D02 v01r02, clause E Method SA-1 Alt. (RMS detection with slow sweep speed)
	duty cycle < 98% and average over on/off periods with duty factor
☐	Refer as FCC KDB 789033 D02 v01r02, clause E Method SA-2 (spectral trace averaging).
☐	Refer as FCC KDB 789033 D02 v01r02, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)
☒	For conducted measurement.
☐	The EUT supports single transmit chain and measurements performed on this transmit chain.
☒	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
☒	The EUT supports multiple transmit chains using options given below:
☒	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
☐	Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.
☐	If multiple transmit chains, EIRP PPSD calculation could be following as methods: $PPSD_{total} = PPSD_1 + PPSD_2 + \dots + PPSD_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = PPSD_{total} + DG$
☐	Each individually PPSD plots refer as test report clause 3.3.5 with each individually PPSD plots.



3.4.4 Test Setup



3.4.5 Test Result of Peak Power Spectral Density



Peak Power Spectral Density Result (5150-5250MHz band)					
Modulation Mode	N _{TX}	Freq. (MHz)	Peak Power Spectral Density (dBm)	PSD Limit	PSD-DG (dBi)
11a	1	5180	1.87	10.36	6.64
11a	1	5200	1.88	10.36	6.64
11a	1	5240	1.40	10.36	6.64
HT20	2	5180	0.79	7.35	9.65
HT20	2	5200	1.34	7.35	9.65
HT20	2	5240	1.09	7.35	9.65
HT40	2	5190	0.84	7.35	9.65
HT40	2	5230	0.18	7.35	9.65
Result			Complied		

Peak Power Spectral Density Result (5725-5850MHz band)					
Modulation Mode	N _{TX}	Freq. (MHz)	Peak Power Spectral Density (dBm)	PSD Limit (500kHz)	PSD-DG (dBi)
11a	1	5745	10.53	29.36	6.64
11a	1	5785	11.75	29.36	6.64
11a	1	5825	11.55	29.36	6.64
HT20	2	5745	11.11	26.35	9.65
HT20	2	5785	10.17	26.35	9.65
HT20	2	5825	9.87	26.35	9.65
HT40	2	5755	9.28	26.35	9.65
HT40	2	5795	9.60	26.35	9.65
Result			Complied		

5150-5250MHz - Worst Power Spectral Density Plots

5725-5850MHz - Worst Power Spectral Density Plots


3.5 Transmitter Bandedge Emissions

3.5.1 Transmitter Radiated Bandedge Emissions Limit




3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method	
☒	The average emission levels shall be measured in [duty cycle $\geq$ 98 or duty factor].
☒	Refer as ANSI C63.10, clause 6.10 bandedge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
☐	If EUT operate in adjacent contiguous bands, bandedge testing performed at the lowest frequency channel at lower-band and highest frequency channel at higher-band. Transmitter in-band emissions will consist of adjacent contiguous bands (e.g., IEEE 802.11ac VHT160 The lowest frequency channel at lower-band and highest frequency channel at higher-band in-band emissions will consist of two adjacent contiguous bands.)
☐	☐ Operating in 5.15-5.25 GHz band (lower-band) and 5.25-5.35 GHz band (higher-band). ☐ Operating in 5.47-5.725 GHz band (lower-band) and 5.725-5.85 GHz band (higher-band).
☐	If EUT operate in individual non-contiguous bands, bandedge testing performed at the lowest frequency channel and highest frequency channel within lower-band and higher-band. (e.g., (e.g., IEEE 802.11ac VHT160)
☐	☐ Operating in 5.25-5.35 GHz band (lower-band) and 5.47-5.725 GHz band (higher-band). ☐ Operating in 5.15-5.25 GHz band (lower-band) and 5.725-5.85 GHz band (higher-band).
☒	For the transmitter unwanted emissions shall be measured using following options below:
☒	Refer as FCC KDB 789033 D02 v01r02, clause H)2) for unwanted emissions into non-restricted bands.
☒	Refer as FCC KDB 789033 D02 v01r02, clause H)1) for unwanted emissions into restricted bands.
☐	☐ Refer as FCC KDB 789033 D02 v01r02, H)6) Method AD (Trace Averaging). ☐ Refer as FCC KDB 789033 D02 v01r02, H)6) Method VB (Reduced VBW). ☒ Refer as ANSI C63.10, clause 4.1.4.2.3 (Reduced VBW). VBW $\geq$ 1/T, where T is pulse time. ☐ Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions. ☒ Refer as FCC KDB 789033 D02 v01r02, clause H)5) measurement procedure peak limit. ☐ Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.
☒	For the transmitter bandedge emissions shall be measured using following options below:
☐	Refer as FCC KDB 789033 D02 v01r02, clause H)3)d) for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
☒	Refer as ANSI C63.10, clause 6.10 for band-edge testing.
☐	Refer as ANSI C63.10, clause 6.10.6.2 for marker-delta method for band-edge measurements.
☒	For radiated measurement, refer as ANSI C63.10, clause 6.6. Test distance is 3m.
☒	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements). Measurements in the bandedge are typically made at a closer distance 3m, because the instrumentation noise floor is typically close to the radiated emission limit.

3.5.4 Test Setup



3.5.5 Transmitter Radiated Bandedge Emissions (with Antenna)

U-NII 5150-5250MHz Transmitter Radiated Bandedge (with Antenna)										
Modulation Mode	N _{TX}	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Freq. (MHz) AV	Level (dBuV/m) AV	Limit (dBuV/m) AV	Pol.
11a	1	5180	3	5128	58.66	74	5127.6	47.37	54	V
11a	1	5240	3	5109.6	57.84	74	5104.8	46.51	54	V
HT20	2	5180	3	5100.2	57.16	74	5128.4	46.29	54	V
HT20	2	5240	3	5100	56.8	74	5123.4	45.79	54	V
HT40	2	5190	3	5145.54	60.42	74	5149.94	49.79	54	V
HT40	2	5230	3	5128.8	57.52	74	5127.6	46.35	54	V

Note 1: Measurement worst emissions of receive antenna polarization.

U-NII 5725-5850MHz Transmitter Radiated Bandedge (with Antenna)							
Modulation Mode	N _{TX}	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Pol.
11a	1	5745	3	5634.1	57.95	68.2	V
11a	1	5825	3	5929.48	58.4	68.2	V
HT20	2	5745	3	5628.9	57.68	68.2	V
HT20	2	5825	3	5945.95	58.05	68.2	V
HT40	2	5755	3	5641.74	58.11	68.2	V
HT40	2	5795	3	5950	57.8	68.2	V

Note 1: Measurement worst emissions of receive antenna polarization.

3.6 Transmitter Unwanted Emissions

3.6.1 Transmitter Radiated Unwanted Emissions Limit

Unwanted emissions below 1 GHz and restricted band emissions above 1GHz limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted band emissions above 1GHz Limit	
Operating Band	Limit
5.15 - 5.25 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.725 - 5.85 GHz	5.650-5700 GHz: e.i.r.p. -27 ~ 10 dBm [68.2 ~ 105.2 dBuV/m@3m] 5.700-5720 GHz: e.i.r.p. 10 ~ 15.6 dBm [105.2 ~ 110.8 dBuV/m@3m] 5.720-5725 GHz: e.i.r.p. 15.6 ~ 27 dBm [110.8 ~ 122.2 dBuV/m@3m] 5.850-5.855 GHz: e.i.r.p. 27 ~ 15.6 dBm [122.2 ~ 110.8 dBuV/m@3m] 5.855-5.875 GHz: e.i.r.p. 15.6 ~ 10 dBm [110.8 ~ 105.2 dBuV/m@3m] 5.875-5.925 GHz: e.i.r.p. 10 ~ -27 dBm [105.2 ~ 68.2dBuV/m@3m] Other un-restricted band: e.i.r.p. -27 dBm [68.2 dBuV/m@3m]

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
☒	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 m for frequencies above 30 MHz, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
☒	The average emission levels shall be measured in [duty cycle $\geq$ 98 or duty factor].
☒	For the transmitter unwanted emissions shall be measured using following options below:
☒	Refer as FCC KDB 789033 D02 v01r02, clause G)2) for unwanted emissions into non-restricted bands.
☒	Refer as FCC KDB 789033 D02 v01r02, clause G)1) for unwanted emissions into restricted bands.
☒	Refer as FCC KDB 789033 D02 v01r02, G)6) Method AD (Trace Averaging).
☐	Refer as FCC KDB 789033 D02 v01r02, G)6) Method VB (Reduced VBW).
☐	Refer as ANSI C63.10, clause 4.1.4.2.3 (Reduced VBW). VBW $\geq$ 1/T, where T is pulse time.
☐	Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions.
☒	Refer as FCC KDB 789033 D02 v01r02, clause G)5) measurement procedure peak limit.
☐	Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.
☒	For radiated measurement.
☒	Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
☒	Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
☒	Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz. For 1 GHz to 5 GHz, test distance is 3m; For 5 GHz to 40 GHz, test distance is 3m.
☒	The any unwanted emissions level shall not exceed the fundamental emission level.
☒	All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


3.6.4 Test Setup

Transmitter Radiated Unwanted Emissions Below 1GHz



Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna.

Transmitter Radiated Unwanted Emissions Above 1GHz




Electric field tests shall be performed in the frequency range of 1 GHz to 10th harmonic of highest fundamental frequency or 40 GHz using a calibrated horn antenna.

3.6.5 Transmitter Radiated Unwanted Emissions-with Antenna (Below 30MHz)


All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Transmitter Radiated Unwanted Emissions (Below 1GHz)																																																																																	
Operating Mode		1			Polarization			V																																																																									
Operating Function		EUT with Notebook and transmit																																																																															
Level (dBuV/m)  Date: 2016-05-18 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>Limit Line</th><th>ReadAntenna Level</th><th>Cable Preamp</th><th>Loss Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr><tr><td>1</td><td>31.94</td><td>29.09</td><td>-10.91</td><td>40.00</td><td>42.30</td><td>23.85</td><td>0.33</td><td>37.39 Peak</td></tr><tr><td>2</td><td>115.36</td><td>37.48</td><td>-6.02</td><td>43.50</td><td>57.03</td><td>16.62</td><td>0.59</td><td>36.76 Peak</td></tr><tr><td>3</td><td>239.52</td><td>32.05</td><td>-13.95</td><td>46.00</td><td>50.62</td><td>16.96</td><td>0.86</td><td>36.39 Peak</td></tr><tr><td>4</td><td>596.48</td><td>36.96</td><td>-9.04</td><td>46.00</td><td>48.26</td><td>24.55</td><td>1.41</td><td>37.26 Peak</td></tr><tr><td>5</td><td>666.32</td><td>29.89</td><td>-16.11</td><td>46.00</td><td>40.21</td><td>25.60</td><td>1.50</td><td>37.42 Peak</td></tr><tr><td>6</td><td>959.26</td><td>33.87</td><td>-12.13</td><td>46.00</td><td>39.41</td><td>30.03</td><td>1.86</td><td>37.43 Peak</td></tr></table>											Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Preamp	Loss Factor	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	1	31.94	29.09	-10.91	40.00	42.30	23.85	0.33	37.39 Peak	2	115.36	37.48	-6.02	43.50	57.03	16.62	0.59	36.76 Peak	3	239.52	32.05	-13.95	46.00	50.62	16.96	0.86	36.39 Peak	4	596.48	36.96	-9.04	46.00	48.26	24.55	1.41	37.26 Peak	5	666.32	29.89	-16.11	46.00	40.21	25.60	1.50	37.42 Peak	6	959.26	33.87	-12.13	46.00	39.41	30.03	1.86	37.43 Peak
	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Preamp	Loss Factor	Remark																																																																									
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB																																																																									
1	31.94	29.09	-10.91	40.00	42.30	23.85	0.33	37.39 Peak																																																																									
2	115.36	37.48	-6.02	43.50	57.03	16.62	0.59	36.76 Peak																																																																									
3	239.52	32.05	-13.95	46.00	50.62	16.96	0.86	36.39 Peak																																																																									
4	596.48	36.96	-9.04	46.00	48.26	24.55	1.41	37.26 Peak																																																																									
5	666.32	29.89	-16.11	46.00	40.21	25.60	1.50	37.42 Peak																																																																									
6	959.26	33.87	-12.13	46.00	39.41	30.03	1.86	37.43 Peak																																																																									
Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.) Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical). Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.																																																																																	

Transmitter Radiated Unwanted Emissions (Below 1GHz)

Operating Mode	1	Polarization	H
Operating Function	EUT with Notebook and transmit		



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Preamp	Loss Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	117.30	39.80	-3.70	43.50	59.22	16.74	0.59	36.75 QP
2	123.12	40.29	-3.21	43.50	59.43	16.96	0.62	36.72 QP
3	245.34	41.84	-4.16	46.00	59.83	17.53	0.87	36.39 Peak
4	373.38	38.91	-7.09	46.00	53.56	20.86	1.08	36.59 Peak
5	598.42	35.35	-10.65	46.00	46.62	24.58	1.41	37.26 Peak
6	959.26	37.58	-8.42	46.00	43.12	30.03	1.86	37.43 Peak


Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).


Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.

3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 5150-5250MHz



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5180
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	7485.00	39.47	-14.53	54.00	30.69	36.56	7.66	35.44	Average
2	7485.00	51.47	-22.53	74.00	42.69	36.56	7.66	35.44	Peak
3	10360.00	61.48	-6.72	68.20	48.20	39.48	9.41	35.61	Peak
4	15540.00	47.52	-6.48	54.00	33.20	38.41	11.54	35.63	Average
5	15540.00	59.22	-14.78	74.00	44.90	38.41	11.54	35.63	Peak

- Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
- Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5200
N_{TX}	1	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8396.00	40.29	-13.71	54.00	30.85	36.88	8.23	35.67	Average
2	8396.00	53.18	-20.82	74.00	43.74	36.88	8.23	35.67	Peak
3	10400.00	59.65	-8.55	68.20	46.25	39.54	9.44	35.58	Peak
4	15600.00	44.37	-9.63	54.00	30.26	38.28	11.50	35.67	Average
5	15600.00	56.38	-17.62	74.00	42.27	38.28	11.50	35.67	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5200
N_{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8002.00	53.55	-14.65	68.20	43.98	37.20	8.00	35.63 Peak
2	10400.00	61.60	-6.60	68.20	48.20	39.54	9.44	35.58 Peak
3	15600.00	46.22	-7.78	54.00	32.11	38.28	11.50	35.67 Average
4	15600.00	57.52	-16.48	74.00	43.41	38.28	11.50	35.67 Peak

- Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
- Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5240
N_{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	7005.00	50.37	-17.83	68.20	42.96	35.31	7.49	35.39	Peak
2	10480.00	56.91	-11.29	68.20	43.26	39.67	9.48	35.50	Peak
3	15720.00	44.82	-9.18	54.00	31.13	38.02	11.40	35.73	Average
4	15720.00	56.55	-17.45	74.00	42.86	38.02	11.40	35.73	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5240
N_{TX}	1	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8496.00	40.04	-13.96	54.00	30.65	36.80	8.27	35.68 Average
2	8496.00	51.86	-22.14	74.00	42.47	36.80	8.27	35.68 Peak
3	10480.00	59.25	-8.95	68.20	45.60	39.67	9.48	35.50 Peak
4	15720.00	45.82	-8.18	54.00	32.13	38.02	11.40	35.73 Average
5	15720.00	57.98	-16.02	74.00	44.29	38.02	11.40	35.73 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5180
N_{TX}	2	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	7185.00	50.62	-17.58	68.20	42.69	35.78	7.56	35.41 Peak
2	10360.00	55.52	-12.68	68.20	42.24	39.48	9.41	35.61 Peak
3	15540.00	45.21	-8.79	54.00	30.89	38.41	11.54	35.63 Average
4	15540.00	57.30	-16.70	74.00	42.98	38.41	11.54	35.63 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5180
N_{TX}	2	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8896.00	52.85	-15.35	68.20	43.01	37.28	8.30	35.74 Peak
2	10360.00	55.68	-12.52	68.20	42.40	39.48	9.41	35.61 Peak
3	15540.00	46.02	-7.98	54.00	31.70	38.41	11.54	35.63 Average
4	15540.00	57.72	-16.28	74.00	43.40	38.41	11.54	35.63 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5200
N_{TX}	2	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	7185.00	50.51	-17.69	68.20	42.58	35.78	7.56	35.41 Peak
2	10400.00	57.60	-10.60	68.20	44.20	39.54	9.44	35.58 Peak
3	15600.00	46.52	-7.48	54.00	32.41	38.28	11.50	35.67 Average
4	15600.00	58.62	-15.38	74.00	44.51	38.28	11.50	35.67 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5200
N _{TX}	2	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8145.00	40.03	-13.97	54.00	30.52	37.08	8.07	35.64	Average
2	8145.00	52.10	-21.90	74.00	42.59	37.08	8.07	35.64	Peak
3	10400.00	58.29	-9.91	68.20	44.89	39.54	9.44	35.58	Peak
4	15600.00	47.14	-6.86	54.00	33.03	38.28	11.50	35.67	Average
5	15600.00	59.10	-14.90	74.00	44.99	38.28	11.50	35.67	Peak

- Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
- Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5240
N _{TX}	2	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	7001.00	50.09	-18.11	68.20	42.69	35.30	7.49	35.39	Peak
2	10480.00	56.66	-11.54	68.20	43.01	39.67	9.48	35.50	Peak
3	15720.00	44.69	-9.31	54.00	31.00	38.02	11.40	35.73	Average
4	15720.00	57.67	-16.33	74.00	43.98	38.02	11.40	35.73	Peak

- Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5240
N_{TX}	2	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamplifier Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8965.00	53.17	-15.03	68.20	43.25	37.36	8.31	35.75 Peak
2	10480.00	57.15	-11.05	68.20	43.50	39.67	9.48	35.50 Peak
3	15720.00	45.98	-8.02	54.00	32.29	38.02	11.40	35.73 Average
4	15720.00	57.98	-16.02	74.00	44.29	38.02	11.40	35.73 Peak

- Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5190
N_{TX}	2	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8003.00	52.59	-15.61	68.20	43.02	37.20	8.00	35.63 Peak
2	10380.00	55.36	-12.84	68.20	42.01	39.51	9.44	35.60 Peak
3	15570.00	45.21	-8.79	54.00	31.01	38.35	11.50	35.65 Average
4	15570.00	57.45	-16.55	74.00	43.25	38.35	11.50	35.65 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
 Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5190
N_{TX}	2	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8965.00	52.61	-15.59	68.20	42.69	37.36	8.31	35.75 Peak
2	10380.00	56.15	-12.05	68.20	42.80	39.51	9.44	35.60 Peak
3	15570.00	46.10	-7.90	54.00	31.90	38.35	11.50	35.65 Average
4	15570.00	58.00	-16.00	74.00	43.80	38.35	11.50	35.65 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5230
N_{TX}	2	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	7152.00	50.85	-17.35	68.20	43.01	35.70	7.55	35.41	Peak
2	10460.00	57.61	-10.59	68.20	44.01	39.64	9.48	35.52	Peak
3	15690.00	44.87	-9.13	54.00	31.11	38.08	11.40	35.72	Average
4	15690.00	59.27	-14.73	74.00	45.51	38.08	11.40	35.72	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5230
N_{TX}	2	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8252.00	39.73	-14.27	54.00	30.25	37.00	8.14	35.66	Average
2	8252.00	52.13	-21.87	74.00	42.65	37.00	8.14	35.66	Peak
3	10460.00	58.50	-9.70	68.20	44.90	39.64	9.48	35.52	Peak
4	15690.00	45.40	-8.60	54.00	31.64	38.08	11.40	35.72	Average
5	15690.00	59.63	-14.37	74.00	45.87	38.08	11.40	35.72	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.


Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

3.6.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 5725-5850MHz

Transmitter Radiated Unwanted Emissions (Above 1GHz)																																																																																
Modulation Mode	11a				Test Freq. (MHz)	5745																																																																										
N _{TX}	1				Polarization	V																																																																										
Level (dBUV/m)  Date: 2016-05-18 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th></th></tr><tr><th></th><th>MHz</th><th>dBUV/m</th><th>Limit</th><th>Line</th><th>Level</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th></th><th></th><th>dB</th><th>dBUV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr><tr><td>1</td><td>8163.00</td><td>39.03</td><td>-14.97</td><td>54.00</td><td>29.52</td><td>37.07</td><td>8.09</td><td>35.65 Average</td></tr><tr><td>2</td><td>8163.00</td><td>52.09</td><td>-21.91</td><td>74.00</td><td>42.58</td><td>37.07</td><td>8.09</td><td>35.65 Peak</td></tr><tr><td>3</td><td>11490.00</td><td>46.06</td><td>-7.94</td><td>54.00</td><td>31.50</td><td>40.10</td><td>9.74</td><td>35.28 Average</td></tr><tr><td>4</td><td>11490.00</td><td>57.46</td><td>-16.54</td><td>74.00</td><td>42.90</td><td>40.10</td><td>9.74</td><td>35.28 Peak</td></tr><tr><td>5</td><td>17235.00</td><td>61.28</td><td>-6.92</td><td>68.20</td><td>43.39</td><td>41.05</td><td>11.93</td><td>35.09 Peak</td></tr></table>										Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp			MHz	dBUV/m	Limit	Line	Level	Loss	Factor	Remark				dB	dBUV/m	dBuV	dB/m	dB	dB	1	8163.00	39.03	-14.97	54.00	29.52	37.07	8.09	35.65 Average	2	8163.00	52.09	-21.91	74.00	42.58	37.07	8.09	35.65 Peak	3	11490.00	46.06	-7.94	54.00	31.50	40.10	9.74	35.28 Average	4	11490.00	57.46	-16.54	74.00	42.90	40.10	9.74	35.28 Peak	5	17235.00	61.28	-6.92	68.20	43.39	41.05	11.93	35.09 Peak
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp																																																																									
	MHz	dBUV/m	Limit	Line	Level	Loss	Factor	Remark																																																																								
			dB	dBUV/m	dBuV	dB/m	dB	dB																																																																								
1	8163.00	39.03	-14.97	54.00	29.52	37.07	8.09	35.65 Average																																																																								
2	8163.00	52.09	-21.91	74.00	42.58	37.07	8.09	35.65 Peak																																																																								
3	11490.00	46.06	-7.94	54.00	31.50	40.10	9.74	35.28 Average																																																																								
4	11490.00	57.46	-16.54	74.00	42.90	40.10	9.74	35.28 Peak																																																																								
5	17235.00	61.28	-6.92	68.20	43.39	41.05	11.93	35.09 Peak																																																																								
Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.) Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical) Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition. Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407. Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.																																																																																

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5745
N_{TX}	1	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8796.00	53.31	-14.89	68.20	43.58	37.16	8.29	35.72 Peak
2	11490.00	52.86	-1.14	54.00	38.30	40.10	9.74	35.28 Average
3	11490.00	63.66	-10.34	74.00	49.10	40.10	9.74	35.28 Peak
4	17235.00	63.13	-5.07	68.20	45.24	41.05	11.93	35.09 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5785
N_{TX}	1	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamplifier	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8896.00	52.42	-15.78	68.20	42.58	37.28	8.30	35.74 Peak
2	11570.00	46.03	-7.97	54.00	31.62	39.93	9.79	35.31 Average
3	11570.00	57.40	-16.60	74.00	42.99	39.93	9.79	35.31 Peak
4	17355.00	61.46	-6.74	68.20	43.24	41.44	11.92	35.14 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5785
N_{TX}	1	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	7985.00	52.68	-15.52	68.20	43.14	37.18	7.98	35.62	Peak
2	11570.00	52.91	-1.09	54.00	38.50	39.93	9.79	35.31	Average
3	11570.00	63.43	-10.57	74.00	49.02	39.93	9.79	35.31	Peak
4	17355.00	63.41	-4.79	68.20	45.19	41.44	11.92	35.14	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5825
N _{TX}	1	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8895.00	53.09	-15.11	68.20	43.26	37.27	8.30	35.74 Peak
2	11650.00	45.93	-8.07	54.00	31.69	39.74	9.84	35.34 Average
3	11650.00	57.13	-16.87	74.00	42.89	39.74	9.84	35.34 Peak
4	17475.00	61.12	-7.08	68.20	42.58	41.82	11.90	35.18 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5825
N_{TX}	1	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	7695.00	39.26	-14.74	54.00	30.14	36.83	7.80	35.51 Average
2	7695.00	51.81	-22.19	74.00	42.69	36.83	7.80	35.51 Peak
3	11650.00	52.94	-1.06	54.00	38.70	39.74	9.84	35.34 Average
4	11650.00	64.84	-9.16	74.00	50.60	39.74	9.84	35.34 Peak
5	17475.00	62.34	-5.86	68.20	43.80	41.82	11.90	35.18 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5745
N _{TX}	2	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	7003.00	50.43	-17.77	68.20	43.02	35.31	7.49	35.39 Peak
2	11490.00	47.18	-6.82	54.00	32.62	40.10	9.74	35.28 Average
3	11490.00	58.21	-15.79	74.00	43.65	40.10	9.74	35.28 Peak
4	17235.00	59.89	-8.31	68.20	42.00	41.05	11.93	35.09 Peak

- Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
- Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
- Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
- Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.
- Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.
- Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5745
N_{TX}	2	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8496.00	40.01	-13.99	54.00	30.62	36.80	8.27	35.68 Average
2	8496.00	52.41	-21.59	74.00	43.02	36.80	8.27	35.68 Peak
3	11490.00	52.76	-1.24	54.00	38.20	40.10	9.74	35.28 Average
4	11490.00	64.46	-9.54	74.00	49.90	40.10	9.74	35.28 Peak
5	17235.00	60.78	-7.42	68.20	42.89	41.05	11.93	35.09 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5785
N _{TX}	2	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8936.00	52.58	-15.62	68.20	42.70	37.32	8.30	35.74	Peak
2	11570.00	47.04	-6.96	54.00	32.63	39.93	9.79	35.31	Average
3	11570.00	57.98	-16.02	74.00	43.57	39.93	9.79	35.31	Peak
4	17355.00	60.79	-7.41	68.20	42.57	41.44	11.92	35.14	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5785
N_{TX}	2	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	7496.00	39.51	-14.49	54.00	30.69	36.59	7.67	35.44	Average
2	7496.00	51.84	-22.16	74.00	43.02	36.59	7.67	35.44	Peak
3	11570.00	52.71	-1.29	54.00	38.30	39.93	9.79	35.31	Average
4	11570.00	64.91	-9.09	74.00	50.50	39.93	9.79	35.31	Peak
5	17355.00	61.91	-6.29	68.20	43.69	41.44	11.92	35.14	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5825
N _{TX}	2	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8969.00	52.61	-15.59	68.20	42.69	37.36	8.31	35.75 Peak
2	11650.00	46.89	-7.11	54.00	32.65	39.74	9.84	35.34 Average
3	11650.00	57.02	-16.98	74.00	42.78	39.74	9.84	35.34 Peak
4	17475.00	61.23	-6.97	68.20	42.69	41.82	11.90	35.18 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5825
N _{TX}	2	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	7369.00	38.97	-15.03	54.00	30.53	36.26	7.61	35.43	Average
2	7369.00	51.14	-22.86	74.00	42.70	36.26	7.61	35.43	Peak
3	11650.00	52.84	-1.16	54.00	38.60	39.74	9.84	35.34	Average
4	11650.00	65.04	-8.96	74.00	50.80	39.74	9.84	35.34	Peak
5	17475.00	62.34	-5.86	68.20	43.80	41.82	11.90	35.18	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5755
N_{TX}	2	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	8265.00	39.72	-14.28	54.00	30.25	36.99	8.14	35.66 Average
2	8265.00	52.16	-21.84	74.00	42.69	36.99	8.14	35.66 Peak
3	11510.00	46.78	-7.22	54.00	32.24	40.08	9.74	35.28 Average
4	11510.00	59.48	-14.52	74.00	44.94	40.08	9.74	35.28 Peak
5	17265.00	62.77	-5.43	68.20	44.81	41.15	11.92	35.11 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5755
N _{TX}	2	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8002.00	52.15	-16.05	68.20	42.58	37.20	8.00	35.63	Peak
2	11510.00	47.49	-6.51	54.00	32.95	40.08	9.74	35.28	Average
3	11510.00	59.54	-14.46	74.00	45.00	40.08	9.74	35.28	Peak
4	17265.00	62.93	-5.27	68.20	44.97	41.15	11.92	35.11	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5795
N _{TX}	2	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	8785.00	52.41	-15.79	68.20	42.70	37.14	8.29	35.72	Peak
2	11590.00	45.90	-8.10	54.00	31.52	39.88	9.82	35.32	Average
3	11590.00	60.07	-13.93	74.00	45.69	39.88	9.82	35.32	Peak
4	17385.00	62.92	-5.28	68.20	44.63	41.53	11.91	35.15	Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5795
N _{TX}	2	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	7985.00	53.23	-14.97	68.20	43.69	37.18	7.98	35.62 Peak
2	11590.00	49.03	-4.97	54.00	34.65	39.88	9.82	35.32 Average
3	11590.00	60.58	-13.42	74.00	46.20	39.88	9.82	35.32 Peak
4	17385.00	63.39	-4.81	68.20	45.10	41.53	11.91	35.15 Peak

Note 1: ">30dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands emission satisfies both the average and peak limits of 15.209, it is not required to satisfy the -27 dBm peak emission limit of 15.407.

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

3.7 Frequency Stability

3.7.1 Frequency Stability Limit

Frequency Stability Limit	
UNII Devices	
☒	In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.
IEEE Std. 802.11n-2009	
☒	The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band and ± 25 ppm maximum for the 2.4 GHz band.


3.7.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method	
☒	Refer as ANSI C63.10, clause 6.8 for frequency stability tests
☒	Frequency stability with respect to ambient temperature
☒	Frequency stability when varying supply voltage
☒	For conducted measurement.
☒	For conducted measurements on devices with multiple transmit chains: Measurements need only to be performed on one of the active transmit chains (antenna outputs)
☐	For radiated measurement. The equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted power level.

3.7.4 Test Setup



3.7.5 Test Result of Frequency Stability

Frequency Stability Result					
Mode		Frequency Stability (ppm)			
Condition	Freq. (MHz)	0 min	2 min	5 min	10 min
T _{20°C} Vmax	5745	-4.0801	-4.2315	-4.1567	-4.0052
T _{20°C} Vmin	5745	-4.0052	-4.0801	-4.2315	-4.2315
T _{50°C} Vnom	5745	6.8773	6.9521	7.0287	6.9521
T _{40°C} Vnom	5745	-0.8320	-0.7554	-0.8320	-0.6806
T _{30°C} Vnom	5745	-3.0983	-3.0235	-2.9469	-2.7955
T _{20°C} Vnom	5745	-4.0052	-4.1567	-4.2315	-4.0052
T _{10°C} Vnom	5745	-3.5527	-3.6275	-3.7023	-3.6275
T _{0°C} Vnom	5745	-1.8138	-1.8886	-1.8138	-1.8886
T _{-10°C} Vnom	5745	0.1514	0.2263	0.3029	0.3029
T _{-20°C} Vnom	5745	2.1166	2.1915	2.2663	2.3429
Limit (ppm)		±20			
Result		Complied			
Note 1: Measure at 85 % [Vmin] and 115 % [Vmax] of the nominal voltage [Vnom].					
Note 2: The nominal voltage refer test report clause 1.1.5 for EUT operational condition.					

4 Test Equipment and Calibration Data

AC Conducted

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Next Calibration Date
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Apr. 15, 2015	Apr. 14, 2016
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	JAN. 22, 2015	JAN. 21, 2016
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9kHz ~ 30MHz	Oct. 31, 2014	Oct. 30, 2015
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	NCR	NCR

RF Conducted

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Next Calibration Date
Spectrum Analyzer	R&S	FSV 40	101500	9KHz~40GHz	May 12, 2016	May 11, 2017
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	-20 ~ 100℃	Jun. 12, 2015	Jun. 11, 2016
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jul. 28, 2015	Jul. 27, 2016

Radiation

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Next Calibration Date
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH09-HY	30MHz ~ 1GHz 3m	May 14, 2016	May 13, 2017
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH09-HY	1GHz ~ 18GHz 3m	Jul. 01, 2015	Jun. 30, 2016
Amplifier	EMC	EMC9135	980232	9kHz ~ 1.0GHz	Jan. 29, 2016	Jan. 28, 2017
Amplifier	Agilent	8449B	3008A02096	1GHz ~ 26.5GHz	Apr.11.2016	Apr.10.2017
Spectrum	KEYSIGHT	N9010A	MY54200885	10Hz ~ 44GHz	Jul. 15, 2015	Jul. 14, 2016
Bilog Antenna & 5dB Attenuator	TESEQ & MTJ	CBL 6111D & MTJ6102	35418	30MHz ~ 1GHz	Mar. 31, 2016	Mar. 30, 2017
Horn Antenna	SCHWARZBECK	BBHA 9120D	BBHA 9120D 1534	1GHz ~ 18GHz	Apr. 22, 2016	Apr. 21, 2017
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170614	18GHz ~ 40GHz	Jan. 04, 2016	Jan. 03, 2017
Amplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz ~ 40GHz	Jun. 02.2015	Jun. 01.2017
Loop Antenna	ROHDE&SCHWARZ	HFH2-Z2	100330	9 kHz~30 MHz	Nov. 10, 2014	Nov. 09, 2016

Appendix A. Test Photos

1. Photographs of Conducted Emissions Test Configuration

FRONT VIEW



REAR VIEW



SIDE VIEW




2. Photographs of Radiated Emissions Test Configuration

For radiated emissions 9kHz~30MHz

FRONT VIEW




REAR VIEW




For radiated emissions 30MHz~1GHz

FRONT VIEW




REAR VIEW




For radiated emissions above 1GHz

FRONT VIEW




REAR VIEW



EUT take a close-up





EUT take a close-up




EUT take a close-up





APPENDIX B. Photographs of EUT











Printed Ant. + USB















Printed Aut +
4pin pin-header









Printed Aut +
4pin wafer con

