

MIC Test Report

Equipment : 802.11abgn USB Module
Brand Name : SparkLAN
Model No. : WUBR-508N
Standard : MIC Certification Rule, Article 2 Paragraph 1 Item 19-3
Category : XW (W52)
Measured Standard : ARIB STD-T71
Frequency Range : 5150 – 5250 MHz
Applicant : SparkLAN Communications, Inc.
Manufacturer : 8F., No.257, Sec. 2, Tiding Blvd., Neihu District,
Taipei City 11493, Taiwan
Operate Mode : Slave without radar detection

The product sample received on Aug. 01, 2013 and completely tested on Feb. 09, 2018. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in MIC Notice No.88 Appendix No.45 and shown compliance with the applicable MIC Ordinance Regulating Radio Equipment Article 49.20 and ARIB STD-71 technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Reviewed by:



Allen Lin



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Support Equipment.....	7
1.3	Testing Applied Standards	8
1.4	Testing Location Information	8
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT	9
2.1	The Worse Case Modulation Configuration	9
2.2	The Worse Case Power Setting Parameter	9
2.3	The Worst Case Measurement Configuration.....	10
2.4	Test Setup Diagram	10
3	TEST RESULT	11
3.1	Frequency Error	11
3.2	Occupied Bandwidth	12
3.3	Antenna Power, Antenna Power Error and EIRP Power	13
3.4	Adjacent Channel Power.....	15
3.5	Transmitter Out-band Emissions.....	16
3.6	Transmitter Spurious Emissions.....	18
3.7	Receiver Spurious Emissions.....	20
3.8	Identification Code.....	21
3.9	Transmission Burst Length.....	22
3.10	Carrier Sense	23
3.11	EUT Construction Protection.....	24
4	TEST EQUIPMENT AND CALIBRATION DATA	26
APPENDIX A. TEST PHOTOS		
APPENDIX B. TEST RESULT		
PHOTOGRAPHS OF EUT v01		



Summary of Test Result

MIC Regulations Requirements				
Report Clause	Ref. Std. Article	Description	Measured	Result
1.1.7	ORE:49.20	Communication Method	half duplex operation	Complied
1.1.7	ORE:49.20	Modulation Method	OFDM	Complied
1.1.7	ORE:49.20	Signal Transmission Rate	refer to type specification	Complied
1.1.1	RLE:6	Frequency Band	refer to RF info.	Complied
3.1	ORE:5	Frequency Error	refer to test data within 20ppm	Complied
3.2	ORE:6	Occupied Bandwidth	refer to test data	Complied
3.3	ORE:49.20	Antenna Power, EIRP Power	refer to test data	Complied
3.3	ORE:14	Antenna Power Error	refer to test data	Complied
3.4	ORE:49.20	Adjacent Channel Power	refer to test data	Complied
3.5	ORE:49.20	Transmitter Out-band Emissions	refer to test data	Complied
3.6	ORE:7, Table 3	Transmitter Spurious Emissions	refer to test data	Complied
3.7	ORE:24	Receiver Spurious Emissions	refer to test data	Complied
3.8	TR:9	Identification Code	48 bits	Complied
3.9	ORE:49.20	Transmission Burst Length	<4ms	Complied
3.10	TR:9	Carrier Sense	refer to test data	Complied
3.11	ORE:49.20	EUT Construction Protection	Shielded Case	Complied
-	ORE:49.20	Transmit Power Control (TPC)	n/a or W53 > 3dB	N/A
-	NT No.368,2011	DFS – Master Device	refer to test data	N/A
RLE: Radio Law Enforcement Regulations ORE: Ordinance Regulating Radio Equipment TR: Terminal and Other Equipment Regulations NT: Notification of the Ministry of Internal Affairs and Communications				

1 General Description

1.1 Information

1.1.1 Frequency Band

Frequency Band	
<input checked="" type="checkbox"/>	(20MHz) - 5180, 5200, 5220, 5240 MHz
<input checked="" type="checkbox"/>	(40MHz) - 5190, 5230MHz
<input type="checkbox"/>	(80MHz) - 5210MHz

1.1.2 RF General Information

RF General Information for Category XW (W52)						
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	Antenna Power (mW/MHz)	EIRP (mW/MHz)
5150-5250	a	5180-5240	36-48 [4]	1	1.75	8.08690
5150-5250	n (HT20)	5180-5240	36-48 [4]	2	1.69	7.79625
5150-5250	n (HT40)	5190-5230	38-46 [2]	2	0.77	3.52951

Note 1: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.3 Antenna Information

Antenna Category	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input checked="" type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)

Antenna General Information					
No.	Ant. Cat.	Ant. Type	Brand	Model	Gain (dBi)
1	External	Dipole	Lct	FDE_ACBSMA-BGP	5.00
2	Integral	Printed	SparkLAN	WUBR-508N	6.64
3	Integral	PCB	NISSEI	FML2.4WA-200	0.42
4	Integral	PCB	SANAV	GEPH-013	1.90
5	External	Dipole	VOXMICRO LTD GROUP	WAND2DBI	2.69

1.1.4 Type of EUT

Identify EUT	
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.:
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.:
<input type="checkbox"/>	Other:

1.1.5 EUT Operational Condition

Supply Voltage	<input type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> System	<input type="checkbox"/> Battery

1.1.6 Table for Existing Change

This product is an extension of original one reported under Sporton project number: JR373103-01XW

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Add Dipole antenna (WAND2DBI)	N/A

1.1.7 Type Specifications

No. 3 Type Specifications				
1	Communication Method	Semi-duplex		
2	Transmitter	(1) Rated Output	Refer test report clause 1.1.2 antenna power	
		(2) Freq. Range of Radio Wave	Refer test report clause 1.1.1 frequency band	
		(3) Oscillation	Synthesizer with Crystal Oscillation (40MHz) (Zero IF)	
		(4) Modulation	OFDM: D1D (16QAM,64QAM), G1D (BPSK, QPSK) Max. Signal Transmission Rate: 11a = 54 Mbps 11n BW _{ch} 20MHz = 130Mbps (MCS8; N _{ss} =2) BW _{ch} 40MHz = 270Mbps (MCS8; N _{ss} =2)	
3	Manufacturer (Brand) Information	Manufacturer (Brand)	Model Type or Name	Serial Number
		SparkLAN	WUBR-508N	n/a
4	Antenna	Type, Structure, Gain refer antenna report and test report clause 1.1.3.		
5	Classification and Model Name of Auxiliary Equipment	Protection Against Interference Automatic Transmission/reception of ID code (Radio equipment law article 9-4, item 9 is carrier sensing.		
6	Other Type Specifications Items	Other design specifications that are not mentioned under above item 1 to 5 all comply with the technical standard stipulated by the 3rd section of radio law.		
7	Attached Drawing	Radio Equipment System Diagram, Schematic Diagram, Layout		
8	Reference Information	Antenna Impedance : 50Ω		

1.2 Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	Serial No.
1	Notebook	DELL	Inspiron 6400	DoC

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ MIC Ordinance Regulating Radio Equipment Article 49.20
- ◆ MIC Notice No.88 Appendix No.45

1.4 Testing Location Information

Testing Location		
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH06-HY	Shiming	24.6°C / 62%	05/Sep/2013
RF Conducted <For carrier sense>	TH01-HY	Andy	21.5°C / 65.5%	09/Feb/2018

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty			
Test Item		Uncertainty	Limit
Radio frequency		$\pm 8.7 \times 10^{-7}$	$\pm 1 \times 10^{-5}$
RF output power, conducted		± 0.63 dB	± 1.5 dB
RF power radiated		± 2.59 dB	± 6 dB
Spurious emissions, conducted	30 – 1000 MHz	± 0.51 dB	± 3 dB
	1 – 18 GHz	± 0.67 dB	± 3 dB
	18 – 26 GHz	± 0.83 dB	± 3 dB
Spurious emissions, radiated	30 – 1000 MHz	± 2.28 dB	± 6 dB
	1 – 18 GHz	± 2.59 dB	± 6 dB
	18 – 26 GHz	± 2.87 dB	± 6 dB
Temperature		± 0.8 °C	± 1 °C
Humidity		± 3 %	± 5 %
Time		± 1.42 %	± 10 %

2 Test Configuration of EUT

2.1 The Worse Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS
11a,6-54Mbps	1	6-54Mbps	6Mbps
HT20, M8-15	2	M8-15	M8
HT40, M8-15	2	M8-15	M8

2.2 The Worse Case Power Setting Parameter


The Worst Case Power Setting Parameter						
Test Software Version	RT5x7xQA V1.0.5.9					
Modulation Mode	N _{TX}	Test Frequency (MHz)				
		NCB: 20MHz			NCB: 40MHz	
		5180	5200	5240	5190	5230
11a,6-54Mbps	1	25	25	27	-	-
HT20, M8-15	2	25 / 24	25 / 24	2A / 26	-	-
HT40, M8-15	2	-	-	-	26 / 24	28 / 25

2.3 The Worst Case Measurement Configuration

Tests Item	Frequency Error
Test Condition	Conducted measurement at transmit chains.
Modulation Mode	Un-modulation

Tests Item	Occupied Bandwidth, Antenna Power, Antenna Power Error, EIRP Power, Adjacent Channel Power, Transmitter Out-band Emissions, Transmitter Spurious Emissions, Receiver Spurious Emissions, Transmission Burst Length, Identification Code, Carrier Sense,
Test Condition	Conducted measurement at transmit chains.
Modulation Mode	11a, HT20, HT40

2.4 Test Setup Diagram



3 Test Result

3.1 Frequency Error

3.1.1 Frequency Error Limit

Frequency Error Limit
$\leq \pm 20$ ppm


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.45, clause 3.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.45, clause 3.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.45, clause 3.4
Presentation of Results	MIC Notice No.88 Appendix No.45, clause 3.5
Other Conditions	MIC Notice No.88 Appendix No.45, clause 3.6

3.1.4 Test Setup



3.1.5 Test Result of Frequency Error

Appendix	Mode	Item
B	Un-modulation	2

3.2 Occupied Bandwidth

3.2.1 Occupied Bandwidth Limit

Occupied Bandwidth Limit
(BW _{ch} 20MHz)[W52/W53] - ≤ 19MHz(OFDM, DSSS);
(BW _{ch} 20MHz)[W52/W53] - ≤ 18MHz(Other);
(BW _{ch} 20MHz) [W56] - ≤ 19.7MHz (OFDM, DSSS, Other);
(BW _{ch} 40MHz) - ≤ 38MHz (OFDM);
(BW _{ch} 80MHz) - ≤ 78MHz (OFDM);
(BW _{ch} 160MHz - contiguous) - ≤ 158MHz (OFDM)
(BW _{ch} 80+80MHz - non-contiguous) - ≤ 78MHz (OFDM)


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.45, clause 4.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.45, clause 4.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.45, clause 4.4
Presentation of Results	MIC Notice No.88 Appendix No.45, clause 4.5
Other Conditions	MIC Notice No.88 Appendix No.45, clause 4.6

3.2.4 Test Setup



3.2.5 Test Result of Occupied Bandwidth

Appendix	Mode	Item
B	11a, HT20, HT40	2

3.3 Antenna Power, Antenna Power Error and EIRP Power

3.3.1 Antenna Power, Antenna Power Error and EIRP Power Limit

Antenna Power Limit (mW/MHz)
(BW _{ch} 20MHz) - ≤10; (BW _{ch} 40MHz) - ≤5; (BW _{ch} 80MHz) - ≤2.5; (BW _{ch} 160MHz) - ≤1.25;

Antenna Power Error Limit (%)
+20% ~ -80%

EIRP Limit (mW/MHz)
(BW _{ch} 20MHz) - ≤10 ; (BW _{ch} 40MHz) - ≤5 ; (BW _{ch} 80MHz) - ≤2.5 ; (BW _{ch} 160MHz) - ≤1.25


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.45, clause 6.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.45, clause 6.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.45, clause 6.4
Presentation of Results	MIC Notice No.88 Appendix No.45, clause 6.5
Other Conditions	MIC Notice No.88 Appendix No.45, clause 6.6

3.3.4 Test Setup



3.3.5 Test Result of Antenna Power, Antenna Power Error and EIRP Power

Appendix	Mode	Item
B	11a, HT20, HT40	2, 3

3.4 Adjacent Channel Power

3.4.1 Adjacent Channel Power Limit

Adjacent Channel Power Limit
(BW _{ch} 20MHz & CP/OBW≤18MHz) - fc±20MHz ≥25dB; fc±40MHz ≥40dB
(BW _{ch} 20MHz & CP/OBW≤19MHz) - fc±20MHz ≥25dB; fc±40MHz ≥40dB
(BW _{ch} 40MHz & CP/OBW≤38MHz) - fc±40MHz ≥25dB; fc±80MHz ≥40dB
(BW _{ch} 80MHz & CP/OBW≤78MHz) - fc±80MHz ≥25dB
(BW _{ch} 80+80MHz & CP/OBW≤78MHz) - fc±80MHz ≥25dB
(BW _{ch} 160MHz & CP/OBW≤158MHz) - N/A


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.45, clause 7.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.45, clause 7.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.45, clause 7.4
Presentation of Results	MIC Notice No.88 Appendix No.45, clause 7.5
Other Conditions	MIC Notice No.88 Appendix No.45, clause 7.6

3.4.4 Test Setup



3.4.5 Test Result of Adjacent Channel Power

Appendix	Mode	Item
B	11a, HT20, HT40	2

3.5 Transmitter Out-band Emissions

3.5.1 Transmitter Out-band Emissions Limit

W52 - BW _{ch} 20MHz (OBW≤18MHz)					
Out Band Emissions		EIRP Limit			
Range (MHz)		mW/MHz		dBm/MHz	
5140	5142	0.0025	0.0025	-26	-26
5142	5150	0.015	0.015	-18	-18
5250	5251	1	0.1	0	-10
5251	5260	0.1	0.0158	-10	-18
5260	5266.7	0.0158	0.0025	-18	-26
5266.7	5360	0.0025	0.0025	-26	-26

W52 - BW _{ch} 40MHz					
Out Band Emissions		EIRP Limit			
Range (MHz)		mW/MHz		dBm/MHz	
5100	5141.6	0.0025	0.0025	-26	-26
5141.6	5150	0.015	0.015	-18	-18
5250	5251	0.5	0.05	-3	-13
5251	5270	0.05	0.0079	-13	-21
5270	5278.4	0.0079	0.0025	-21	-26
5278.4	5400	0.0025	0.0025	-26	-26

W52 - BW _{ch} 80MHz					
Out Band Emissions		EIRP Limit			
Range (MHz)		mW/MHz		dBm/MHz	
5020	5123.2	0.0025	0.0025	-26	-26
5123.2	5150	0.015	0.015	-18	-18
5250	5251	0.25	0.025	-6	-16
5251	5290	0.025	0.0040	-16	-24
5290	5296.7	0.0040	0.0025	-24	-26
5296.7	5480	0.0025	0.0025	-26	-26


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.1, clause 1.3
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.1, clause 1.4
Measuring Operation Procedures	MIC Notice No.88 Appendix No.1, clause 1.5
Presentation of Results	MIC Notice No.88 Appendix No.1, clause 1.6

3.5.4 Test Setup



3.5.5 Test Result of Transmitter Out-band Emissions

Appendix	Mode	Item
B	11a, HT20, HT40	2

3.6 Transmitter Spurious Emissions

3.6.1 Transmitter Spurious Emissions Limit

W52 - BW _{ch} 20MHz (OBW≤18MHz)						
Transmitter Spurious Emissions					Limit	
Range (MHz)		Bn (MHz)	2.5xBn	fc (MHz)	uW/MHz	dBm/MHz
30	5140	16	40	5180	2.5	-26
5360	26000	16	40	5320	2.5	-26
W52 - BW _{ch} 40MHz						
Transmitter Spurious Emissions					EIRP Limit	
Range (MHz)		Bn (MHz)	2.5xBn	fc (MHz)	uW/MHz	dBm/MHz
30	5100	36	90	5190	2.5	-26
5400	26000	36	90	5310	2.5	-26
W52 - BW _{ch} 80MHz						
Transmitter Spurious Emissions					Limit	
Range (MHz)		Bn (MHz)	2.5xBn	fc (MHz)	uW/MHz	dBm/MHz
30	5020	76	190	5210	2.5	-26
5480	26000	76	190	5290	2.5	-26


3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.1, clause 1.3
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.1, clause 1.4
Measuring Operation Procedures	MIC Notice No.88 Appendix No.1, clause 1.5
Presentation of Results	MIC Notice No.88 Appendix No.1, clause 1.6

3.6.4 Test Setup





3.6.5 Test Result of Transmitter Spurious Emissions

Appendix	Mode	Item
B	11a, HT20, HT40	2

3.7 Receiver Spurious Emissions

3.7.1 Receiver Spurious Emissions Limit

RX Spurious Emission		Limit			
Range (MHz)		nW		dBm	
30	1000	4	4	-54	-54
1000	26000	20	20	-47	-47


3.7.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.45, clause 8.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.45, clause 8.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.45, clause 8.4
Presentation of Results	MIC Notice No.88 Appendix No.45, clause 8.5
Other Conditions	MIC Notice No.88 Appendix No.45, clause 8.6

3.7.4 Test Setup



3.7.5 Test Result of Receiver Spurious Emissions

Appendix	Mode	Item
B	11a, HT20, HT40	4

3.8 Identification Code

3.8.1 Identification Code Limit

Identification Code Limit
≥ 19 bits


3.8.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.8.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.45, clause 9.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.45, clause 9.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.45, clause 9.4
Presentation of Results	MIC Notice No.88 Appendix No.45, clause 9.5
Other Conditions	MIC Notice No.88 Appendix No.45, clause 9.6

3.8.4 Test Setup



3.8.5 Test Result of Identification Code

Appendix	Mode	Item
B	11a, HT20, HT40	2

3.9 Transmission Burst Length

3.9.1 Transmission Burst Length Limit

Transmission Burst Length Limit
≤ 4msec. (OFDM)


3.9.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.9.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.45, clause 10.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.45, clause 10.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.45, clause 10.4
Presentation of Results	MIC Notice No.88 Appendix No.45, clause 10.5
Other Conditions	MIC Notice No.88 Appendix No.45, clause 10.6

3.9.4 Test Setup



3.9.5 Test Result of Transmission Burst Length

Appendix	Mode	Item
B	11a, HT20, HT40	2

3.10 Carrier Sense

3.10.1 Carrier Sense Limit

Carrier Sense Limit
Stop transmission for interference signal level above 100mV/m (or level at $22.79+Gr-20*\log(f)$ [dBm])


3.10.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.10.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.45, clause 12.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.45, clause 12.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.45, clause 12.4
Presentation of Results	MIC Notice No.88 Appendix No.45, clause 12.5
Other Conditions	MIC Notice No.88 Appendix No.45, clause 12.6

3.10.4 Test Setup



3.10.5 Test Result of Carrier Sense

Appendix	Mode	Item
B	11a, HT20, HT40	2

3.11 EUT Construction Protection

3.11.1 EUT Construction Protection Limit

EUT Construction Protection Limit	
The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily.	

3.11.2 EUT Construction Protection

Refer a test equipment and calibration data table in this test report.

EUT Construction Protection	
Protected Method	Description
Shielding Case	RF and Modulation components are covered with shielding case and this shielding case is soldered

3.11.3 Reference Documents


Photo	Item
Photo 1	

Photo 2





Photo 3





4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Until	Cal. Body
Spectrum Analyzer	R&S	FSP 40	100305	9kHz~40GHz	20/Mar/2013	19/Mar/2014	ETC
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	21/Jun/2013	20/Jun/2014	ETC
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	27/Jun/2013	26/Jun/2014	ETC
Power Sensor	Anritsu	MA2411B	0917017	300MHz ~ 40GHz	02/Feb/2013	01/Feb/2014	ETC
Power Meter	Anritsu	ML2495A	0949003	300MHz ~ 40GHz	02/Feb/2013	01/Feb/2014	ETC

Note: Calibration Interval of instruments listed above is one year.

<For carrier sense>


Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Until	Cal. Body
Spectrum Analyzer	R&S	FSV 40	101515	9kHz~40GHz	08/Dec/2017	07/Dec/2018	R&S
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	27/Jul/2017	26/Jul/2018	R&S
RF Cable-0.2m	HUBER+SUHNER	SUCOFLEX_104	MY10710/4	30MHz ~ 26.5GHz	25/Aug/2017	24/Aug/2018	Sporton


Note: Calibration Interval of instruments listed above is one year.

Appendix A. Test Photos









Appendix B 19-3-11a-G1D(A-Mode)

Sporton No.	JR373103-02
Test Date for other	2013/9/5
Test Date for carrier sense	2018/2/9
Test Location	SPORTON Lab.
Temp. / Humid.	24.6 C / 62%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19-3	Antenna Port	DAC 0	Test Location	SPORTON Lab.
	Type of Emission	G1D / D1D	Model	WUBR-508N	Temp. / Humid.	24.6 C / 62%
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Serial No.	12635W2002256	Test Site	TH06-HY
	Frequency	5180~5240MHz(20MHz Space 4 Channels)	Antenna Power	1.75 mW/MHz	Engineer	Shiming
					Department	Radio Service Group

2. Test Results

Test Voltage		V	Normal Voltage (5V)			Remarks											
Test Frequency		MHz	5180	5200	5240	Low/Mid/High of test frequency range											
Testing for Electrical Specification	Measured Frequency	MHz	5179.9352	5199.9334	5239.9346												
	Frequency Error	ppm	12.51	12.81	12.48	Limit ≤ 20 ppm											
	Occupied Bandwidth	MHz	16.64	16.60	16.60	99% OBW Limit ≤ 19 MHz (RB/VB : 300kHz)											
	Spreading Bandwidth (DSSS only)	MHz	14.56	14.52	14.52	90% of total emission power											
	EIRP Power	mW/MHz	8.08690	7.25742	7.95760	Ant Gain : 6.64 [dBi]											
	Antenna Power (Conducted)	mW/MHz	1.75300	1.57319	1.72497	Limit ≤ 10 mW/MHz - Antenna power & EIRP power											
	Antenna Power Error	Δp	0.00300	-0.17681	-0.02503												
	Power Error Rate	%	0.17	-10.10	-1.43	Limit + 20% - 30%											
	Adjacent Channel Leakage Power	-20MHz	dB	33.52	35.58	34.30	Limit ≥ 25dB (18MHz)										
		+20MHz	dB	33.18	35.68	34.95	Limit ≥ 25dB (18MHz)										
		-40MHz	dB	32.20	32.44	32.94	Limit ≥ 40dB (18MHz)										
		+40MHz	dB	53.97	53.38	57.17	Limit ≥ 40dB (18MHz)										
	Limitation of Collateral Emission of Receiver	< 1GHz	nW	0.0192	0.0323	0.0164	Limit ≤ 4 nW (-54 dBm)										
		≥ 1GHz	nW	0.9419	0.9354	1.2331	Limit ≤ 20 nW (-47 dBm)										
	Transmission Burst Length	msec	2.3000	2.3000	2.3000	Limit ≤ 4msec											
Carrier Sense (100mW/m)	OK / NG	OK	OK	OK	Pin = 22.79+Gr-20*log(freq_MHz) [dBm]												
Radio Interface	ID code	ID code	Good, MAC Address:00-0E-8E-40-89-82														
Prevention Function	Test Frequency (W53)	MHz	-	-	-	Pin = Gr - 62 [dBm]Gr is max receiving antenna gain in dBi											
	DFS function	OK / NG	-	-	-												
	Test Frequency (W53)	MHz	-	-	-	If EIRP power density of EUT is less than 5mW/MHz, without TPC function											
	TPC function	dB	-	-	-												
Testing for Electrical Specification	Unwanted Emission Intensity	W52	Test Frequency	MHz	5180	5200	5240	Low/Mid/High of test frequency range									
			Max value in the band	MHz	5135.00	5135.00	5043.11										
			Raw dBm	dBm	-39.25	-44.26	-43.29	30MHz~5135MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)									
			dBm/MHz	dBm/MHz	-37.00	-42.01	-41.04										
			μW/MHz	μW/MHz	0.19953	0.06295	0.07870										
			Max value in the band	MHz	21955.54	21790.46	21955.54	5365MHz~26000MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)									
			Raw dBm	dBm	-33.41	-33.95	-34.27										
			dBm/MHz	dBm/MHz	-29.73	-30.27	-30.59										
			μW/MHz	μW/MHz	1.06414	0.93972	0.87297										
			Test Frequency	MHz	5180	5200	5240	Low/Mid/High of test frequency range									
			Max value in the band	MHz	5137.17	5135.41	5137.09	5135MHz~5142MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)									
			Raw dBm	dBm	-37.83	-41.96	-43.67										
			dBm/MHz	dBm/MHz	-28.94	-33.07	-34.78	5142MHz~5150MHz Limit ≤ 15 μW/MHz (-18.24 dBm/MHz)									
			μW/MHz	μW/MHz	1.27644	0.49317	0.33266										
			Max value in the band	MHz	5148.90	5146.94	5145.34										
Raw dBm	dBm	-32.19	-39.20	-43.46													
dBm/MHz	dBm/MHz	-23.30	-30.31	-34.57													
μW/MHz	μW/MHz	4.67735	0.93111	0.34914													
Max value in the band	MHz	5250.14	5251.00	5250.00	5250MHz~5251MHz Limit ≤ 1000 - 100 μW/MHz (0 - -10 dBm/MHz)												
Raw dBm	dBm	-43.80	-42.77	-12.13													
dBm/MHz	dBm/MHz	-34.91	-33.88	-3.24	Margin to the technical requirement												
μW/MHz	μW/MHz	0.32285	0.40926	474.24199													
Max value in the band	MHz	5259.30	5252.48	5251.04	5251MHz~5260MHz Limit ≤ 100 - 15.8 μW/MHz (-10 - -18 dBm/MHz)												
Raw dBm	dBm	-35.69	-31.89	-21.20													
dBm/MHz	dBm/MHz	-35.53	-23.92	3.24	Margin to the technical requirement												
μW/MHz	μW/MHz	0.26977	0.64714	7.58578													
Max value in the band	MHz	5265.35	5265.95	5260.00	5260MHz~5266.7MHz Limit ≤ 15.8 - 2.5 μW/MHz (-18 - -26 dBm/MHz)												
Raw dBm	dBm	-44.23	-44.02	-39.91													
dBm/MHz	dBm/MHz	-35.34	-35.13	-31.02													
μW/MHz	μW/MHz	0.29242	0.30690	0.79068													
Max value in the band	MHz	5271.62	5267.09	5267.49	5266.7MHz~5365MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)												
Raw dBm	dBm	-45.15	-44.04	-36.20													
dBm/MHz	dBm/MHz	-36.26	-35.15	-27.31													
μW/MHz	μW/MHz	0.23659	0.30549	1.85780													

Appendix B 19-3-11a-G1D-Power(A-Mode)

3. Antenna Power (Conducted Power)

Test Voltage	V	Normal Voltage (5V)							Remarks
Test Frequency	MHz	5180	5200	5240					
Power Meter Raw (IF of Spectrum)	dBm	-18.26	-18.73	-18.33					
Power Measurement System Loss	dB	21.19	21.19	21.19					Refer to Calibration Result
Transmitter Duty Cycle Factor	dB	0.00	0.00	0.00					Duty Factor = $10 \times 10\log_{10}(1/\text{Duty Cycle})$
Equivalent Noise Bandwidth	MHz	1.12	1.12	1.12					ENB = $\text{Total_Sum}^2 / \text{Peak_Level} * \text{Point_Width}$
Equivalent Noise Bandwidth Factor	dB	0.49	0.49	0.49					ENB Factor = $10 \times 10\log_{10}(1/\text{ENB})$
Antenna Power (Conducted)	dBm/MHz	2.44	1.97	2.37					Limit ≤ 10 mW/MHz (10 dBm/MHz)
Antenna Power (Conducted)	mW/MHz	1.7530	1.5732	1.7250					
Transmitter ON _{Time}	msec				1.0000				RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz
Transmitter (ON+OFF) _{Time}	msec				1.0000				
Transmitter Duty Cycle	%				100.00%				

4. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)							Remarks
Test Frequency	MHz	5180	5200	5240					
Spurious Emission Frequency	※ 1	MHz	844.80	76.56	452.92				1st 30MHz~1000MHz:: Maximum emission and
	※ 1	MHz	-	-	-				2nd all emissions beyond 1/10 of the limitation
	※ 1	MHz	-	-	-				3rd must be indicated.
	※ 2	MHz	21950.00	21950.00	3450.00				1st 1000MHz~26GHz:: Maximum emission and all
	※ 2	MHz	-	-	-				2nd emissions beyond 1/10 of the limitation must
	※ 2	MHz	-	-	-				3rd be indicated.
Cable Loss	※ 1	dB	0.78	0.78	0.78				1st
	※ 1	dB	-	-	-				2nd
	※ 1	dB	-	-	-				3rd
	※ 2	dB	3.68	3.68	3.68				1st
	※ 2	dB	-	-	-				2nd
	※ 2	dB	-	-	-				3rd
Spectrum Raw	※ 1	dBm	-77.95	-75.69	-78.62				1st
	※ 1	dBm	-	-	-				2nd
	※ 1	dBm	-	-	-				3rd
	※ 2	dBm	-63.94	-63.97	-62.77				1st
	※ 2	dBm	-	-	-				2nd
	※ 2	dBm	-	-	-				3rd
Spurious Emission Intensity	※ 1	dBm	-77.17	-74.91	-77.84				1st Limit ≤ 4 nW (-54 dBm)
	※ 1	dBm	-	-	-				2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	dBm	-	-	-				3rd
	※ 2	dBm	-60.26	-60.29	-59.09				1st Limit ≤ 20 nW (-47 dBm)
	※ 2	dBm	-	-	-				2nd RBW : 1 MHz ; VBW : 1 MHz
	※ 2	dBm	-	-	-				3rd
Spurious Emission Intensity	※ 1	nW	0.0192	0.0323	0.0164				Total Emission Power
	※ 1	nW	0.0192	0.0323	0.0164				1st
	※ 1	nW	-	-	-				2nd Limit ≤ 4 nW (-54 dBm)
	※ 1	nW	-	-	-				3rd RBW : 100 kHz ; VBW : 100 kHz
	※ 2	nW	0.9419	0.9354	1.2331				Total Emission Power
	※ 2	nW	0.9419	0.9354	1.2331				1st
※ 2	nW	-	-	-				2nd Limit ≤ 20 nW (-47 dBm)	
※ 2	nW	-	-	-				3rd RBW : 1 MHz ; VBW : 1 MHz	

※ 1: Frequency Band 5 (30 MHz \leq f < 1000 MHz) ※ 2: Frequency Band 6 (1000 MHz \leq f < 26 GHz)

5. Carrier Sense Capability

Test Voltage	V	Normal Voltage (5V)							Remarks
Test Frequency	MHz	5180	5200	5240					
Mini. Antenna Gain	dBi	0.42	0.42	0.42					
Carrier Level	dBm	-51.08	-51.11	-51.18					Pin = $22.79 + Gr - 20 * \log(\text{freq_MHz})$ [dBm]
Result	Good/Fail	Good	Good	Good					

Appendix B 19-3-11n-20M

Sporton No.	JR373103-02
Test Date for other	2013/9/5
Test Date for carrier sense	2018/2/9
Test Location	SPORTON Lab.
Temp. / Humid.	24.6°C / 62%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19-3	Antenna Port	DAC 0	Test Location	SPORTON Lab.
	Type of Emission	G1D / D1D	Model	WUUBR-508N	Temp. / Humid.	24.6°C / 62%
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Serial No.	12635W2002256	Test Site	TH06-HY
	Frequency	5180~5240MHz(20MHz Space 4 Channels)	Antenna Power	0.86 mW/MHz	Engineer	Shiming
					Department	Radio Service Group

2. Test Results

Test Voltage		V	Normal Voltage (5V)			Remarks			
Test Frequency	MHz	5180	5200	5240		Low/Mid/High of test frequency range			
Measured Frequency	MHz	5180.0054	5200.0078	5240.0060					
Frequency Error	ppm	-1.04	-1.50	-1.15		Limit ≤ 20 ppm			
Occupied Bandwidth	MHz	17.52	17.48	17.52		99% OBW Limit ≤ 19 MHz (RB/VB : 300kHz)			
Spreading Bandwidth (DSSS only)	MHz	15.08	15.12	15.08		90% of total emission power			
EIRP Power	mW/MHz	3.71349	3.61228	3.96992		Ant Gain : 6.64 [dBi]			
Antenna Power (Conducted)	mW/MHz	0.80497	0.78304	0.86056		Limit ≤ 10 mW/MHz - Antenna power & EIRP power			
Antenna Power Error	Δp	mW/MHz	-0.05503	-0.07696	0.00056				
Power Error Rate	%		-6.40	-8.95	0.07	Limit + 20% - - 80%			
Adjacent Channel Power	-20MHz	dB	37.10	36.54	35.83	Limit ≥ 25dB (18MHz)			
	+20MHz	dB	38.51	37.36	37.39	Limit ≥ 25dB (18MHz)			
	-40MHz	dB	51.78	52.33	52.04	Limit ≥ 40dB (18MHz)			
	+40MHz	dB	52.40	53.00	52.84	Limit ≥ 40dB (18MHz)			
Limitation of Collateral Emission of Receiver	< 1GHz	nW	0.0183	0.0262	0.0185	Limit ≤ 4 nW (-54 dBm)			
	≥ 1GHz	nW	0.8590	0.8185	3.3554	Limit ≤ 20 nW (-47 dBm)			
Transmission Burst Length	msec		2.3000	2.3000	2.3000	Limit ≤ 4msec			
Radio Interface Prevention Function	Carrier Sense (100mV/m)	OK / NG	OK	OK	OK	Pin = 22.79+Gr-20*log(freq_MHz) [dBm]			
	ID code	ID code	Good, MAC Address:00-0E-8E-40-89-82						
	Test Frequency (W53)	MHz	-	-	-	Pin = Gr - 62 [dBm]Gr is max receiveing antenna gain in dBi			
	DFS function	OK / NG	-	-	-				
	TPC function	dB	-	-	-	If EIRP power density of EUT is less than 5mW/MHz, without TPC function			
Unwanted Emission Intensity	W52	Test Frequency	MHz	5180	5200	5240	Low/Mid/High of test frequency range		
		Max value in the band	MHz	5135.00	5063.53	5012.48			
		Raw dBm	-42.54	-44.12	-43.42		30MHz~5135MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)		
		dBm/MHz	-40.29	-41.87	-41.17				
		μW/MHz	0.09354	0.06501	0.07638				
		Max value in the band	MHz	20634.90	21955.54	21831.73			
		Raw dBm	-33.43	-34.81	-33.99		5365MHz~26000MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)		
		dBm/MHz	-29.75	-31.13	-30.31				
		μW/MHz	1.05925	0.77090	0.93111				
		TPC function	dB	-	-	-			
Out-Band Leakage Power (EIRP)	W52	Test Frequency	MHz	5180	5200	5240	Low/Mid/High of test frequency range		
		Max value in the band	MHz	5141.69	5137.44	5140.80			
			Raw dBm	-43.51	-43.40	-43.37		5135MHz~5142MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)	
			dBm/MHz	-34.62	-34.51	-34.48			
			μW/MHz	0.34514	0.35400	0.35645			
			Max value in the band	MHz	5148.35	5148.00	5142.66		
			Raw dBm	-40.12	-40.95	-43.41		5142MHz~5150MHz Limit ≤ 15 μW/MHz (-18.24 dBm/MHz)	
			dBm/MHz	-31.23	-32.06	-34.52			
			μW/MHz	0.75336	0.62230	0.35318			
			Max value in the band	MHz	5250.14	5250.99	5250.04		
		Raw dBm	-44.68	-43.80	-12.02		5250MHz~5251MHz Limit ≤ 1000 - 100 μW/MHz (0 - -10 dBm/MHz)		
		dBm/MHz	-35.79	-34.91	-3.13				
		μW/MHz	0.26363	0.32285	486.40721				
		dB	34.39	25.01	2.73		Margin to the technical requirement		
		Max value in the band	MHz	5255.48	5252.48	5252.40			
		Raw dBm	-45.03	-42.05	-37.08		5251MHz~5260MHz Limit ≤ 100 - 15.8 μW/MHz (-10 - -18 dBm/MHz)		
		dBm/MHz	-36.14	-33.16	-28.19				
		μW/MHz	0.24322	0.48306	1.51705				
		dB	22.16	21.85	16.94		Margin to the technical requirement		
		Max value in the band	MHz	5266.30	5265.20	5260.52			
	Raw dBm	-44.92	-44.53	-31.18		5260MHz~5266.7MHz Limit ≤ 15.8 - 2.5 μW/MHz (-18 - -26 dBm/MHz)			
	dBm/MHz	-36.03	-35.64	-22.29					
	μW/MHz	0.24946	0.27290	5.90201					
	dB	10.47	11.40	3.66		Margin to the technical requirement			
	Max value in the band	MHz	5295.99	5268.27	5267.88				
	Raw dBm	-45.53	-45.03	-40.58		5266.7MHz~5365MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)			
	dBm/MHz	-36.64	-36.14	-31.69					
	μW/MHz	0.21677	0.24322	0.67764					

Appendix B 19-3-11n-20M-Power

3. Antenna Power (Conducted Power)

Test Voltage	V	Normal Voltage (5V)							Remarks
Test Frequency	MHz	5180	5200	5240					
Power Meter Raw (IF of Spectrum)	dBm	-21.64	-21.76	-21.35					
Power Measurement System Loss	dB	21.19	21.19	21.19					Refer to Calibration Result
Transmitter Duty Cycle Factor	dB	0.00	0.00	0.00					Duty Factor = $10 \times 10\log_{10}(1/Duty\ Cycle)$
Equivalent Noise Bandwidth	MHz	1.12	1.12	1.12					ENB = $Total_Sum^2 / Peak_Level * Point_Width$
Equivalent Noise Bandwidth Factor	dB	0.49	0.49	0.49					ENB Factor = $10 \times 10\log_{10}(1/ENB)$
Antenna Power (Conducted)	dBm/MHz	-0.94	-1.06	-0.65					Limit $\leq 10\ mW/MHz$ (10 dBm/MHz)
Antenna Power (Conducted)	mW/MHz	0.8050	0.7830	0.8606					
Transmitter ON _{Time}	msec	1.0000							RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz
Transmitter (ON+OFF) _{Time}	msec	1.0000							
Transmitter Duty Cycle	%	100.00%							

4. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)							Remarks	
Test Frequency	MHz	5180	5200	5240						
Spurious Emission Frequency	※ 1	MHz	119.24	74.62	738.10				1st	30MHz ~ 1000MHz:: Maximum emission and all emissions beyond 1/10 of the limitation must be indicated.
	※ 1	MHz	-	-	-				2nd	
	※ 1	MHz	-	-	-				3rd	
	※ 2	MHz	3438.00	22000.00	3450.00				1st	1000MHz ~ 26GHz:: Maximum emission and all emissions beyond 1/10 of the limitation must be indicated.
	※ 2	MHz	-	-	21950.00				2nd	
	※ 2	MHz	-	-	21800.00				3rd	
Cable Loss	※ 1	dB	0.78	0.78	0.78				1st	
	※ 1	dB	-	-	-				2nd	
	※ 1	dB	-	-	-				3rd	
	※ 2	dB	3.68	3.68	3.68				1st	
	※ 2	dB	-	-	3.68				2nd	
	※ 2	dB	-	-	3.68				3rd	
Spectrum Raw	※ 1	dBm	-78.15	-76.60	-78.11				1st	
	※ 1	dBm	-	-	-				2nd	
	※ 1	dBm	-	-	-				3rd	
	※ 2	dBm	-64.34	-64.55	-62.51				1st	
	※ 2	dBm	-	-	-63.19				2nd	
	※ 2	dBm	-	-	-64.01				3rd	
Spurious Emission Intensity	※ 1	dBm	-77.37	-75.82	-77.33				1st	Limit $\leq 4\ nW$ (-54 dBm) RBW : 100 kHz ; VBW : 100 kHz
	※ 1	dBm	-	-	-				2nd	
	※ 1	dBm	-	-	-				3rd	
	※ 2	dBm	-60.66	-60.87	-58.83				1st	Limit $\leq 20\ nW$ (-47 dBm) RBW : 1 MHz ; VBW : 1 MHz
	※ 2	dBm	-	-	-59.51				2nd	
	※ 2	dBm	-	-	-60.33				3rd	
Spurious Emission Intensity	※ 1	nW	0.0183	0.0262	0.0185				1st	Total Emission Power
	※ 1	nW	0.0183	0.0262	0.0185				1st	
	※ 1	nW	-	-	-				2nd	Limit $\leq 4\ nW$ (-54 dBm) RBW : 100 kHz ; VBW : 100 kHz
	※ 1	nW	-	-	-				3rd	
	※ 2	nW	0.8590	0.8185	3.3554				1st	Total Emission Power
	※ 2	nW	0.8590	0.8185	1.3092				1st	
※ 2	nW	-	-	1.1194				2nd	Limit $\leq 20\ nW$ (-47 dBm) RBW : 1 MHz ; VBW : 1 MHz	
※ 2	nW	-	-	0.9268				3rd		

※ 1: Frequency Band 5 (30 MHz $\leq f < 1000$ MHz) ※ 2: Frequency Band 6 (1000 MHz $\leq f < 26$ GHz)

5. Carrier Sense Capability

Test Voltage	V	Normal Voltage (5V)							Remarks
Test Frequency	MHz	5180	5200	5240					
Mini. Antenna Gain	dBi	0.42	0.42	0.42					
Carrier Level	dBm	-51.08	-51.11	-51.18					Pin = $22.79 + Gr - 20 * \log(freq_MHz)$ [dBm]
Result	Good/Fail	Good	Good	Good					

Appendix B 19-3-11n-20M

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19-3	Antenna Port	DAC 1	Sporton No.	JR373103-02
	Type of Emission	G1D / D1D	Model	WUBR-508N	Test Date for other	2013/9/5
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Serial No.	12635W2002256	Test Date for carrier sense	2018/2/9
	Frequency	5180~5240MHz(20MHz Space 4 Channels)	Antenna Power	0.83 mW/MHz	Test Location	SPORTON Lab.
				W52	Temp. / Humid.	24.6°C / 62%
				Test Site	TH06-HY	
				Engineer	Shiming	
				Department	Radio Service Group	

2. Test Results

Test Voltage		V			Normal Voltage (5V)																		
Test Frequency		MHz			5180	5200	5240																
Testing for Electrical Specification	Measured Frequency	MHz			5180.0054	5200.0078	5240.0060													Remarks			
	Frequency Error	ppm			-1.04	-1.50	-1.15													Low/Mid/High of test frequency range			
	Occupied Bandwidth	MHz			17.52	17.56	17.52													Limit ≤ 20 ppm			
	Spreading Bandwidth (DSSS only)	MHz			15.20	15.24	15.16													99% OBW Limit ≤ 19 MHz (RB/VB : 300kHz)			
	EIRP Power	mW/MHz			2.86934	3.01149	3.82633													90% of total emission power			
	Antenna Power (Conducted)	mW/MHz			0.62199	0.65280	0.82943													Ant Gain : 6.64 [dBi]			
	Antenna Power Error	Δp			-0.20801	-0.17720	-0.00057																
	Power Error Rate	%			-25.06	-21.35	-0.07																
	Adjacent Channel Power	-20MHz	dB			37.55	38.18	37.21													Limit + 20% - - 80%		
		+20MHz	dB			37.61	37.44	36.85													Limit ≥ 25dB (18MHz)		
-40MHz		dB			51.84	52.40	52.36													Limit ≥ 25dB (18MHz)			
+40MHz		dB			52.64	53.00	52.87													Limit ≥ 40dB (18MHz)			
Limitation of Collateral Emission of Receiver	< 1GHz	nW			0.0155	0.0321	0.0169													Limit ≥ 40dB (18MHz)			
	≥ 1GHz	nW			0.3664	0.7621	3.0754													Limit ≤ 4 nW (-54 dBm)			
Transmission Burst Length	msec			2.3000	2.3000	2.3000													Limit ≤ 20 nW (-47 dBm)				
Radio Interface Prevention Function	Carrier Sense (100mV/m)	OK / NG			OK	OK	OK													Limit ≤ 4msec			
	ID code	ID code			Good, MAC Address:00-0E-8E-40-89-82															Pin = 22.79+Gr-20*log(freq_MHz) [dBm]			
	Test Frequency (W53)	MHz			-	-	-																
	DFS function	OK / NG			-	-	-																
	Test Frequency (W53)	MHz			-	-	-													Pin = Gr - 62 [dBm]Gr is max receiving antenna gain in dBi			
TPC function	dB			-	-	-													If EIRP power density of EUT is less than 5mW/MHz, without TPC function				
Unwanted Emission Intensity	W52	Max value in the band	Test Frequency	MHz			5180	5200	5240										Low/Mid/High of test frequency range				
			MHz	5135.00	4981.85	4941.01																	
		Raw dBm	-43.08			-44.19	-44.32																
		dBm/MHz	-40.83			-41.94	-42.07																
		μW/MHz	0.08260			0.06397	0.06209										30MHz~5135MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)						
	W52	Max value in the band	Test Frequency	MHz			21831.73	21996.81	21749.19														
			MHz	21831.73	21996.81	21749.19																	
		Raw dBm	-33.98			-33.99	-34.12																
		dBm/MHz	-30.30			-30.31	-30.44																
		μW/MHz	0.93325			0.93111	0.90365										5365MHz~26000MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)						
Testing for Electrical Specification	W52	Max value in the band	Test Frequency	MHz			5180	5200	5240										Low/Mid/High of test frequency range				
			MHz	5141.99	5135.24	5141.41																	
			Raw dBm	-42.94			-43.68	-44.43															
			dBm/MHz	-34.05			-34.79	-35.54										5135MHz~5142MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)					
			μW/MHz	0.39355			0.33189	0.27925															
			MHz	5145.25	5148.11	5149.78																	
			Raw dBm	-37.99			-40.63	-43.57															
			dBm/MHz	-29.10			-31.74	-34.68										5142MHz~5150MHz Limit ≤ 15 μW/MHz (-18.24 dBm/MHz)					
			μW/MHz	1.23027			0.66988	0.34041															
			μW/MHz	0.23121			0.43652	350.75187										5250MHz~5251MHz Limit ≤ 1000 - 100 μW/MHz (0 - -10 dBm/MHz)					
	W52	Max value in the band	Test Frequency	MHz			5250.97	5250.95	5250.00														
			MHz	5257.93	5251.90	5251.50																	
			Raw dBm	-45.25			-42.49	-13.44															
			dBm/MHz	-36.36			-33.60	-4.55										5250MHz~5251MHz Limit ≤ 1000 - 100 μW/MHz (0 - -10 dBm/MHz)					
			μW/MHz	0.23121			0.43652	350.75187															
			dB	26.64			24.08	4.55															
			MHz	5257.93	5251.90	5251.50																	
			Raw dBm	-44.97			-41.05	-36.02															
			dBm/MHz	-36.08			-32.16	-27.13										5251MHz~5260MHz Limit ≤ 100 - 15.8 μW/MHz (-10 - -18 dBm/MHz)					
			μW/MHz	0.24660			0.60814	1.93642															
W52	Max value in the band	Test Frequency	MHz			5260.13	5264.48	5260.72										Margin to the technical requirement					
		MHz	5260.13	5264.48	5260.72																		
		Raw dBm	-45.25			-44.09	-29.34																
		dBm/MHz	-36.36			-35.20	-20.45																
		μW/MHz	0.23121			0.30200	9.01571										5260MHz~5266.7MHz Limit ≤ 15.8 - 2.5 μW/MHz (-18 - -26 dBm/MHz)						
		dB	18.20			11.83	1.58																
		MHz	5270.63	5268.08	5267.68																		
		Raw dBm	-45.35			-44.38	-40.64																
		dBm/MHz	-36.46			-35.49	-31.75										Margin to the technical requirement						
		μW/MHz	0.22594			0.28249	0.66834										5266.7MHz~5365MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)						

Appendix B 19-3-11n-20M-Power

3. Antenna Power (Conducted Power)

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5180	5200	5240						
Power Meter Raw (IF of Spectrum)	dBm	-22.76	-22.55	-21.51						
Power Measurement System Loss	dB	21.19	21.19	21.19						Refer to Calibration Result
Transmitter Duty Cycle Factor	dB	0.00	0.00	0.00						Duty Factor = $10 \times 10\text{Log}_{10}(1/\text{Duty Cycle})$
Equivalent Noise Bandwidth	MHz	1.12	1.12	1.12						ENB = $\text{Total_Sum}^2 / \text{Peak_Level} * \text{Point_Width}$
Equivalent Noise Bandwidth Factor	dB	0.49	0.49	0.49						ENB Factor = $10 \times 10\text{Log}_{10}(1/\text{ENB})$
Antenna Power (Conducted)	dBm/MHz	-2.06	-1.85	-0.81						Limit ≤ 10 mW/MHz (10 dBm/MHz)
Antenna Power (Conducted)	mW/MHz	0.6220	0.6528	0.8294						
Transmitter ON _{Time}	msec	1.0000								RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz
Transmitter (ON+OFF) _{Time}	msec	1.0000								
Transmitter Duty Cycle	%	100.00%								

4. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5180	5200	5240						
Spurious Emission Frequency	※ 1	MHz	74.62	72.68	712.88					1st 30MHz ~ 1000MHz:: Maximum emission and
	※ 1	MHz	-	-	-					2nd all emissions beyond 1/10 of the limitation
	※ 1	MHz	-	-	-					3rd must be indicated.
	※ 2	MHz	3438.00	21900.00	21950.00					1st 1000MHz ~ 26GHz:: Maximum emission and all
	※ 2	MHz	-	-	21800.00					2nd emissions beyond 1/10 of the limitation must
	※ 2	MHz	-	-	21250.00					3rd be indicated.
Cable Loss	※ 1	dB	0.78	0.78	0.78					1st
	※ 1	dB	-	-	-					2nd
	※ 1	dB	-	-	-					3rd
	※ 2	dB	3.68	3.68	3.68					1st
	※ 2	dB	-	-	3.68					2nd
	※ 2	dB	-	-	3.68					3rd
Spectrum Raw	※ 1	dBm	-78.87	-75.71	-78.51					1st
	※ 1	dBm	-	-	-					2nd
	※ 1	dBm	-	-	-					3rd
	※ 2	dBm	-68.04	-64.86	-63.13					1st
	※ 2	dBm	-	-	-63.64					2nd
	※ 2	dBm	-	-	-63.99					3rd
Spurious Emission Intensity	※ 1	dBm	-78.09	-74.93	-77.73					1st Limit ≤ 4 nW (-54 dBm)
	※ 1	dBm	-	-	-					2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	dBm	-	-	-					3rd
	※ 2	dBm	-64.36	-61.18	-59.45					1st Limit ≤ 20 nW (-47 dBm)
	※ 2	dBm	-	-	-59.96					2nd RBW : 1 MHz ; VBW : 1 MHz
	※ 2	dBm	-	-	-60.31					3rd
Spurious Emission Intensity	※ 1	nW	0.0155	0.0321	0.0169					Total Emission Power
	※ 1	nW	0.0155	0.0321	0.0169					1st Limit ≤ 4 nW (-54 dBm)
	※ 1	nW	-	-	-					2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	nW	-	-	-					3rd
	※ 2	nW	0.3664	0.7621	3.0754					Total Emission Power
	※ 2	nW	0.3664	0.7621	1.1350					1st Limit ≤ 20 nW (-47 dBm)
※ 2	nW	-	-	1.0093					2nd RBW : 1 MHz ; VBW : 1 MHz	
※ 2	nW	-	-	0.9311					3rd	

※ 1: Frequency Band 5 (30 MHz \leq f < 1000 MHz) ※ 2: Frequency Band 6 (1000 MHz \leq f < 26 GHz)

5. Carrier Sense Capability

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5180	5200	5240						
Mini. Antenna Gain	dBi	0.42	0.42	0.42						
Carrier Level	dBm	-51.08	-51.11	-51.18						Pin = $22.79 + \text{Gr} - 20 * \log(\text{freq_MHz})$ [dBm]
Result	Good/Fail	Good	Good	Good						

Appendix B 19-3-11n-20M

Sporton No.	JR373103-02
Test Date for other	2013/9/5
Test Date for carrier sense	2018/2/9
Test Location	SPORTON Lab.
Temp. / Humid.	24.6°C / 62%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19-3	Antenna Port	DAC 0+DAC 1	Test Location	SPORTON Lab.
	Type of Emission	G1D / D1D	Model	WUBR-508N	Temp. / Humid.	24.6°C / 62%
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Serial No.	12635W2002256	Test Site	TH06-HY
	Frequency	5180~5240MHz(20MHz Space 4 Channels)	Antenna Power	1.69 mW/MHz	Engineer	Shiming
					Department	Radio Service Group

2. Test Results

Test Voltage		V	Normal Voltage (5V)			Remarks							
Test Frequency		MHz	5180	5200	5240	Low/Mid/High of test frequency range							
Testing for Electrical Specification	Measured Frequency	MHz	-	-	-								
	Frequency Error	ppm	-	-	-	Limit ≤ 20 ppm							
	Occupied Bandwidth	MHz	-	-	-	99% OBW Limit ≤ 19 MHz (RB/VB : 300kHz)							
	Spreading Bandwidth (DSSS only)	MHz	-	-	-	90% of total emission power							
	EIRP Power	mW/MHz	6.58283	6.62378	7.79625	Ant Gain : 6.64 [dBi]							
	Antenna Power (Conducted)	mW/MHz	1.42696	1.43584	1.69000	Limit ≤ 10 mW/MHz - Antenna power & EIRP power							
	Antenna Power Error	Δp	-0.26304	-0.25416	0.00000								
	Power Error Rate	%	-15.56	-15.04	0.00	Limit + 20% - 80%							
	Adjacent Channel Power	-20MHz	dB	-	-	-	Limit ≥ 25dB (18MHz)						
		+20MHz	dB	-	-	-	Limit ≥ 25dB (18MHz)						
		-40MHz	dB	-	-	-	Limit ≥ 40dB (18MHz)						
		+40MHz	dB	-	-	-	Limit ≥ 40dB (18MHz)						
	Limitation of Collateral Emission of Receiver	< 1GHz	nW	0.0338	0.0583	0.0354	Limit ≤ 4 nW (-54 dBm)						
		≥ 1GHz	nW	1.2255	1.5805	6.4308	Limit ≤ 20 nW (-47 dBm)						
	Transmission Burst Length	msec	2.3000	2.3000	2.3000	Limit ≤ 4msec							
Radio Interface Prevention Function	Carrier Sense (100mV/m)	OK / NG	OK	OK	OK	Pin = 22.79+Gr-20*log(freq_MHz) [dBm]							
	ID code	ID code	Good, MAC Address:00-0E-8E-40-89-82										
	Test Frequency (W53)	MHz	-	-	-	Pin = Gr - 62 [dBm]Gr is max receiving antenna gain in dBi							
	DFS function	OK / NG	-	-	-								
Unwanted Emission Intensity	Test Frequency	MHz	5180	5200	5240	Low/Mid/High of test frequency range							
	W52	Raw dBm	-	-	-								
		dBm/MHz	-37.54	-38.89	-38.59	30MHz~5135MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)							
	W53	Raw dBm	-	-	-								
dBm/MHz		0.17614	0.12899	0.13847	5365MHz~26000MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)								
Testing for Electrical Specification	Out-Band Leakage Power (EIRP)	W52	Test Frequency	MHz	5180	5200	5240	Low/Mid/High of test frequency range					
			Raw dBm	-	-	-							
		Max value in the band	dBm/MHz	-31.32	-31.64	-31.97	5135MHz~5142MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)						
			μW/MHz	0.73869	0.68589	0.63571							
		W53	Raw dBm	-	-	-							
			dBm/MHz	-27.03	-28.89	-31.59	5142MHz~5150MHz Limit ≤ 15 μW/MHz (-18.24 dBm/MHz)						
		Max value in the band	Raw dBm	-	-	-							
			dBm/MHz	1.98362	1.29218	0.69359							
		W52	Raw dBm	-	-	-							
			dBm/MHz	-33.06	-31.20	-0.77	5250MHz~5251MHz Limit ≤ 1000 - 100 μW/MHz (0 - -10 dBm/MHz)						
		Max value in the band	Raw dBm	-	-	-							
			dBm/MHz	0.49484	0.75937	3.45347	5251MHz~5260MHz Limit ≤ 100 - 15.8 μW/MHz (-10 - -18 dBm/MHz)						
		Max value in the band	Raw dBm	-	-	-							
			dBm/MHz	-33.10	-29.62	-24.62	5260MHz~5266.7MHz Limit ≤ 15.8 - 2.5 μW/MHz (-18 - -26 dBm/MHz)						
		Max value in the band	Raw dBm	-	-	-							
dBm/MHz	0.48982		1.09119	3.45347	5266.7MHz~5365MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)								
Max value in the band	Raw dBm	-	-	-									
	dBm/MHz	-33.54	-32.79	-28.71									
Max value in the band	Raw dBm	-	-	-									
	dBm/MHz	0.44271	0.52571	1.34599									

Appendix B 19-3-11n-20M-Power

3. Antenna Power (Conducted Power)

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5180	5200	5240						
Power Meter Raw (IF of Spectrum)	dBm	-19.15	-19.13	-18.42						
Power Measurement System Loss	dB	21.19	21.19	21.19						Refer to Calibration Result
Transmitter Duty Cycle Factor	dB	0.00	0.00	0.00						Duty Factor = $10 \times 10\text{Log}_{10}(1/\text{Duty Cycle})$
Equivalent Noise Bandwidth	MHz	1.12	1.12	1.12						ENB = $\text{Total_Sum}^2 / \text{Peak_Level} * \text{Point_Width}$
Equivalent Noise Bandwidth Factor	dB	0.49	0.49	0.49						ENB Factor = $10 \times 10\text{Log}_{10}(1/\text{ENB})$
Antenna Power (Conducted)	dBm/MHz	1.54	1.57	2.28						Limit ≤ 10 mW/MHz (10 dBm/MHz)
Antenna Power (Conducted)	mW/MHz	1.4270	1.4358	1.6900						
Transmitter ON _{Time}	msec				1.0000					RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz
Transmitter (ON+OFF) _{Time}	msec				1.0000					
Transmitter Duty Cycle	%				100.00%					

4. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5180	5200	5240						
Spurious Emission Frequency	※ 1	MHz	-	-	-					1st 30MHz ~ 1000MHz:: Maximum emission and
	※ 1	MHz	-	-	-					2nd all emissions beyond 1/10 of the limitation
	※ 1	MHz	-	-	-					3rd must be indicated.
	※ 2	MHz	-	-	-					1st 1000MHz ~ 26GHz:: Maximum emission and all
	※ 2	MHz	-	-	-					2nd emissions beyond 1/10 of the limitation must
	※ 2	MHz	-	-	-					3rd be indicated.
Cable Loss	※ 1	dB	0.78	0.78	0.78					1st
	※ 1	dB	-	-	-					2nd
	※ 1	dB	-	-	-					3rd
	※ 2	dB	3.68	3.68	3.68					1st
	※ 2	dB	-	-	3.68					2nd
	※ 2	dB	-	-	3.68					3rd
Spectrum Raw	※ 1	dBm	-	-	-					1st
	※ 1	dBm	-	-	-					2nd
	※ 1	dBm	-	-	-					3rd
	※ 2	dBm	-	-	-					1st
	※ 2	dBm	-	-	-					2nd
	※ 2	dBm	-	-	-					3rd
Spurious Emission Intensity	※ 1	dBm	-74.70	-72.34	-74.52					1st Limit ≤ 4 nW (-54 dBm)
	※ 1	dBm	-	-	-					2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	dBm	-	-	-					3rd
	※ 2	dBm	-59.12	-58.01	-56.12					1st Limit ≤ 20 nW (-47 dBm)
	※ 2	dBm	-	-	-56.72					2nd RBW : 1 MHz ; VBW : 1 MHz
	※ 2	dBm	-	-	-57.31					3rd
Spurious Emission Intensity	※ 1	nW	0.0338	0.0583	0.0354					Total Emission Power
	※ 1	nW	0.0338	0.0583	0.0354					1st Limit ≤ 4 nW (-54 dBm)
	※ 1	nW	-	-	-					2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	nW	-	-	-					3rd
	※ 2	nW	1.2255	1.5805	6.4308					Total Emission Power
	※ 2	nW	1.2255	1.5805	2.4442					1st Limit ≤ 20 nW (-47 dBm)
※ 2	nW	-	-	2.1287					2nd RBW : 1 MHz ; VBW : 1 MHz	
※ 2	nW	-	-	1.8579					3rd	

※ 1: Frequency Band 5 (30 MHz \leq f < 1000 MHz) ※ 2: Frequency Band 6 (1000 MHz \leq f < 26 GHz)

5. Carrier Sense Capability

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5180	5200	5240						
Mini. Antenna Gain	dBi	0.42	0.42	0.42						
Carrier Level	dBm	-51.08	-51.11	-51.18						Pin = $22.79 + \text{Gr} - 20 * \log(\text{freq_MHz})$ [dBm]
Result	Good/Fail	Good	Good	Good						

Appendix B 19-3-11n-D1D (40MHz mode)

Sporton No.	JR373103-02
Test Date for other	2013/9/5
Test Date for carrier sense	2018/2/9
Test Location	SPORTON Lab.
Temp. / Humid.	24.6 °C / 62%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19-3	Antenna Port	DAC 0
	Type of Emission	G1D / DID	Model	WUBR-508N
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Serial No.	12635W2002256
	Frequency	5190 ~ 5230MHz(40MHz Space 2 Channels)	Antenna Power	0.41 mW/MHz
				W52

2. Test Results

Test Voltage		V	Normal Voltage (5V)				Remarks								
Testing for Electrical Specification	Test Frequency	MHz	5190	5230	-	-	-	-	-	Low/Mid/High of test frequency range					
	Measured Frequency	MHz	5189.9898	5229.9892	-	-	-	-	-						
	Frequency Error	ppm	1.97	2.07	-	-	-	-	-	Limit ≤ 20 ppm					
	Occupied Bandwidth	MHz	36.00	36.00	-	-	-	-	-	99% OBW Limit ≤ 38 MHz (RB/VB : 300kHz)					
	Spreading Bandwidth (DSSS only)	MHz	32.08	32.08	-	-	-	-	-	90% of total emission power					
	EIRP Power	mW/MHz	1.74093	1.87837	-	-	-	-	-	Ant Gain : 6.64 [dBi]					
	Antenna Power (Conducted)	mW/MHz	0.37738	0.40718	-	-	-	-	-	For 40M Limit ≤ 5 mW/MHz - Antenna power & EIRP power					
	Antenna Power Error (Cond.)	Δp	-0.03262	-0.00282	-	-	-	-	-	For W53-40M, EIRP ≤ 2.5mW/MHz, w/o TPC function					
	Power Error Rate (Cond.)	%	-7.96	-0.69	-	-	-	-	-	Limit + 20% - - 80%					
	Adjacent Channel Leakage Power	-40MHz	dB	34.32	33.87	-	-	-	-	-	Limit ≥ 25dB (38MHz)				
		+40MHz	dB	35.80	35.64	-	-	-	-	-	Limit ≥ 25dB (38MHz)				
		-80MHz	dB	48.72	48.73	-	-	-	-	-	Limit ≥ 40dB (38MHz)				
		+80MHz	dB	49.86	50.28	-	-	-	-	-	Limit ≥ 40dB (38MHz)				
	Limitation of Collateral Emission of Receiver	< 1GHz	nW	0.0178	0.0170	-	-	-	-	-	Limit ≤ 4 nW (-54 dBm)				
		≥ 1GHz	nW	0.8790	0.9863	-	-	-	-	-	Limit ≤ 20 nW (-47 dBm)				
Transmission Burst Length	msec	2.3000	2.3000	-	-	-	-	-	Limit ≤ 4msec						
Radio Interface Prevention Function	Carrier Sense (100mV/m)	OK / NG	OK	OK	-	-	-	-	-	Pin = 22.79+Gr-20*log(freq_MHz) [dBm]					
	ID code	ID code	Good, MAC Address:00-0E-8E-40-89-82												
	Test Frequency (W53)	MHz	-	-	-	-	-	-	-	Pin = Gr - 62 [dBm]Gr is max receiving antenna gain in dBi					
	DFS function	OK / NG	-	-	-	-	-	-	-	For W53-40M, EIRP ≤ 2.5mW/MHz, w/o TPC function					
Testing for Electrical Specification	Unwanted Emission Intensity	W52	Test Frequency	MHz	5190	5230	-	-	-	-	Low/Mid/High of test frequency range				
			Max value in the band	MHz	5089.86	5008.74	-	-	-	-	-	30MHz~5100MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)			
		Raw dBm		-40.44	-42.73	-	-	-	-	-					
		dBm/MHz	-44.98	-45.33	-	-	-	-	-						
		μW/MHz	0.09036	0.05333	-	-	-	-	-						
		W53	Max value in the band	MHz	21838.80	21838.80	-	-	-	-	-	5400MHz~26000MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)			
				Raw dBm	-34.79	-35.13	-	-	-	-	-				
		dBm/MHz	-31.11	-31.45	-	-	-	-	-						
		μW/MHz	0.77446	0.71614	-	-	-	-	-						
		Testing for Electrical Specification	Out-Band Leakage Power (EIRP)	W52	Test Frequency	MHz	5190	5230	-	-	-	-	Low/Mid/High of test frequency range		
					Max value in the band	MHz	5139.98	5127.47	-	-	-	-	-	5100MHz~5142MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)	
						Raw dBm	49.83	-41.45	-	-	-	-	-		
						dBm/MHz	-40.94	-32.56	-	-	-	-	-		
					μW/MHz	0.08054	0.55463	-	-	-	-	-			
					Max value in the band	MHz	5148.87	5148.72	-	-	-	-	-	5142MHz~5150MHz Limit ≤ 15 μW/MHz (-18.24 dBm/MHz)	
Raw dBm	-43.52					-43.79	-	-	-	-	-				
dBm/MHz	-34.63					-34.90	-	-	-	-	-				
μW/MHz	0.34435				0.32359	-	-	-	-	-					
Max value in the band	MHz				5250.03	5250.01	-	-	-	-	-	5250MHz~5251MHz Limit ≤ 500 - 50 μW/MHz (-3 - -13 dBm/MHz)			
	Raw dBm				-42.61	-18.65	-	-	-	-	-				
	dBm/MHz				-33.72	-9.76	-	-	-	-	-				
μW/MHz	0.40458				2.17771	-	-	-	-	-					
Max value in the band	dB				20.52	13.61	-	-	-	-	-	Margin to the technical requirement			
	MHz				5271.58	5270.09	-	-	-	-	-	5270MHz~5275.8MHz Limit ≤ 7.924 - 2.547 μW/MHz (-21 - -25.9 dBm/MHz)			
	Raw dBm	-45.82	-45.27	-	-	-	-	-							
dBm/MHz	-36.93	-36.38	-	-	-	-	-								
μW/MHz	0.20277	0.23014	-	-	-	-	-								
dB	14.58	15.29	-	-	-	-	-	Margin to the technical requirement							
Max value in the band	MHz	5293.19	5275.80	-	-	-	-	-	5275.8MHz~5400MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)						
	Raw dBm	-45.34	-47.48	-	-	-	-	-							
	dBm/MHz	-36.45	-38.59	-	-	-	-	-							
μW/MHz	0.22646	0.13836	-	-	-	-	-								

Appendix B 19-3-11n-D1D-Power (40MHz mode)

3. Antenna Power (Conducted Power)

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230							
Power Meter Raw (IF of Spectrum)	dBm	-24.93	-24.60							
Power Measurement System Loss	dB	21.19	21.19							Refer to Calibration Result
Transmitter Duty Cycle Factor	dB	0.00	0.00							Duty Factor = $10 \times 10\text{Log}_{10}(1/\text{Duty Cycle})$
Equivalent Noise Bandwidth	MHz	1.12	1.12							ENB = $\text{Total_Sum}^2 / \text{Peak_Level} * \text{Point_Width}$
Equivalent Noise Bandwidth Factor	dB	0.49	0.49							ENB Factor = $10 \times 10\text{Log}_{10}(1/\text{ENB})$
Antenna Power (Conducted)	dBm/MHz	-4.23	-3.90							Limit ≤ 5 mW/MHz (7 dBm/MHz)
Antenna Power (Conducted)	mW/MHz	0.3774	0.4072							
Transmitter ON _{Time}	msec	1.0000						RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz		
Transmitter (ON+OFF) _{Time}	msec	1.0000								
Transmitter Duty Cycle	%	100.00%								

4. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230							
Spurious Emission Frequency	※ 1	MHz	138.64	134.76						1st 30MHz ~ 1000MHz:: Maximum emission and
	※ 1	MHz	-	-						2nd all emissions beyond 1/10 of the limitation
	※ 1	MHz	-	-						3rd must be indicated.
	※ 2	MHz	24800.00	3450.00						1st 1000MHz ~ 26GHz:: Maximum emission and all
	※ 2	MHz	-	-						2nd emissions beyond 1/10 of the limitation must
	※ 2	MHz	-	-						3rd be indicated.
Cable Loss	※ 1	dB	0.78	0.78						1st
	※ 1	dB	-	-						2nd
	※ 1	dB	-	-						3rd
	※ 2	dB	3.68	3.68						1st
	※ 2	dB	-	-						2nd
	※ 2	dB	-	-						3rd
Spectrum Raw	※ 1	dBm	-78.28	-78.48						1st
	※ 1	dBm	-	-						2nd
	※ 1	dBm	-	-						3rd
	※ 2	dBm	-64.24	-63.74						1st
	※ 2	dBm	-	-						2nd
	※ 2	dBm	-	-						3rd
Spurious Emission Intensity	※ 1	dBm	-77.50	-77.70						1st Limit ≤ 4 nW (-54 dBm)
	※ 1	dBm	-	-						2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	dBm	-	-						3rd
	※ 2	dBm	-60.56	-60.06						1st Limit ≤ 20 nW (-47 dBm)
	※ 2	dBm	-	-						2nd RBW : 1 MHz ; VBW : 1 MHz
	※ 2	dBm	-	-						3rd
Spurious Emission Intensity	※ 1	nW	0.0178	0.0170						Total Emission Power
	※ 1	nW	0.0178	0.0170						1st Limit ≤ 4 nW (-54 dBm)
	※ 1	nW	-	-						2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	nW	-	-						3rd
	※ 2	nW	0.8790	0.9863						Total Emission Power
	※ 2	nW	0.8790	0.9863						1st Limit ≤ 20 nW (-47 dBm)
※ 2	nW	-	-						2nd RBW : 1 MHz ; VBW : 1 MHz	
※ 2	nW	-	-						3rd	

※ 1: Frequency Band 5 (30 MHz \leq f < 1000 MHz) ※ 2: Frequency Band 6 (1000 MHz \leq f < 26 GHz)

5. Carrier Sense Capability

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230							
Mini. Antenna Gain	dBi	0.42	0.42							
Carrier Level	dBm	-51.09	-51.16							Pin = $22.79 + \text{Gr} - 20 * \log(\text{freq_MHz})$ [dBm]
Result	Good/Fail	Good	Good							

Appendix B 19-3-11n-D1D (40MHz mode)

Sporton No.	JR373103-02
Test Date for other	2013/9/5
Test Date for carrier sens	2018/2/9
Test Location	SPORTON Lab.
Temp. / Humid.	24.6°C / 62%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19-3	Antenna Port	DAC 1	Test Location	SPORTON Lab.
	Type of Emission	G1D / D1D	Model	WUBR-508N	Temp. / Humid.	24.6°C / 62%
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Serial No.	12635W2002256	Test Site	TH06-HY
	Frequency	5190~5230MHz(40MHz Space 2 Channels)	Antenna Power	0.37 mW/MHz	Engineer	Shiming
					Department	Radio Service Group

2. Test Results

Test Voltage		V		Normal Voltage (5V)						Remarks		
Testing for Electrical Specification	Test Frequency	MHz	5190	5230	-						Low/Mid/High of test frequency range	
	Measured Frequency	MHz	5189.9898	5229.9892								
	Frequency Error	ppm	1.97	2.07							Limit ≤ 20 ppm	
	Occupied Bandwidth	MHz	36.08	36.00							99% OBW Limit ≤ 38 MHz (RB/VB : 300kHz)	
	Spreading Bandwidth (DSSS only)	MHz	32.32	32.32							90% of total emission power	
	EIRP Power	mW/MHz	1.70130	1.65113							Ant Gain : 6.64 [dBi]	
	Antenna Power (Conducted)	mW/MHz	0.36879	0.35792							For 40M Limit ≤ 5 mW/MHz - Antenna power & EIRP power	
	Power Error Rate (Cond.)	Δp	-0.00121	-0.01208							For W53-40M, EIRP ≤ 2.5mW/MHz, w/o TPC function	
	Power Error Rate (Cond.)	%	-0.33	-3.27							Limit + 20% - - 80%	
	Adjacent Channel Leakage Power	-40MHz	dB	34.95	35.37							Limit ≥ 25dB (38MHz)
		+40MHz	dB	34.71	35.21							Limit ≥ 25dB (38MHz)
		-80MHz	dB	48.75	48.75							Limit ≥ 40dB (38MHz)
		+80MHz	dB	49.86	49.69							Limit ≥ 40dB (38MHz)
		Limitation of Collateral Emission of Receiver	nW	0.0231	0.0191							Limit ≤ 4 nW (-54 dBm)
	Transmission Burst Length	msec	2.3000	2.3000							Limit ≤ 4msec	
Radio Interface Prevention Function	Carrier Sense (100mV/m)	OK / NG	OK	OK							Pin = 22.79+Gr-20*log(freq_MHz) [dBm]	
	ID code	ID code	Good, MAC Address:00-0E-8E-40-89-82									
	Test Frequency (W53)	MHz	-	-							Pin = Gr - 62 [dBm]Gr is max receiveing antenna gain in dBi	
	TPC function	dB	-	-							For W53-40M, EIRP ≤ 2.5mW/MHz, w/o TPC function	
Unwanted Emission Intensity	W52	Test Frequency	MHz	5190	5230	-					Low/Mid/High of test frequency range	
		Max value in the band	MHz	3203.82	4958.04							30MHz~5100MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)
	W52	Raw dBm	-42.25	-43.12								5400MHz~26000MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)
		dBm/MHz	0.05957	0.04875								
		Raw dBm	-34.95	-34.69								
		dBm/MHz	-31.27	-31.01								
Out-Band Leakage Power (EIRP)	W52	Test Frequency	MHz	5190	5230	-						Low/Mid/High of test frequency range
		Max value in the band	MHz	5111.83	5126.80							
		Raw dBm	-47.38	-43.44								5100MHz~5142MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)
		dBm/MHz	-38.49	-34.55								
		Raw dBm	-40.49	-44.52								5142MHz~5150MHz Limit ≤ 15 μW/MHz (-18.24 dBm/MHz)
		dBm/MHz	-31.60	-35.63								
	W52	Max value in the band	MHz	5250.09	5250.01							
		Raw dBm	-44.50	-19.31								5250MHz~5251MHz Limit ≤ 500 - 50 μ W/MHz (-3 - -13 dBm/MHz)
		dBm/MHz	-35.61	-10.42								
		Raw dBm	-44.64	-36.24								Margin to the technical requirement
		dBm/MHz	-35.75	-27.35								5251MHz~5270MHz Limit ≤ 50 - 7.924 μ W/MHz (-13 - -21 dBm/MHz)
		Raw dBm	-46.08	-47.91								Margin to the technical requirement
W52	Max value in the band	MHz	5272.38	5272.48								
	Raw dBm	-37.19	-39.02								5270MHz~5275.8MHz Limit ≤ 7.924 - 2.547 μ W/MHz (-21 - -25.9 dBm/MHz)	
	dBm/MHz	-37.19	-39.02									
	Raw dBm	-45.49	-47.55								Margin to the technical requirement	
	dBm/MHz	-36.60	-38.66								5275.8MHz~5400MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)	
	Raw dBm	-45.49	-47.55									

Appendix B 19-3-11n-D1D-Power (40MHz mode)

3. Antenna Power (Conducted Power)

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230							
Power Meter Raw (IF of Spectrum)	dBm	-25.03	-25.16							
Power Measurement System Loss	dB	21.19	21.19							Refer to Calibration Result
Transmitter Duty Cycle Factor	dB	0.00	0.00							Duty Factor = $10 \times 10\log_{10}(1/\text{Duty Cycle})$
Equivalent Noise Bandwidth	MHz	1.12	1.12							ENB = $\text{Total_Sum}^2 / \text{Peak_Level} * \text{Point_Width}$
Equivalent Noise Bandwidth Factor	dB	0.49	0.49							ENB Factor = $10 \times 10\log_{10}(1/\text{ENB})$
Antenna Power (Conducted)	dBm/MHz	-4.33	-4.46							Limit ≤ 5 mW/MHz (7 dBm/MHz)
Antenna Power (Conducted)	mW/MHz	0.3688	0.3579							
Transmitter ON _{Time}	msec	1.0000						RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz		
Transmitter (ON+OFF) _{Time}	msec	1.0000								
Transmitter Duty Cycle	%	100.00%								

4. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230	-						
Spurious Emission Frequency	※ 1	MHz	961.20	672.14						1st 30MHz ~ 1000MHz:: Maximum emission and
	※ 1	MHz	-	-						2nd all emissions beyond 1/10 of the limitation
	※ 1	MHz	-	-						3rd must be indicated.
	※ 2	MHz	21800.00	21800.00						1st 1000MHz ~ 26GHz:: Maximum emission and all
	※ 2	MHz	-	-						2nd emissions beyond 1/10 of the limitation must
	※ 2	MHz	-	-						3rd be indicated.
Cable Loss	※ 1	dB	0.78	0.78						1st
	※ 1	dB	-	-						2nd
	※ 1	dB	-	-						3rd
	※ 2	dB	3.68	3.68						1st
	※ 2	dB	-	-						2nd
	※ 2	dB	-	-						3rd
Spectrum Raw	※ 1	dBm	-77.14	-77.96						1st
	※ 1	dBm	-	-						2nd
	※ 1	dBm	-	-						3rd
	※ 2	dBm	-64.36	-64.47						1st
	※ 2	dBm	-	-						2nd
	※ 2	dBm	-	-						3rd
Spurious Emission Intensity	※ 1	dBm	-76.36	-77.18						1st Limit ≤ 4 nW (-54 dBm)
	※ 1	dBm	-	-						2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	dBm	-	-						3rd
	※ 2	dBm	-60.68	-60.79						1st Limit ≤ 20 nW (-47 dBm)
	※ 2	dBm	-	-						2nd RBW : 1 MHz ; VBW : 1 MHz
	※ 2	dBm	-	-						3rd
Spurious Emission Intensity	※ 1	nW	0.0231	0.0191						Total Emission Power
	※ 1	nW	0.0231	0.0191						1st Limit ≤ 4 nW (-54 dBm)
	※ 1	nW	-	-						2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	nW	-	-						3rd
	※ 2	nW	0.8551	0.8337						Total Emission Power
	※ 2	nW	0.8551	0.8337						1st Limit ≤ 20 nW (-47 dBm)
※ 2	nW	-	-						2nd RBW : 1 MHz ; VBW : 1 MHz	
※ 2	nW	-	-						3rd	

※ 1: Frequency Band 5 (30 MHz \leq f < 1000 MHz) ※ 2: Frequency Band 6 (1000 MHz \leq f < 26 GHz)

5. Carrier Sense Capability

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230							
Mini. Antenna Gain	dBi	0.42	0.42							
Carrier Level	dBm	-51.09	-51.16							Pin = $22.79 + Gr - 20 * \log(\text{freq_MHz})$ [dBm]
Result	Good/Fail	Good	Good							

Appendix B 19-3-11n-D1D (40MHz mode)

Sporton No.	JR373103-02
Test Date for other	2013/9/5
Test Date for carrier sens	2018/2/9
Test Location	SPORTON Lab.
Temp. / Humid.	24.6°C / 62%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19-3	Antenna Port	DAC 0+DAC 1	Test Location	SPORTON Lab.
	Type of Emission	G1D / D1D	Model	WUBR-508N	Temp. / Humid.	24.6°C / 62%
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Serial No.	12635W2002256	Test Site	TH06-HY
	Frequency	5190~5230MHz(40MHz Space 2 Channels)	Antenna Power	0.77 mW/MHz	Engineer	Shiming
				W52	Department	Radio Service Group

2. Test Results

Test Voltage		V	Normal Voltage (5V)			Remarks			
Testing for Electrical Specification	Test Frequency	MHz	5190	5230	-	Low/Mid/High of test frequency range			
	Measured Frequency	MHz	-	-	-				
	Frequency Error	ppm	-	-	-	Limit ≤ 20 ppm			
	Occupied Bandwidth	MHz	-	-	-	99% OBW Limit ≤ 38 MHz (RB/VB : 300kHz)			
	Spreading Bandwidth (DSSS only)	MHz	-	-	-	90% of total emission power			
	EIRP Power	mW/MHz	3.44224	3.52951	-	Ant Gain : 6.64 [dBi]			
	Antenna Power (Conducted)	mW/MHz	0.74618	0.76509	-	For 40M Limit ≤ 5 mW/MHz - Antenna power & EIRP power			
	Power Error Rate (Cond.)	∅p	-0.02382	-0.00491	-	For W53-40M, EIRP ≤ 2.5mW/MHz, w/o TPC function			
	Power Error Rate (Cond.)	%	-3.09	-0.64	-	Limit + 20% - - 80%			
	Adjacent Channel Leakage Power	-40MHz	dB	-	-	-	Limit ≥ 25dB (38MHz)		
		+40MHz	dB	-	-	-	Limit ≥ 25dB (38MHz)		
		-80MHz	dB	-	-	-	Limit ≥ 40dB (38MHz)		
		+80MHz	dB	-	-	-	Limit ≥ 40dB (38MHz)		
Limitation of Collateral Emission of Receiver	< 1GHz	nW	0.0409	0.0361	-	Limit ≤ 4 nW (-54 dBm)			
	≥ 1GHz	nW	1.7341	1.8200	-	Limit ≤ 20 nW (-47 dBm)			
Transmission Burst Length	msec	2.3000	2.3000	-	Limit ≤ 4msec				
Radio Interface Prevention Function	Carrier Sense (100mV/m)	OK / NG	OK	OK	-	Pin = 22.79+Gr-20*log(freq_MHz) [dBm]			
	ID code	ID code	Good, MAC Address:00-0E-8E-40-89-82						
	Test Frequency (W53)	MHz	-	-	-	Pin = Gr - 62 [dBm]Gr is max receiveing antenna gain in dBi			
	DFS function	OK / NG	-	-	-	For W53-40M, EIRP ≤ 2.5mW/MHz, w/o TPC function			
Testing for Electrical Specification	Unwanted Emission Intensity	W52	Test Frequency	MHz	5190	5230	-	Low/Mid/High of test frequency range	
			Max value in the band	MHz	-	-	-		
	Out-Band Leakage Power (EIRP)	W52	Max value in the band	Raw dBm	-38.24	-39.91	-	30MHz~5100MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)	
				dBm/MHz	-38.24	-39.91	-		
		Raw dBm	-28.18	-28.21	-	5400MHz~26000MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)			
		dBm/MHz	-28.18	-28.21	-				
		Raw dBm	-36.53	-30.43	-	5100MHz~5142MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)			
		dBm/MHz	-36.53	-30.43	-				
		Raw dBm	-29.85	-32.24	-	5142MHz~5150MHz Limit ≤ 15 μW/MHz (-18.24 dBm/MHz)			
		dBm/MHz	-29.85	-32.24	-				
		Raw dBm	-31.55	-7.07	-	5250MHz~5251MHz Limit ≤ 500 - 50 μW/MHz (-3 - -13 dBm/MHz)			
		dBm/MHz	-31.55	-7.07	-				
	Raw dBm	-31.74	-23.96	-	5251MHz~5270MHz Limit ≤ 50 - 7.924 μW/MHz (-13 - -21 dBm/MHz)				
dBm/MHz	-31.74	-23.96	-						
Raw dBm	-34.05	-34.49	-	5270MHz~5275.8MHz Limit ≤ 7.924 - 2.547 μW/MHz (-21 - -25.9 dBm/MHz)					
dBm/MHz	-34.05	-34.49	-						
Raw dBm	-33.51	-35.61	-	5275.8MHz~5400MHz Limit ≤ 2.5 μW/MHz (-26 dBm/MHz)					
dBm/MHz	-33.51	-35.61	-						

Appendix B 19-3-11n-D1D-Power (40MHz mode)

3. Antenna Power (Conducted Power)

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230							
Power Meter Raw (IF of Spectrum)	dBm	-21.97	-21.86							
Power Measurement System Loss	dB	21.19	21.19							Refer to Calibration Result
Transmitter Duty Cycle Factor	dB	0.00	0.00							Duty Factor = $10 \times 10\log_{10}(1/Duty\ Cycle)$
Equivalent Noise Bandwidth	MHz	1.12	1.12							ENB = $Total_Sum^2 / Peak_Level * Point_Width$
Equivalent Noise Bandwidth Factor	dB	0.49	0.49							ENB Factor = $10 \times 10\log_{10}(1/ENB)$
Antenna Power (Conducted)	dBm/MHz	-1.27	-1.16							Limit $\leq 5\ mW/MHz$ (7 dBm/MHz)
Antenna Power (Conducted)	mW/MHz	0.7462	0.7651							
Transmitter ON _{Time}	msec	1.0000								RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz
Transmitter (ON+OFF) _{Time}	msec	1.0000								
Transmitter Duty Cycle	%	100.00%								

4. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230	-						
Spurious Emission Frequency	※ 1	MHz	-	-	-					1st 30MHz ~ 1000MHz:: Maximum emission and
	※ 1	MHz	-	-	-					2nd all emissions beyond 1/10 of the limitation
	※ 1	MHz	-	-	-					3rd must be indicated.
	※ 2	MHz	-	-	-					1st 1000MHz ~ 26GHz:: Maximum emission and all
	※ 2	MHz	-	-	-					2nd emissions beyond 1/10 of the limitation must
	※ 2	MHz	-	-	-					3rd be indicated.
Cable Loss	※ 1	dB	0.78	0.78	-					1st
	※ 1	dB	-	-	-					2nd
	※ 1	dB	-	-	-					3rd
	※ 2	dB	3.68	3.68	-					1st
	※ 2	dB	-	-	-					2nd
	※ 2	dB	-	-	-					3rd
Spectrum Raw	※ 1	dBm	-	-	-					1st
	※ 1	dBm	-	-	-					2nd
	※ 1	dBm	-	-	-					3rd
	※ 2	dBm	-	-	-					1st
	※ 2	dBm	-	-	-					2nd
	※ 2	dBm	-	-	-					3rd
Spurious Emission Intensity	※ 1	dBm	-73.88	-74.42	-					1st Limit $\leq 4\ nW$ (-54 dBm)
	※ 1	dBm	-	-	-					2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	dBm	-	-	-					3rd
	※ 2	dBm	-57.61	-57.40	-					1st Limit $\leq 20\ nW$ (-47 dBm)
	※ 2	dBm	-	-	-					2nd RBW : 1 MHz ; VBW : 1 MHz
	※ 2	dBm	-	-	-					3rd
Spurious Emission Intensity	※ 1	nW	0.0409	0.0361	-					Total Emission Power
	※ 1	nW	0.0409	0.0361	-					1st Limit $\leq 4\ nW$ (-54 dBm)
	※ 1	nW	-	-	-					2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 1	nW	-	-	-					3rd
	※ 2	nW	1.7341	1.8200	-					Total Emission Power
	※ 2	nW	1.7341	1.8200	-					1st Limit $\leq 20\ nW$ (-47 dBm)
※ 2	nW	-	-	-					2nd RBW : 1 MHz ; VBW : 1 MHz	
※ 2	nW	-	-	-					3rd	

※ 1: Frequency Band 5 (30 MHz $\leq f < 1000$ MHz) ※ 2: Frequency Band 6 (1000 MHz $\leq f < 26$ GHz)

5. Carrier Sense Capability

Test Voltage	V	Normal Voltage (5V)								Remarks
Test Frequency	MHz	5190	5230							
Mini. Antenna Gain	dBi	0.42	0.42							
Carrier Level	dBm	-51.09	-51.16							Pin = $22.79 + Gr - 20 * \log(freq_MHz)$ [dBm]
Result	Good/Fail	Good	Good							

Power Supply Voltage Fluctuation Test

Voltage Fluctuation Test	Normal Voltage	High Voltage + 10% of Normal Voltage	Low Voltage - 10% of Normal Voltage
Input DC Power	5	5.5	4.5
Output DC Power	3.26	3.27	3.25
Voltage Variation (%)	-	0.306748	-0.306748

Note: Voltage Variation (%) = (Output High or Low Voltage - Output Normal Voltage)/Output Normal Voltage X 100
 During the input supply voltage to the EUT from the external power source is varied by +/- 10%, if output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/- 1%. Exempt extremely high and low supply voltage condition tests, EUT only operated in normal voltage to test all regulations.

Calibration Result

1. Linearity Check

SG Output (dBm)	Spectrum Raw (dBm)	Power Meter Raw (dBm)	Remark
0	-0.86	0.01	<ul style="list-style-type: none"> • SG Test Frequency : 2450 MHz • RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz • ATT(30dB) ; Ref : 20 dBm
-5	-5.73	-4.91	
-10	-10.77	-9.89	
0	-1.54	-0.1	<ul style="list-style-type: none"> • SG Test Frequency : 5250 MHz • RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz • ATT(30dB) ; Ref : 20 dBm
-5	-6.44	-5.03	
-10	-11.43	-9.99	

2. Frequency Accuracy Confirmation

SG Output (dBm)	Spectrum Raw (MHz)	Frequency Error (ppm)	Remark
2450	2450.0012	0.4898	<ul style="list-style-type: none"> • SG Output : 0dBm • RBW : 30 kHz ; VBW : 30 kHz ; SP : 300kHz • Limit \leq 10% of frequency error limits
5250	5250.0036	0.6857	

3. Cable Loss

SG Output (MHz)	Power Meter Raw Without Cable (dBm)	Power Meter Raw With Cable (dBm)	Cable Loss (dB)	Remark
1000	0.23	-0.55	0.78	<ul style="list-style-type: none"> • SG Output : 0dBm
2450	-0.01	-1.35	1.34	
5250	-0.11	-2.36	2.25	
12500	-0.99	-4.67	3.68	
26000	-2.63	-16.56	13.93	

4. Power Measurement System Loss (EUT Output to IF Output of Spectrum)

SG Output (MHz)	Spectrum Raw (dBm)	Power Meter Raw With Cable form IF (dBm)	System Path Loss EUT to IF (dB)	Remark
2450	-1.29	-20.5	20.49	<ul style="list-style-type: none"> • SG : 10 dBm • RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz • ATT(30dB) ; Ref : 20 dBm
5250	-2.1	-21.3	21.19	