

MIC Test Report

Equipment : 802.11abgn USB Module
Brand Name : SparkLAN
Model No. : WUBR-508N
Standard : MIC Certification Rule, Article 2 Paragraph 1 Item 19
Category : WW
Measured Standard : ARIB STD-T66
Frequency Range : 2400 – 2483.5 MHz
Applicant : SparkLAN Communications, Inc.
Manufacturer : 8F., No.257, Sec. 2, Tiding Blvd., Neihu
District, Taipei City 11493, Taiwan

The product sample received on Aug. 01, 2013 and completely tested on Sep. 05, 2013. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in MIC Notice No.88 Appendix No.43 and shown compliance with the applicable MIC Ordinance Regulating Radio Equipment Article 49.20 and ARIB STD-66 technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Wayne Hsu / Assistant Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Support Equipment.....	8
1.3	Testing Applied Standards	8
1.4	Testing Location Information.....	8
1.5	Measurement Uncertainty	9
2	TEST CONFIGURATION OF EUT	10
2.1	The Worse Case Modulation Configuration	10
2.2	The Worse Case Power Setting Parameter	10
2.3	The Worst Case Measurement Configuration.....	11
2.4	Test Setup Diagram	11
3	TEST RESULT	12
3.1	Frequency Error	12
3.2	Occupied Bandwidth, Spread Bandwidth and Spread Factor	13
3.3	Antenna Power, Antenna Power Error	14
3.4	Antenna Beamwidth and EIRP Limit	15
3.5	Radiated EIRP (For EIRP \geq Antenna Power Limit +2.14 dBi).....	17
3.6	Transmitter Spurious Emissions.....	19
3.7	Receiver Spurious Emissions.....	20
3.8	Identification Code.....	21
3.9	Carrier Sense	22
3.10	EUT Construction Protection.....	23
4	TEST EQUIPMENT AND CALIBRATION DATA	25
APPENDIX B. PHOTOGRAPHS OF EUT		
APPENDIX C. TEST RESULT		

Summary of Test Result

MIC Regulations Requirements				
Report Clause	Ref. Std. Article	Description	Measured	Result
1.1.5	ORE:49.20	Communication Method	half duplex operation	Complied
1.1.5	ORE:49.20	Modulation Method	OFDM, DSSS	Complied
1.1.5	n/a	Signal Transmission Rate	refer to type specification	Complied
1.1.1	RLE:6	Frequency Band	refer to RF info.	Complied
3.1	ORE:5	Frequency Error	refer to test data within 50ppm	Complied
3.2	ORE:6	Occupied Bandwidth	refer to test data	Complied
3.2	ORE:49.20	Spread Bandwidth / Factor	refer to test data	Complied
3.3	ORE:49.20	Antenna Power	refer to test data	Complied
3.3	ORE:14	Antenna Power Error	refer to test data within +20~-80%	Complied
3.4	ORE:49.20	Antenna Beamwidth, EIRP Limit	refer to test data	Complied
3.5	ORE:49.20	Radiated EIRP* ¹	refer to test data	n/a
3.6	ORE:7, Table 3	Transmitter Spurious Emissions	refer to test data	Complied
3.7	ORE:24	Receiver Spurious Emissions	refer to test data	Complied
3.8	TR:9	Identification Code	48 bits	Complied
3.9	TR:9	Carrier Sense* ²	refer to test data	Complied
3.10	ORE:49.20	EUT Construction Protection	Shielded Case	Complied
<p>RLE: Radio Law Enforcement Regulations ORE: Ordinance Regulating Radio Equipment TR: Terminal and Other Equipment Regulations NT: Notification of the Ministry of Internal Affairs and Communications *¹: If EIRP < (Antenna Power Limit +2.14 dBi), Radiated EIRP test could be exempted. *²: If OFDM modulation and Occupied Bandwidth ≥ 26MHz, Carrier Sense shall be performed.</p>				



SPORTON INTERNATIONAL INC.
TEL : 886-3-327-3456
FAX : 886-3-327-0973

1 General Description

1.1 Information

1.1.1 RF General Information

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number	Transmit Chains (N _{TX})	Antenna Power (mW/MHz)
2400-2483.5	b	2412-2472	1-13 [13]	1	5.10
2400-2483.5	g	2412-2472	1-13 [13]	1	2.21
2400-2483.5	n (HT20)	2412-2472	1-13 [13]	2	2.45
2400-2483.5	n (HT40)	2422-2462	3-11 [9]	2	1.19
Note 1: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.					
Note 2: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.					

1.1.2 Antenna Information

Antenna Category	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input checked="" type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)

Antenna General Information					
No.	Ant. Cat.	Ant. Type	Brand	Model	Gain (dBi)
1	External	Dipole	Lct	FDE_ACBSMA-BGP	3
2	Integral	Printed	SparkLAN	WUBR-508N	3.79

1.1.3 Type of EUT

Identify EUT	
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.:
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.:
<input type="checkbox"/>	Other:

1.1.4 EUT Operational Condition

Supply Voltage	<input type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> System	<input type="checkbox"/> Battery

1.1.5 Type Specifications

No. 3 Type Specifications			
1 Communication Method	Semi-duplex		
2 Transmitter	(1) Rated Output	Refer test report clause 1.1.1 antenna power	
	(2) Freq. Range of Radio Wave	Refer test report clause 1.1.1 frequency band and channel	
	(3) Oscillation	Synthesizer with Crystal Oscillation (40MHz) (Zero IF)	
	(4) Modulation	DSSS: G1D (BPSK, QPSK, CCK) OFDM: D1D (16QAM, 64QAM), G1D (BPSK, QPSK) Max. Signal Transmission Rate: 11b = 11 Mbps 11g = 54 Mbps 11n BW _{ch} 20MHz = 130 Mbps (MCS8; N _{ss} =2) BW _{ch} 40MHz = 270 Mbps (MCS8; N _{ss} =2)	
3 Manufacturer (Brand) Information	Manufacturer (Brand)	Model Type or Name	Serial Number
	SparkLAN	WUBR-508N	n/a
4 Antenna	Type, Structure, Gain refer antenna report and test report clause 1.1.2.		
5 Classification and Model Name of Auxiliary Equipment	Protection Against Interference Automatic Transmission/reception of ID code (Radio equipment law article 9-4, item 9 is carrier sensing.		
6 Other Type Specifications Items	Other design specifications that are not mentioned under above item 1 to 5 all comply with the technical standard stipulated by the 3rd section of radio law.		
7 Attached Drawing	Radio Equipment System Diagram, Schematic Diagram, Layout		
8 Reference Information	Antenna Impedance : 50Ω Occupied frequency bandwidth wider than 26MHz and narrower than 38MHz, whether the carrier sense function.		

1.2 Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	Serial No.
1	Notebook	DELL	Inspiron 6400	DoC

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- MIC Ordinance Regulating Radio Equipment Article 49.20
- MIC Notice No.88 Appendix No.43

1.4 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973		
Test Condition		Test Site No.	Test Engineer	Test Date
RF Conducted		TH06-HY	Shiming	Sep. 04, 2013 ~ Sep. 05, 2013

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty			
Test Item		Uncertainty	Limit
Radio frequency		$\pm 8.7 \times 10^{-7}$	$\pm 1 \times 10^{-5}$
RF output power, conducted		± 0.63 dB	± 1.5 dB
RF power radiated		± 2.59 dB	± 6 dB
conducted	30 – 1000 MHz	± 0.51 dB	± 3 dB
	1 – 18 GHz	± 0.67 dB	± 3 dB
	18 – 26 GHz	± 0.83 dB	± 3 dB
radiated	30 – 1000 MHz	± 2.28 dB	± 6 dB
	1 – 18 GHz	± 2.59 dB	± 6 dB
	18 – 26 GHz	± 2.87 dB	± 6 dB
Temperature		± 0.8 °C	± 1 °C
Humidity		± 3 %	± 5 %
Time		± 1.42 %	± 10 %

2 Test Configuration of EUT

2.1 The Worse Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS
11b,1-11Mbps	1	1-11Mbps	11Mbps
11g,6-54Mbps	1	6-54Mbps	6Mbps
HT20,M8-15	2	M8-15	M8
HT40,M8-15	2	M8-15	M8

Note 1: Modulation modes consist of below configuration:
 11b: IEEE 802.11b, 11g: IEEE 802.11g, HT20/HT40: IEEE 802.11n, VHT20/VHT40: IEEE 802.11ac
 Note 2: IEEE Std. 802.11n/ac modulation consists of HT20, HT40. Then EUT support HT20, HT40.
 Worst modulation mode: HT20, HT40. Worst modulation of Guard Interval (GI) is 800ns.

2.2 The Worse Case Power Setting Parameter

The Worst Case Power Setting Parameter							
Test Software Version	RT5x7xQA V1.0.5.9						
Modulation Mode	N _{TX}	Test Frequency (MHz)					
		NCB: 20MHz			NCB: 40MHz		
		2412	2442	2472	2422	2437	2462
11b,1-11Mbps	1	18	18	18	-	-	-
11g,6-54Mbps	1	16	16	17	-	-	-
HT20,M8-15	2	16,1B	17,1C	17,1D	-	-	-
HT40,M8-15	2	-	-	-	17,1B	17,1C	18,1D


2.3 The Worst Case Measurement Configuration

Tests Item	Frequency Error
Test Condition	Conducted measurement at transmit chains.
Modulation Mode	Un-modulation

Tests Item	Occupied Bandwidth, Spread Bandwidth, Spread Factor, Antenna Power, Antenna Power Error, EIRP Power, Transmitter Spurious Emissions, Receiver Spurious Emissions, Identification Code, Carrier Sense
Test Condition	Conducted measurement at transmit chains.
Modulation Mode	11b, 11g, HT20, HT40

Tests Item	Antenna Beamwidth
Test Condition	Radiated measurement
Modulation Mode	11b, 11g, HT20, HT40

2.4 Test Setup Diagram



3 Test Result

3.1 Frequency Error

3.1.1 Frequency Error Limit

Frequency Error Limit
$\leq \pm 50$ ppm


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.43, clause 3.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.43, clause 3.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.43, clause 3.4
Presentation of Results	MIC Notice No.88 Appendix No.43, clause 3.5
Other Conditions	MIC Notice No.88 Appendix No.43, clause 3.6

3.1.4 Test Setup



3.1.5 Test Result of Frequency Error

Appendix	Mode	Item
C	Un-modulation	2

3.2 Occupied Bandwidth, Spread Bandwidth and Spread Factor

3.2.1 Occupied Bandwidth Limit

Occupied Bandwidth Limit	
FHSS	83.5 MHz
FHSS + DSSS	83.5 MHz
FHSS + OFDM	83.5 MHz
OFDM	38 MHz
Other	26 MHz

Spread Bandwidth and Spread Factor Limit	
Spread Bandwidth	≥500kHz
Spread Factor	≥5


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.43, clause 4.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.43, clause 4.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.43, clause 4.4
Presentation of Results	MIC Notice No.88 Appendix No.43, clause 4.5
Other Conditions	MIC Notice No.88 Appendix No.43, clause 4.6

3.2.4 Test Setup



3.2.5 Test Result of Occupied Bandwidth / Spread Bandwidth / Spread Factor

Appendix	Mode	Item
C	11b, 11g, HT20, HT40	2,9

3.3 Antenna Power, Antenna Power Error

3.3.1 Antenna Power and Antenna Power Error Limit

Antenna Power Limit (mW/MHz)
$\leq 3\text{mW/MHz}$ (FHSS, FHSS+DSSS, FHSS+OFDM from 2427~2470.75 MHz) $\leq 10\text{mW/MHz}$ (DSSS from 2400~2483.5MHz) $\leq 10\text{mW/MHz}$ (OFDM from 2400~2483.5MHz) – [OBW \leq 26MHz] $\leq 5\text{mW/MHz}$ (OFDM from 2400~2483.5MHz) – [26MHz<OBW \leq 38MHz] $\leq 10\text{mW}$ (Other from 2400~2483.5MHz)

Antenna Power Error Limit (%)
+20% ~ -80%


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.43, clause 6.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.43, clause 6.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.43, clause 6.4
Presentation of Results	MIC Notice No.88 Appendix No.43, clause 6.5
Other Conditions	MIC Notice No.88 Appendix No.43, clause 6.6

3.3.4 Test Setup



3.3.5 Test Result of Antenna Power and Antenna Power Error

Appendix	Mode	Item
C	11b, 11g, HT20, HT40	2, 3

3.4 Antenna Beamwidth and EIRP Limit

3.4.1 EIRP and Antenna Beamwidth Limit

Antenna Beamwidth Limit
$\leq 360/A$; $A = \text{EIRP}[\text{mW/MHz}]/4.91$ (FHSS, FHSS+DSSS, FHSS+OFDM form 2427 - 2470.75 MHz) $\leq 360/A$; $A = \text{EIRP}[\text{mW/MHz}]/16.37$ (DSSS from 2400~2483.5MHz) $\leq 360/A$; $A = \text{EIRP}[\text{mW/MHz}]/16.37$ (OFDM from 2400~2483.5MHz) – [OBW \leq 26MHz] $\leq 360/A$; $A = \text{EIRP}[\text{mW/MHz}]/8.18$ (OFDM from 2400~2483.5MHz) – [26MHz<OBW \leq 38MHz] $\leq 360/A$; $A = \text{EIRP}[\text{mW}]/16.37$ (Other from 2400~2483.5MHz)

Max. EIRP Limit for Antenna Beamwidth $\leq 10^\circ$
$\leq 16.91\text{dBm/MHz}$ (FHSS, FHSS+DSSS, FHSS+OFDM form 2427~2470.75 MHz) $\leq 22.14\text{dBm/MHz}$ (DSSS from 2400~2483.5MHz) $\leq 22.14\text{dBm/MHz}$ (OFDM from 2400~2483.5MHz) – [OBW \leq 26MHz] $\leq 19.14\text{dBm/MHz}$ (OFDM from 2400~2483.5MHz) – [26MHz<OBW \leq 38MHz] $\leq 22.14\text{dBm}$ (Other from 2400~2483.5MHz)


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.43, clause 11.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.43, clause 11.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.43, clause 11.4
Presentation of Results	MIC Notice No.88 Appendix No.43, clause 11.5
Other Conditions	MIC Notice No.88 Appendix No.43, clause 11.6

3.4.4 Test Setup



3.4.5 Test Result of Antenna Beamwidth

Appendix	Mode	Item
C	11b, 11g, HT20, HT40	4

3.5 Radiated EIRP (For EIRP \geq Antenna Power Limit +2.14 dBi)

3.5.1 EIRP and Antenna Beamwidth Limit

Antenna Beamwidth Limit
$\leq 360^\circ$; $A = \text{EIRP}[\text{mW/MHz}] / 4.91$ (FHSS, FHSS+DSSS, FHSS+OFDM form 2427 - 2470.75 MHz)
$\leq 360^\circ$; $A = \text{EIRP}[\text{mW/MHz}] / 16.37$ (DSSS from 2400~2483.5MHz)
$\leq 360^\circ$; $A = \text{EIRP}[\text{mW/MHz}] / 16.37$ (OFDM from 2400~2483.5MHz) – [OBW \leq 26MHz]
$\leq 360^\circ$; $A = \text{EIRP}[\text{mW/MHz}] / 8.18$ (OFDM from 2400~2483.5MHz) – [26MHz<OBW \leq 38MHz]
$\leq 360^\circ$; $A = \text{EIRP}[\text{mW/MHz}] / 16.37$ (Other from 2400~2483.5MHz)

Max. EIRP Limit for Antenna Beamwidth $\leq 10^\circ$
$\leq 16.91\text{dBm/MHz}$ (FHSS, FHSS+DSSS, FHSS+OFDM form 2427~2470.75 MHz)
$\leq 22.14\text{dBm/MHz}$ (DSSS from 2400~2483.5MHz)
$\leq 22.14\text{dBm/MHz}$ (OFDM from 2400~2483.5MHz) – [OBW \leq 26MHz]
$\leq 19.14\text{dBm/MHz}$ (OFDM from 2400~2483.5MHz) – [26MHz<OBW \leq 38MHz]
$\leq 22.14\text{dBm}$ (Other from 2400~2483.5MHz)


3.5.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.43, clause 10.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.43, clause 10.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.43, clause 10.4
Presentation of Results	MIC Notice No.88 Appendix No.43, clause 10.5
Other Conditions	MIC Notice No.88 Appendix No.43, clause 10.6
If EIRP < Antenna Power Limit +2.14 dBi, radiated EIRP test could be exempted.	

3.5.4 Test Setup



Radiated EIRP - Used SG and Std. Antenna Substitution

3.5.5 Test Result of Radiated EIRP

Appendix	Mode	Item
C	-	-

3.6 Transmitter Spurious Emissions

3.6.1 Transmitter Spurious Emissions Limit

Transmitter Spurious Emissions		Limit	
Range (MHz)		uW/MHz	dBm/MHz
30	2387	2.5	-26
2387	2400	25	-16
2483.5	2496.5	25	-16
2496.5	12500	2.5	-26


3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.1, clause 1.3
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.1, clause 1.4
Measuring Operation Procedures	MIC Notice No.88 Appendix No.1, clause 1.5
Presentation of Results	MIC Notice No.88 Appendix No.1, clause 1.6

3.6.4 Test Setup



3.6.5 Test Result of Transmitter Spurious Emissions

Appendix	Mode	Item
C	11b, 11g, HT20, HT40	6

3.7 Receiver Spurious Emissions

3.7.1 Receiver Spurious Emissions Limit

RX Spurious Emission		Limit			
Range (MHz)		nW		dBm	
30	1000	4	4	-54	-54
1000	12500	20	20	-47	-47


3.7.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.43, clause 7.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.43, clause 7.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.43, clause 7.4
Presentation of Results	MIC Notice No.88 Appendix No.43, clause 7.5
Other Conditions	MIC Notice No.88 Appendix No.43, clause 7.6

3.7.4 Test Setup



3.7.5 Test Result of Receiver Spurious Emissions

Appendix	Mode	Item
C	11b, 11g, HT20, HT40	7

3.8 Identification Code

3.8.1 Identification Code Limit

Identification Code Limit
≤ 48 bits


3.8.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.8.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.43, clause 12.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.43, clause 12.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.43, clause 12.4
Presentation of Results	MIC Notice No.88 Appendix No.43, clause 12.5
Other Conditions	MIC Notice No.88 Appendix No.43, clause 12.6

3.8.4 Test Setup



3.8.5 Test Result of Identification Code

Appendix	Mode	Item
C	11b, 11g, HT20, HT40	2

3.9 Carrier Sense

3.9.1 Carrier Sense Limit

Carrier Sense Limit
Stop transmission for interference signal level above 100mV/m (or level at $22.79 + Gr - 20 \cdot \log(f)$ [dBm])


3.9.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.9.3 Test Procedures

Test Method	
Measuring Equipment Conditions	MIC Notice No.88 Appendix No.43, clause 8.2
Conditions of Equipment under Test	MIC Notice No.88 Appendix No.43, clause 8.3
Measuring Operation Procedures	MIC Notice No.88 Appendix No.43, clause 8.4
Presentation of Results	MIC Notice No.88 Appendix No.43, clause 8.5
Other Conditions	MIC Notice No.88 Appendix No.43, clause 8.6

3.9.4 Test Setup



3.9.5 Test Result of Carrier Sense

Appendix	Mode	Item
C	HT40	8

3.10 EUT Construction Protection

3.10.1 EUT Construction Protection Limit

EUT Construction Protection Limit	
The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily.	

3.10.2 EUT Construction Protection

Refer a test equipment and calibration data table in this test report.

EUT Construction Protection	
Protected Method	Description
Shielding Case	RF and Modulation components are covered with shielding case and this shielding case is soldered

3.10.3 Reference Documents


Photo	Item
Photo 1	

Photo 2





Photo 3



4 Test Equipment and Calibration Data


Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP 40	100305	9KHz~40GHz	Mar. 20, 2013	Conducted
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Jun. 21, 2013	Conducted
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jun. 27, 2013	Conducted
Power Sensor	Anritsu	MA2411B	0917017	300MHz ~ 40GHz	Feb. 02, 2013	Conducted
Power Meter	Anritsu	ML2495A	0949003	300MHz ~ 40GHz	Feb. 02, 2013	Conducted


Note: Calibration Interval of instruments listed above is one year.

Appendix A. Test Photos

















APPENDIX B Photographs of EUT


























Printed Ant. +4pin wafer con

















MIC Test Report



































lpex+4pin wafer con










MIC Test Report



Appendix C 19-11b-G1D(20MHz Mode)

Sporton No.	JR373103
Test Date	2013/9/5
Test Location	SPORTON Lab.
Temp. / Humid.	24.6℃ / 62%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19	Model	WUJBR-508N	Temp. / Humid.	24.6℃ / 62%
	Type of Emission	G1D	Serial No.	12635W2002256	Test Site	TH06-HY
	Modulation Type	DSSS: BPSK, QPSK, CCK	Antenna Power	5.10 mW/MHz	Engineer	Shiming
	Frequency	2412~2472 MHz	Antenna Port	DAC 0	Department	Radio Service Group

2. Test Results

Test Voltage		Normal Voltage (5V)			Remarks				
Test Frequency	MHz	2412	2442	2472					Low/Mid/High of test frequency range
Measured Frequency	MHz	2411.9700	2441.9682	2471.9676					
Frequency Error	ppm	-12.44	-13.02	-13.11					Limit ≤ 50 ppm
Occupied Bandwidth	MHz	14.36	14.36	14.32					Limit ≤ 26 MHz (RB/NB : 300kHz)
Spread-spectrum Bandwidth	MHz	10.60	10.60	10.56					Spread Factor Limit ≥ 5 (DSSS and FHSS)
Unwanted Emission Intensity (Power emission within 1MHz bandwidth)	※ 1	μW	0.08472	0.09419	0.13552				Limit ≤ 2.5 μW/MHz (-26 dBm)
	※ 2	μW	5.84790	0.09772	0.07516				Limit ≤ 25 μW/MHz (-16 dBm)
	※ 3	μW	0.05984	0.09204	10.06932				Limit ≤ 25 μW/MHz (-16 dBm)
	※ 4	μW	0.07244	0.09528	0.09795				Limit ≤ 2.5 μW/MHz (-26 dBm)
Antenna Power (Conducted)	mW/MHz	5.05571	5.02900	5.10249					Limit ≤ 10 mW/MHz (10 dBm/MHz)
Antenna Power Error		-0.04429	-0.07100	0.00249					
	%	-0.87	-1.39	0.05					Limit + 20% ~ - 80%
Limitation of Collateral Emission of Receiver	※ 5	nW	0.0175	0.0188	0.0169				Limit ≤ 4 nW (-54 dBm)
	※ 6	nW	1.1912	1.2331	0.8035				Limit ≤ 20 nW (-47 dBm)
Hopping Frequency Dwell Time	sec	-	-	-					Limit ≤ 0.4 sec (In 0.4 sec × spreading rate)
Radio Interference Prevention Function	ID Code	Good, MAC Address:00-0E-8E-40-89-82							
	Carrier Sense	NR	NR	NR					NR: Not Require

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz)

※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz)

※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz)

※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

3. Antenna Power (Conducted Power)

Test Voltage		Normal Voltage (5V)			Remarks				
Test Frequency	MHz	2412	2442	2472					
Power Meter Raw (IF of Spectrum)	dBm	-12.96	-12.98	-12.92					
Power Measurement System Loss	dB	20.49	20.49	20.49					Refer to Calibration Result
Transmitter Duty Cycle Factor	dB	0.00	0.00	0.00					Duty Factor = 10 × 10Log ₁₀ (1/Duty Cycle)
Equivalent Noise Bandwidth	MHz	1.12	1.12	1.12					ENB = Total_Sum^2 / Peak_Level * Point_Width
Equivalent Noise Bandwidth Factor	dB	0.49	0.49	0.49					ENB Factor = 10 × 10Log ₁₀ (1/ENB)
Antenna Power (Conducted)	dBm/MHz	7.04	7.01	7.08					Limit ≤ 10 mW/MHz (10 dBm/MHz)
Antenna Power (Conducted)	mW/MHz	5.0557	5.0290	5.1025					
Antenna Power Error	mW	-0.0443	-0.0710	0.0025					
	%	-0.87	-1.39	0.05					Limit + 20% ~ - 80%
Transmitter ON _{Time}	msec	1.0000							
Transmitter (ON+OFF) _{Time}	msec	1.0000							
Transmitter Duty Cycle	%	100.00%							

4. Transmission Radiation Angle Width (This test item will not be applied to the EIRP power is lower than 12.14dBm/MHz)

No.	Antenna Power		Antenna				Cable			Total Gain D=B+C	EIRP F=A+D	Permitted Angle	Judgement	Remarks (Antenna Model)
	A		Type	Gain B (dBi)	3dB Beam- width Horizontal (Degree)	3dB Beam- width Vertical (Degree)	Model	Length (m)	Loss C (dB)					
1	7.08		Dipole	3.67			-	-		3.67	10.75	360.00	Good	
2	7.08		Printed	3.79			-	-		3.79	10.87	360.00	Good	
3														
4														
5														
6														
7														
8														
9														
10														
11														
12														

6. Unwanted Emission Intensity

Test Voltage	V	Normal Voltage (5V)										Remarks
Test Frequency	MHz	2412	2442	2472								
Unwanted Emission Frequency	* 1	MHz	2358.72	1628.05	1646.90							RBW : 1 MHz ; VBW : 1 MHz
	* 2	MHz	2397.24	2387.13	2387.31							
	* 3	MHz	2488.88	2495.98	2486.78							
	* 4	MHz	3216.75	2496.50	3196.75							
Cable Loss	* 1	dB	1.34	1.34	1.34							
	* 2	dB	1.34	1.34	1.34							
	* 3	dB	1.34	1.34	1.34							
	* 4	dB	3.68	3.68	3.68							
Spectrum Raw	* 1	dBm	-42.06	-41.60	-40.02							
	* 2	dBm	-23.67	-41.44	-42.58							
	* 3	dBm	-43.57	-41.70	-21.31							
	* 4	dBm	-45.08	-43.89	-43.77							
Unwanted Emission Intensity	* 1	dBm	-40.72	-40.26	-38.68							Limit $\leq 2.5 \mu\text{W/MHz}$ (-26 dBm)
	* 2	dBm	-22.33	-40.10	-41.24							Limit $\leq 25 \mu\text{W/MHz}$ (-16 dBm)
	* 3	dBm	-42.23	-40.36	-19.97							Limit $\leq 25 \mu\text{W/MHz}$ (-16 dBm)
	* 4	dBm	-41.40	-40.21	-40.09							Limit $\leq 2.5 \mu\text{W/MHz}$ (-26 dBm)
Unwanted Emission Intensity	* 1	μW	0.0847	0.0942	0.1355							Limit $\leq 2.5 \mu\text{W/MHz}$ (-26 dBm)
	* 2	μW	5.8479	0.0977	0.0752							Limit $\leq 25 \mu\text{W/MHz}$ (-16 dBm)
	* 3	μW	0.0598	0.0920	10.0693							Limit $\leq 25 \mu\text{W/MHz}$ (-16 dBm)
	* 4	μW	0.0724	0.0953	0.0979							Limit $\leq 2.5 \mu\text{W/MHz}$ (-26 dBm)

- * 1: Frequency Band 1 (30 MHz $\leq f \leq$ 2387 MHz) * 4: Frequency Band 4 (2496.5 MHz $\leq f <$ 12.5 GHz)
 * 2: Frequency Band 2 (2387 MHz $< f \leq$ 2400 MHz) * 5: Frequency Band 5 (30 MHz $\leq f <$ 1000 MHz)
 * 3: Frequency Band 3 (2483.5 MHz $\leq f <$ 2496.5 MHz) * 6: Frequency Band 6 (1000 MHz $\leq f <$ 12.5 GHz)

7. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)										Remarks
Test Frequency	MHz	2412	2442	2472								
Spurious Emission Frequency	* 5	MHz	774.96	542.16	724.52							1st 30MHz~1000MHz:: Maximum emission and all emissions beyond 1/10 of the limitation must be indicated.
	* 5	MHz	-	-	-							2nd
	* 5	MHz	-	-	-							3rd
	* 6	MHz	3208.00	3254.00	3300.00							1st 1000MHz~12.5GHz:: Maximum emission and all emissions beyond 1/10 of the limitation must be indicated.
	* 6	MHz	-	-	-							2nd
	* 6	MHz	-	-	-							3rd
Cable Loss	* 5	dB	0.78	0.78	0.78							1st
	* 5	dB	-	-	-							2nd
	* 5	dB	-	-	-							3rd
	* 6	dB	3.68	3.68	3.68							1st
	* 6	dB	-	-	-							2nd
	* 6	dB	-	-	-							3rd
Spectrum Raw	* 5	dBm	-78.35	-78.03	-78.51							1st
	* 5	dBm	-	-	-							2nd
	* 5	dBm	-	-	-							3rd
	* 6	dBm	-62.92	-62.77	-64.63							1st
	* 6	dBm	-	-	-							2nd
	* 6	dBm	-	-	-							3rd
Spurious Emission Intensity	* 5	dBm	-77.57	-77.25	-77.73							1st Limit $\leq 4 \text{ nW}$ (-54 dBm)
	* 5	dBm	-	-	-							2nd RBW : 100 kHz ; VBW : 100 kHz
	* 5	dBm	-	-	-							3rd
	* 6	dBm	-59.24	-59.09	-60.95							1st Limit $\leq 20 \text{ nW}$ (-47 dBm)
	* 6	dBm	-	-	-							2nd RBW : 1 MHz ; VBW : 1 MHz
	* 6	dBm	-	-	-							3rd
Spurious Emission Intensity	* 5	nW	0.0175	0.0188	0.0169							Total Emission Power
	* 5	nW	0.0175	0.0188	0.0169							1st Limit $\leq 4 \text{ nW}$ (-54 dBm)
	* 5	nW	-	-	-							2nd RBW : 100 kHz ; VBW : 100 kHz
	* 5	nW	-	-	-							3rd
	* 6	nW	1.1912	1.2331	0.8035							Total Emission Power
	* 6	nW	1.1912	1.2331	0.8035							1st
	* 6	nW	-	-	-							2nd Limit $\leq 20 \text{ nW}$ (-47 dBm)
	* 6	nW	-	-	-							3rd RBW : 1 MHz ; VBW : 1 MHz

- * 1: Frequency Band 1 (30 MHz $\leq f \leq$ 2387 MHz) * 4: Frequency Band 4 (2496.5 MHz $\leq f <$ 12.5 GHz)
 * 2: Frequency Band 2 (2387 MHz $< f \leq$ 2400 MHz) * 5: Frequency Band 5 (30 MHz $\leq f <$ 1000 MHz)
 * 3: Frequency Band 3 (2483.5 MHz $\leq f <$ 2496.5 MHz) * 6: Frequency Band 6 (1000 MHz $\leq f <$ 12.5 GHz)

8. Spread Factor

Test Voltage	V	Normal Voltage (5V)										Remarks
Test Frequency	MHz	2412	2442	2472								
Spread-Spectrum Bandwidth	MHz	10.60	10.60	10.56								
Modulation Rate	Mcps	1.375	1.375	1.375								
Spread Factor		7.7091	7.7091	7.6800								Spread Factor Limit ≥ 5 (DSSS and FHSS)

Appendix C 19-11g-G1D(20MHz Mode)

Sporton No.	JR373103
Test Date	2013/9/5
Test Location	SPORTON Lab.
Temp. / Humid.	24.6℃ / 62%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19	Model	WUJB-R-508N	Temp. / Humid.	24.6℃ / 62%
	Type of Emission	G1D / D1D	Serial No.	12635W2002256	Test Site	TH06-HY
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Antenna Power	2.21 mW/MHz	Engineer	Shiming
	Frequency	2412~2472 MHz	Antenna Port	DAC 0	Department	Radio Service Group

2. Test Results

Testing for Electrical Specification	Test Voltage		V			Normal Voltage (5V)								Remarks	
	Test Frequency		MHz			2412	2442	2472						Low/Mid/High of test frequency range	
	Measured Frequency		MHz			2411.9694	2441.9688	2471.9682							
	Frequency Error		ppm			-12.69	-12.78	-12.86						Limit ≤ 50 ppm	
	Occupied Bandwidth		MHz			16.64	16.60	16.64						Limit ≤ 26 MHz (RB/NB : 300kHz)	
	Spread-spectrum Bandwidth		MHz			14.56	14.60	14.60						Spread Factor Limit ≥ 5 (DSSS and FHSS)	
	Unwanted Emission Intensity (Power emission within 1MHz bandwidth)	※ 1	μW	0.19275	0.07482	0.07278								Limit ≤ 2.5 μW/MHz (-26 dBm)	
		※ 2	μW	1.33660	0.20654	0.08851								Limit ≤ 25 μW/MHz (-16 dBm)	
		※ 3	μW	0.09572	0.18793	2.25944								Limit ≤ 25 μW/MHz (-16 dBm)	
		※ 4	μW	0.09638	0.13709	1.43219								Limit ≤ 2.5 μW/MHz (-26 dBm)	
	Antenna Power (Conducted)		mW/MHz			2.19170	2.20182	2.21198						Limit ≤ 10 mW/MHz (10 dBm/MHz)	
	Antenna Power Error		%			-0.01830	-0.00818	0.00198						Limit + 20% ~ - 80%	
	Limitation of Collateral Emission of Receiver	※ 5	nW	0.0180	0.0167	0.0165								Limit ≤ 4 nW (-54 dBm)	
		※ 6	nW	1.1858	1.1967	0.7603								Limit ≤ 20 nW (-47 dBm)	
	Hopping Frequency Dwell Time		sec			-	-	-						Limit ≤ 0.4 sec (In 0.4 sec × spreading rate)	
	Radio Interference Prevention Function		ID Code		Good, MAC Address:00-0E-8E-40-89-82										
			Carrier Sense			NR	NR	NR						NR: Not Require	

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz)

※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz)

※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz)

※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

3. Antenna Power (Conducted Power)

Testing for Electrical Specification	Test Voltage	V	Normal Voltage (5V)										Remarks
	Test Frequency	MHz	2412	2442	2472								
	Power Meter Raw (IF of Spectrum)	dBm	-16.59	-16.57	-16.55								
	Power Measurement System Loss	dB	20.49	20.49	20.49								Refer to Calibration Result
	Transmitter Duty Cycle Factor	dB	0.00	0.00	0.00								Duty Factor = 10 × 10Log ₁₀ (1/Duty Cycle)
	Equivalent Noise Bandwidth	MHz	1.12	1.12	1.12								ENB = Total_Sum^2 / Peak_Level * Point_Width
	Equivalent Noise Bandwidth Factor	dB	0.49	0.49	0.49								ENB Factor = 10 × 10Log ₁₀ (1/ENB)
	Antenna Power (Conducted)	dBm/MHz	3.41	3.43	3.45								Limit ≤ 10 mW/MHz (10 dBm/MHz)
	Antenna Power (Conducted)	mW/MHz	2.1917	2.2018	2.2120								
	Antenna Power Error	mW	-0.0183	-0.0082	0.0020								
		%	-0.83	-0.37	0.09								Limit + 20% ~ - 80%
	Transmitter ON _{Time}	msec	1.0000									RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz	
	Transmitter (ON+OFF) _{Time}	msec	1.0000										
	Transmitter Duty Cycle	%	100.00%										

4. Transmission Radiation Angle Width (This test item will not be applied to the EIRP power is lower than 12.14dBm/MHz)

No.	Antenna Power		Antenna				Cable			Total Gain D=B+C	EIRP F=A+D	Permitted Angle	Judgement	Remarks (Antenna Model)
	A (dBm/MHz)	Type	Gain B (dBi)	3dB Beam-width Horizontal (Degree)	3dB Beam-width Vertical (Degree)	Model	Length (m)	Loss C (dB)						
1	3.45	Dipole	3.67			-	-			3.67	7.12	360.00	Good	
2	3.45	Printed	3.79			-	-			3.79	7.24	360.00	Good	
3														
4														
5														
6														
7														
8														
9														
10														
11														
12														

6. Unwanted Emission Intensity

Test Voltage	V	Normal Voltage (5V)											Remarks
Test Frequency	MHz	2412	2442	2472									
Unwanted Emission Frequency	※ 1	MHz	2387.00	2387.00	2349.29								RBW : 1 MHz ; VBW : 1 MHz
	※ 2	MHz	2399.87	2389.55	2389.31								
	※ 3	MHz	2493.20	2494.55	2484.36								
	※ 4	MHz	2516.51	2496.50	2496.50								
Cable Loss	※ 1	dB	1.34	1.34	1.34								
	※ 2	dB	1.34	1.34	1.34								
	※ 3	dB	1.34	1.34	1.34								
	※ 4	dB	3.68	3.68	3.68								
Spectrum Raw	※ 1	dBm	-38.49	-42.60	-42.72								
	※ 2	dBm	-30.08	-38.19	-41.87								
	※ 3	dBm	-41.53	-38.60	-27.80								
	※ 4	dBm	-43.84	-42.31	-32.12								
Unwanted Emission Intensity	※ 1	dBm	-37.15	-41.26	-41.38								Limit ≤ 2.5 μW/MHz (-26 dBm)
	※ 2	dBm	-28.74	-36.85	-40.53								Limit ≤ 25 μW/MHz (-16 dBm)
	※ 3	dBm	-40.19	-37.26	-28.46								Limit ≤ 25 μW/MHz (-16 dBm)
	※ 4	dBm	-40.16	-38.63	-28.44								Limit ≤ 2.5 μW/MHz (-26 dBm)
Unwanted Emission Intensity	※ 1	μW	0.1928	0.0748	0.0728								Limit ≤ 2.5 μW/MHz (-26 dBm)
	※ 2	μW	1.3366	0.2065	0.0885								Limit ≤ 25 μW/MHz (-16 dBm)
	※ 3	μW	0.0957	0.1879	2.2594								Limit ≤ 25 μW/MHz (-16 dBm)
	※ 4	μW	0.0964	0.1371	1.4322								Limit ≤ 2.5 μW/MHz (-26 dBm)

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz) ※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz) ※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz) ※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

7. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V)											Remarks
Test Frequency	MHz	2412	2442	2472									
Spurious Emission Frequency	※ 5	MHz	513.06	866.14	187.14								1st
	※ 5	MHz	-	-	-								2nd
	※ 5	MHz	-	-	-								3rd
	※ 6	MHz	3208.00	3254.00	3300.00								1st
	※ 6	MHz	-	-	-								2nd
	※ 6	MHz	-	-	-								3rd
Cable Loss	※ 5	dB	0.78	0.78	0.78								1st
	※ 5	dB	-	-	-								2nd
	※ 5	dB	-	-	-								3rd
	※ 6	dB	3.68	3.68	3.68								1st
	※ 6	dB	-	-	-								2nd
	※ 6	dB	-	-	-								3rd
Spectrum Raw	※ 5	dBm	-78.23	-78.56	-78.60								1st
	※ 5	dBm	-	-	-								2nd
	※ 5	dBm	-	-	-								3rd
	※ 6	dBm	-62.94	-62.90	-64.87								1st
	※ 6	dBm	-	-	-								2nd
	※ 6	dBm	-	-	-								3rd
Spurious Emission Intensity	※ 5	dBm	-77.45	-77.78	-77.82								1st
	※ 5	dBm	-	-	-								2nd
	※ 5	dBm	-	-	-								3rd
	※ 6	dBm	-59.26	-59.22	-61.19								1st
	※ 6	dBm	-	-	-								2nd
	※ 6	dBm	-	-	-								3rd
Spurious Emission Intensity	※ 5	nW	0.0180	0.0167	0.0165								Total Emission Power
	※ 5	nW	0.0180	0.0167	0.0165								1st
	※ 5	nW	-	-	-								2nd
	※ 5	nW	-	-	-								3rd
	※ 6	nW	1.1858	1.1967	0.7603								Total Emission Power
	※ 6	nW	1.1858	1.1967	0.7603								1st
Spurious Emission Intensity	※ 6	nW	-	-	-								2nd
	※ 6	nW	-	-	-								3rd
	※ 6	nW	-	-	-								Limit ≤ 20 nW (-47 dBm)
	※ 6	nW	-	-	-								RBW : 1 MHz ; VBW : 1 MHz

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz) ※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz) ※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz) ※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

Appendix C 19-11n-G1D

Sporton No.	JR373103
Test Date	2013/9/4
Test Location	SPORTON Lab.
Temp. / Humid.	24.6°C / 56%
Test Site	TH06-HY
Engineer	Shiming
Department	Radio Service Group

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19	Model	WUBR-508N	Temp. / Humid.	24.6°C / 56%
	Type of Emission	G1D	Serial No.	12635W2002256	Test Site	TH06-HY
	Modulation Type	DSSS: BPSK, QPSK, CCK	Antenna Power	2.45 mW/MHz	Engineer	Shiming
	Frequency	2412~2472 MHz			Department	Radio Service Group

2. Test Results

Testing for Electrical Specification	Test Voltage	V	Normal Voltage (5V) Port 1			Normal Voltage (5V) Port 2			Normal Voltage (5V) Port Total			Remarks
	Test Frequency	MHz	2412	2442	2472	2412	2442	2472	2412	2442	2472	Low/Mid/High of test frequency range
	Measured Frequency	MHz	2411.9706	2441.9712	2471.9712	2411.9706	2441.9712	2471.9712	-	-	-	Limit \leq 50 ppm
	Frequency Error	ppm	-12.19	-11.79	-11.65	-12.19	-11.79	-11.65	-	-	-	Limit \leq 50 ppm
	Occupied Bandwidth	MHz	17.52	17.52	17.48	17.52	17.52	17.52	-	-	-	Limit \leq 26 MHz (RB/VB : 300kHz)
	Spread-spectrum Bandwidth	MHz	15.16	15.16	15.16	15.20	15.20	15.20	-	-	-	Spread Factor Limit \geq 5 (DSSS and FHSS)
	Unwanted Emission Intensity (Power emission within 1MHz bandwidth)	μ W	0.10023	0.05458	0.05000	0.13583	0.10691	0.09376	0.23606	0.16148	0.14376	Limit \leq 2.5 μ W (-26 dBm)
	※ 1	μ W	6.87068	0.13772	0.05875	1.91867	0.18923	0.08995	8.78935	0.32696	0.14870	Limit \leq 25 μ W (-16 dBm)
	※ 2	μ W	0.05164	0.13305	0.57810	0.05768	0.17258	0.39994	0.10932	0.30563	0.97804	Limit \leq 25 μ W (-16 dBm)
	※ 3	μ W	0.08433	0.09572	0.20749	0.11912	0.09484	0.14859	0.20346	0.19056	0.35608	Limit \leq 2.5 μ W (-26 dBm)
	※ 4	μ W										
	Antenna Power (Conducted)	mW/MHz	1.19339	1.19890	1.22119	1.24389	1.25251	1.19890	2.43728	2.45141	2.42008	Limit \leq 10 mW/MHz (10 dBm/MHz)
	Antenna Power Error	%	-1.25661	-1.25110	-1.22881	-1.20611	-1.19749	-1.25110	-0.01272	0.00141	-0.02992	Limit + 20% ~ - 80%
	Limitation of Collateral Emission of Receiver	nW	0.0194	0.0171	0.0192	0.0179	0.0177	0.0176	0.0373	0.0347	0.0368	Limit \leq 4 nW (-54 dBm)
	※ 5	nW	1.1298	1.1641	0.6577	0.3741	0.3342	0.2344	1.5039	1.4983	0.8921	Limit \leq 20 nW (-47 dBm)
	※ 6	nW										
	Hopping Frequency Dwell Time	sec	-	-	-	-	-	-	-	-	-	Limit \leq 0.4 sec (In 0.4 sec \times spreading rate)
	Radio Interference Prevention Function	ID Code	Good, MAC Address:00-0E-8E-40-89-82									
	Carrier Sense	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR: Not Require

※ 1: Frequency Band 1 (30 MHz \leq f \leq 2387 MHz)※ 4: Frequency Band 4 (2496.5 MHz \leq f < 12.5 GHz)※ 2: Frequency Band 2 (2387 MHz < f \leq 2400 MHz)※ 5: Frequency Band 5 (30 MHz \leq f < 1000 MHz)※ 3: Frequency Band 3 (2483.5 MHz \leq f < 2496.5 MHz)※ 6: Frequency Band 6 (1000 MHz \leq f < 12.5 GHz)

3. Antenna Power (Conducted Power)

Testing for Electrical Specification	Test Voltage	V	Normal Voltage (5V) Port 1			Normal Voltage (5V) Port 2			Normal Voltage (5V) Port Total			Remarks
	Test Frequency	MHz	2412	2442	2472	2412	2442	2472	2412	2442	2472	
	Power Meter Raw (IF of Spectrum)	dBm	-19.23	-19.21	-19.13	-19.05	-19.02	-19.21	-16.13	-16.10	-16.16	
	Power Measurement System Loss	dB	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	Refer to Calibration Result
	Transmitter Duty Cycle Factor	dB	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	Duty Factor = 10 × 10Log ₁₀ (1/Duty Cycle)
	Equivalent Noise Bandwidth	MHz	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	ENB = Total_Sum^2 / Peak_Level * Point_Width
	Equivalent Noise Bandwidth Factor	dB	0.49	0.49	0.49	0.49	0.49	0.49	0.49	0.49	0.49	ENB Factor = 10 × 10Log ₁₀ (1/ENB)
	Antenna Power (Conducted)	dBm/MHz	0.77	0.79	0.87	0.95	0.98	0.79	3.87	3.89	3.84	Limit ≤ 10 mW/MHz (10 dBm/MHz)
	Antenna Power (Conducted)	mW/MHz	1.1934	1.1989	1.2212	1.2439	1.2525	1.1989	2.4373	2.4514	2.4201	
	Antenna Power Error	mW	-1.2566	-1.2511	-1.2288	-1.2061	-1.1975	-1.2511	-0.0127	0.0014	-0.0299	
		%	-51.29	-51.07	-50.16	-49.23	-48.88	-51.07	-0.52	0.06	-1.22	Limit + 20% ~ - 80%
	Transmitter ON _{Time}	msec	1.0000									RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz
	Transmitter (ON+OFF) _{Time}	msec	1.0000									
	Transmitter Duty Cycle	%	100.00%									

4. Transmission Radiation Angle Width (This test item will not be applied to the EIRP power is lower than 12.14dBm/MHz)

No.	Antenna Power	Antenna				Cable			Total Gain D=B+C	EIRP F=A+D	Permitted Angle	Judgement	Remarks (Antenna Model)
	A (dBm/MHz)	Type	Gain B (dBi)	3dB Beam-width Horizontal (Degree)	3dB Beam-width Vertical (Degree)	Model	Length (m)	Loss C (dB)					
1	3.89	Dipole	3.67	-	-	-	-	-	3.67	7.57	360.00	Good	
2	3.89	Printed	3.79	-	-	-	-	-	3.79	7.68	360.00	Good	
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													

6. Unwanted Emission Intensity

Test Voltage	V	Normal Voltage (5V) Port 1			Normal Voltage (5V) Port 2			Normal Voltage (5V) Port Total			Remarks
Test Frequency	MHz	2412	2442	2472	2412	2442	2472	2412	2442	2472	
※ 1	MHz	2387.00	2377.57	2335.15	2363.43	2321.00	2335.15	-	-	-	RBW : 1 MHz ; VBW : 1 MHz
※ 2	MHz	2399.45	2389.81	2390.41	2399.84	2389.47	2398.78	-	-	-	
※ 3	MHz	2495.67	2493.82	2484.25	2493.72	2494.24	2483.53	-	-	-	
※ 4	MHz	3156.73	3116.72	2496.50	3126.75	2496.50	2496.50	-	-	-	
※ 1	dB	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	
※ 2	dB	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	
※ 3	dB	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	
※ 4	dB	3.68	3.68	3.68	3.68	3.68	3.68	3.68	3.68	3.68	
※ 1	dBm	-41.33	-43.97	-44.35	-40.01	-41.05	-41.62	-37.61	-39.26	-39.76	
※ 2	dBm	-22.97	-39.95	-43.65	-28.51	-38.57	-41.80	-21.90	-36.20	-39.62	
※ 3	dBm	-44.21	-40.10	-33.72	-43.73	-38.97	-35.32	-40.95	-36.49	-31.44	
※ 4	dBm	-44.42	-43.87	-40.51	-42.92	-43.91	-41.96	-40.60	-40.88	-38.16	
※ 1	dBm	-39.99	-42.63	-43.01	-38.67	-39.71	-40.28	-36.27	-37.92	-38.42	Limit ≤ 2.5 μW (-26 dBm)
※ 2	dBm	-21.63	-38.61	-42.31	-27.17	-37.23	-40.46	-20.56	-34.86	-38.28	Limit ≤ 25 μW (-16 dBm)
※ 3	dBm	-42.87	-38.76	-32.38	-42.39	-37.63	-33.98	-39.61	-35.15	-30.10	Limit ≤ 25 μW (-16 dBm)
※ 4	dBm	-40.74	-40.19	-36.83	-39.24	-40.23	-38.28	-36.92	-37.20	-34.48	Limit ≤ 2.5 μW (-26 dBm)
※ 1	μW	0.1002	0.0546	0.0500	0.1358	0.1069	0.0938	0.2361	0.1615	0.1438	Limit ≤ 2.5 μW (-26 dBm)
※ 2	μW	6.8707	0.1377	0.0587	1.9187	0.1892	0.0899	8.7894	0.3270	0.1487	Limit ≤ 25 μW (-16 dBm)
※ 3	μW	0.0516	0.1330	0.5781	0.0577	0.1726	0.3999	0.1093	0.3056	0.9780	Limit ≤ 25 μW (-16 dBm)
※ 4	μW	0.0843	0.0957	0.2075	0.1191	0.0948	0.1486	0.2035	0.1906	0.3561	Limit ≤ 2.5 μW (-26 dBm)

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz)

※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz)

※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz)

※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

7. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V) Port 1			Normal Voltage (5V) Port 2			Normal Voltage (5V) Port Total			Remarks
Test Frequency	MHz	2412	2442	2472	2412	2442	2472	2412	2442	2472	
※ 5	MHz	871.96	773.02	518.88	322.94	47.46	866.14	-	-	-	1st 30MHz~1000MHz:: Maximum emission and all
※ 5	MHz	-	-	-	-	-	-	-	-	-	emissions beyond 1/10 of the limitation must
※ 5	MHz	-	-	-	-	-	-	-	-	-	be indicated.
※ 6	MHz	3208.00	3254.00	3300.00	3208.00	3254.00	3300.00	-	-	-	1st 1000MHz~12.5GHz:: Maximum emission and
※ 6	MHz	-	-	-	-	-	-	-	-	-	all emissions beyond 1/10 of the limitation
※ 6	MHz	-	-	-	-	-	-	-	-	-	must be indicated.
※ 5	dB	0.78	0.78	0.78	0.78	0.78	0.78	0.78	0.78	0.78	1st
※ 5	dB	-	-	-	-	-	-	-	-	-	2nd
※ 5	dB	-	-	-	-	-	-	-	-	-	3rd
※ 6	dB	3.68	3.68	3.68	3.68	3.68	3.68	3.68	3.68	3.68	1st
※ 6	dB	-	-	-	-	-	-	-	-	-	2nd
※ 6	dB	-	-	-	-	-	-	-	-	-	3rd
※ 5	dBm	-77.91	-78.46	-77.95	-78.24	-78.31	-78.33	-75.06	-75.37	-75.13	1st
※ 5	dBm	-	-	-	-	-	-	-	-	-	2nd
※ 5	dBm	-	-	-	-	-	-	-	-	-	3rd
※ 6	dBm	-63.15	-63.02	-65.50	-67.95	-68.44	-69.98	-61.91	-61.92	-64.18	1st
※ 6	dBm	-	-	-	-	-	-	-	-	-	2nd
※ 6	dBm	-	-	-	-	-	-	-	-	-	3rd
※ 5	dBm	-77.13	-77.68	-77.17	-77.46	-77.53	-77.55	-74.28	-74.59	-74.35	1st
※ 5	dBm	-	-	-	-	-	-	-	-	-	2nd Limit ≤ 4 nW (-54 dBm)
※ 5	dBm	-	-	-	-	-	-	-	-	-	3rd RBW : 100 kHz ; VBW : 100 kHz
※ 6	dBm	-59.47	-59.34	-61.82	-64.27	-64.76	-66.30	-58.23	-58.24	-60.50	1st
※ 6	dBm	-	-	-	-	-	-	-	-	-	2nd Limit ≤ 20 nW (-47 dBm)
※ 6	dBm	-	-	-	-	-	-	-	-	-	3rd RBW : 1 MHz ; VBW : 1 MHz
※ 5	nW	0.0194	0.0171	0.0192	0.0179	0.0177	0.0176	0.0373	0.0347	0.0368	Total Emission Power
※ 5	nW	0.0194	0.0171	0.0192	0.0179	0.0177	0.0176	0.0373	0.0347	0.0368	1st
※ 5	nW	-	-	-	-	-	-	-	-	-	2nd Limit ≤ 4 nW (-54 dBm)
※ 5	nW	-	-	-	-	-	-	-	-	-	3rd RBW : 100 kHz ; VBW : 100 kHz
※ 6	nW	1.1298	1.1641	0.6577	0.3741	0.3342	0.2344	1.5039	1.4983	0.8921	Total Emission Power
※ 6	nW	1.1298	1.1641	0.6577	0.3741	0.3342	0.2344	1.5039	1.4983	0.8921	1st
※ 6	nW	-	-	-	-	-	-	-	-	-	2nd Limit ≤ 20 nW (-47 dBm)
※ 6	nW	-	-	-	-	-	-	-	-	-	3rd RBW : 1 MHz ; VBW : 1 MHz

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz)

※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz)

※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz)

※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

Appendix C 19-11n-G1D

1. General Information

Specified Radio Equipment	Class	Article 2 Paragraph 1 Item 19	Model	WUBR-508N	Temp. / Humid.	24.6℃ / 56%
	Type of Emission	G1D / DID	Serial No.	1.2635W2002256	Test Site	TH06-HY
	Modulation Type	OFDM: BPSK, QPSK, 16QAM, 64QAM	Antenna Power	1.19 mW/MHz	Engineer	Shiming
	Frequency	2422~2462 MHz			Department	Radio Service Group

2. Test Results

Testing for Electrical Specification	Test Voltage	V	Normal Voltage (5V) Port 1			Normal Voltage (5V) Port 2			Normal Voltage (5V) Port Total			Remarks	
	Test Frequency	MHz	2422	2442	2462	2422	2442	2462	2422	2442	2462	Low/Mid/High of test frequency range	
	Measured Frequency	MHz	2421.9724	2441.9826	2461.9778	2421.9724	2441.9826	2461.9778	-	-	-		
	Frequency Error	ppm	-11.40	-7.13	-9.02	-11.40	-7.13	-9.02	-	-	-	Limit ≤ 50 ppm	
	Occupied Bandwidth	MHz	35.92	35.92	35.92	35.92	36.00	36.00	-	-	-	Limit ≤ 38 MHz (RB/VB : 300kHz)	
	Spread-spectrum Bandwidth	MHz	31.92	31.92	31.84	32.08	32.16	32.16	-	-	-	Spread Factor Limit ≥ 5 (DSSS and FHSS)	
	Unwanted Emission Intensity (Power emission within 1MHz bandwidth)	※ 1	μW	1.53462	0.06823	0.06982	0.20701	0.10351	0.10593	1.74163	0.17175	0.17575	Limit ≤ 2.5 μW (-26 dBm)
		※ 2	μW	3.54813	0.81470	0.06730	1.58855	0.20559	0.07345	5.13668	1.02029	0.14075	Limit ≤ 25 μW (-16 dBm)
		※ 3	μW	0.07603	1.24165	8.24138	0.05875	0.80353	5.18800	0.13478	2.04518	13.42938	Limit ≤ 25 μW (-16 dBm)
		※ 4	μW	0.08730	0.08166	0.19011	0.11455	0.07852	0.11092	0.20185	0.16018	0.30103	Limit ≤ 2.5 μW (-26 dBm)
	Antenna Power (Conducted)	mW/MHz	0.57914	0.57119	0.60087	0.55307	0.55819	0.59126	1.13221	1.12938	1.19214	Limit ≤ 5 mW/MHz (7 dBm/MHz)	
	Antenna Power Error	mW/MHz	-0.61086	-0.61881	-0.58913	-0.63693	-0.63181	-0.59874	-0.05797	-0.06062	0.00214		
		%	-51.33	-52.00	-49.51	-53.52	-53.09	-50.31	-4.86	-5.09	0.18	Limit + 20% ~ - 80%	
	Limitation of Collateral Emission of Receiver	※ 5	nW	0.0199	0.0206	0.0160	0.0244	0.0187	0.0236	0.0443	0.0393	0.0396	Limit ≤ 4 nW (-54 dBm)
		※ 6	nW	1.1641	1.1117	0.8260	0.3776	0.3206	0.2138	1.5417	1.4324	1.0398	Limit ≤ 20 nW (-47 dBm)
	Hopping Frequency Dwell Time	sec	-	-	-	-	-	-	-	-	-	Limit ≤ 0.4 sec (In 0.4 sec × spreading rate)	
	Radio Interference Prevention Function	ID Code	Good, MAC Address:00-0E-8E-40-89-82										
		Carrier Sense	Good	Good	Good	Good	Good	Good	Good	Good	Good	NR: Not Require	

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz)

※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz)

※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz)

※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

3. Antenna Power (Conducted Power)

Testing for Electrical Specification	Test Voltage	V	Normal Voltage (SV) Port 1			Normal Voltage (SV) Port 2			Normal Voltage (SV) Port Total			Remarks
	Test Frequency	MHz	2422	2442	2462	2422	2442	2462	2422	2442	2462	
	Power Meter Raw (IF of Spectrum)	dBm	-22.37	-22.43	-22.21	-22.57	-22.53	-22.28	-19.46	-19.47	-19.23	
	Power Measurement System Loss	dB	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	Refer to Calibration Result
	Transmitter Duty Cycle Factor	dB	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	Duty Factor = $10 \times 10\text{Log}_{10}(1/\text{Duty Cycle})$
	Equivalent Noise Bandwidth	MHz	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	ENB = $\text{Total_Sum}^2 / \text{Peak_Level} \times \text{Point_Width}$
	Equivalent Noise Bandwidth Factor	dB	0.49	0.49	0.49	0.49	0.49	0.49	0.49	0.49	0.49	ENB Factor = $10 \times 10\text{Log}_{10}(1/\text{ENB})$
	Antenna Power (Conducted)	dBm/MHz	-2.37	-2.43	-2.21	-2.57	-2.53	-2.28	0.54	0.53	0.76	Limit ≤ 10 mW/MHz (10 dBm/MHz)
	Antenna Power (Conducted)	mW/MHz	0.5791	0.5712	0.6009	0.5531	0.5582	0.5913	1.1322	1.1294	1.1921	
	Antenna Power Error	mW	-0.6109	-0.6188	-0.5891	-0.6369	-0.6318	-0.5987	-0.0578	-0.0606	0.0021	
		%	-51.33	-52.00	-49.51	-53.52	-53.09	-50.31	-4.86	-5.09	0.18	Limit + 20% ~ - 80%
	Transmitter ON _{time}	msec	1.0000									RBW : 1 MHz ; VBW : 1 MHz ; SP : 0Hz
	Transmitter (ON+OFF) _{time}	msec	1.0000									
	Transmitter Duty Cycle	%	100.00%									

4. Transmission Radiation Angle Width (This test item will not be applied to the EIRP power is lower than 12.14dBm/MHz)

No.	Antenna Power		Antenna				Cable			Total Gain D=B+C	EIRP F=A+D	Permitted Angle	Judgement	Remarks (Antenna Model)
	A	Type	Gain B (dBi)	3dB Beam- width Horizontal (Degree)	3dB Beam- width Vertical (Degree)	Model	Length (m)	Loss C (dB)						
1	0.76	Dipole	3.67	-	-	-	-	-	3.67	4.44	360.00	Good		
2	0.76	Printed	3.79	-	-	-	-	-	3.79	4.55	360.00	Good		
3														
4														
5														
6														
7														
8														
9														
10														
11														
12														

6. Unwanted Emission Intensity

Test Voltage	V	Normal Voltage (5V) Port 1			Normal Voltage (5V) Port 2			Normal Voltage (5V) Port Total			Remarks
Test Frequency	MHz	2422	2442	2462	2422	2442	2462	2422	2442	2462	
Unwanted Emission Frequency	※ 1	MHz	2387.00	2339.86	2363.43	2387.00	2339.86	2358.72	-	-	RBW : 1 MHz ; VBW : 1 MHz
	※ 2	MHz	2395.89	2398.02	2391.47	2400.00	2399.45	2387.91	-	-	
	※ 3	MHz	2485.09	2486.33	2483.92	2484.93	2483.86	2483.71	-	-	
	※ 4	MHz	2516.51	3156.73	2496.50	3216.75	3296.78	2496.50	-	-	
Cable Loss	※ 1	dB	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	
	※ 2	dB	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	
	※ 3	dB	1.34	1.34	1.34	1.34	1.34	1.34	1.34	1.34	
	※ 4	dB	3.68	3.68	3.68	3.68	3.68	3.68	3.68	3.68	
Spectrum Raw	※ 1	dBm	-29.48	-43.00	-42.90	-38.18	-41.19	-41.09	-28.93	-38.99	-38.89
	※ 2	dBm	-25.84	-32.23	-43.06	-29.33	-38.21	-42.68	-24.23	-31.25	-39.86
	※ 3	dBm	-42.53	-30.40	-22.18	-43.65	-32.29	-24.19	-40.04	-28.23	-20.06
	※ 4	dBm	-44.27	-44.56	-40.89	-43.09	-44.73	-43.23	-40.63	-41.63	-38.89
Unwanted Emission Intensity	※ 1	dBm	-28.14	-41.66	-41.56	-36.84	-39.85	-39.75	-27.59	-37.65	Limit ≤ 2.5 μW (-26 dBm)
	※ 2	dBm	-24.50	-30.89	-41.72	-27.99	-36.87	-41.34	-22.89	-29.91	Limit ≤ 25 μW (-16 dBm)
	※ 3	dBm	-41.19	-29.06	-42.31	-30.95	-22.85	-38.70	-26.89	-18.72	Limit ≤ 25 μW (-16 dBm)
	※ 4	dBm	-40.59	-40.88	-37.21	-39.41	-41.05	-39.55	-36.95	-37.95	Limit ≤ 2.5 μW (-26 dBm)
Unwanted Emission Intensity	※ 1	μW	1.5346	0.0682	0.0698	0.2070	0.1035	0.1059	1.741631	0.171748	0.175749
	※ 2	μW	3.5481	0.8147	0.0673	1.5885	0.2056	0.0735	5.136681	1.020293	0.140749
	※ 3	μW	0.0760	1.2417	8.2414	0.0587	0.8035	5.1880	0.134782	2.045178	13.429382
	※ 4	μW	0.0873	0.0817	0.1901	0.1146	0.0785	0.1109	0.201848	0.160182	0.301025

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz)

※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz)

※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz)

※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

7. Limitation of Collateral Emission of Receiver

Test Voltage	V	Normal Voltage (5V) Port 1			Normal Voltage (5V) Port 2			Normal Voltage (5V) Port Total			Remarks
Test Frequency	MHz	2422	2442	2462	2422	2442	2462	2422	2442	2462	
Spurious Emission Frequency	※ 5	MHz	790.48	565.44	80.44	961.20	161.92	961.20	-	-	1st 30MHz~1000MHz:: Maximum emission and all emissions beyond 1/10 of the limitation must be indicated.
	※ 5	MHz	-	-	-	-	-	-	-	-	
	※ 5	MHz	-	-	-	-	-	-	-	-	
	※ 6	MHz	3231.00	3254.00	3277.00	3231.00	3254.00	3277.00	-	-	1st 1000MHz~12.5GHz:: Maximum emission and all emissions beyond 1/10 of the limitation must be indicated.
	※ 6	MHz	-	-	-	-	-	-	-	-	
	※ 6	MHz	-	-	-	-	-	-	-	-	
Cable Loss	※ 5	dB	0.78	0.78	0.78	0.78	0.78	0.78	0.78	0.78	1st
	※ 5	dB	-	-	-	-	-	-	-	-	2nd
	※ 5	dB	-	-	-	-	-	-	-	-	3rd
	※ 6	dB	3.68	3.68	3.68	3.68	3.68	3.68	3.68	3.68	1st
	※ 6	dB	-	-	-	-	-	-	-	-	2nd
	※ 6	dB	-	-	-	-	-	-	-	-	3rd
Spectrum Raw	※ 5	dBm	-77.79	-77.65	-78.73	-76.90	-78.06	-77.05	-74.31	-74.84	-74.80
	※ 5	dBm	-	-	-	-	-	-	-	-	1st
	※ 5	dBm	-	-	-	-	-	-	-	-	2nd
	※ 5	dBm	-	-	-	-	-	-	-	-	3rd
	※ 6	dBm	-63.02	-63.22	-64.51	-67.91	-68.62	-70.38	-61.80	-62.12	-63.51
	※ 6	dBm	-	-	-	-	-	-	-	-	1st
Spurious Emission Intensity	※ 5	dBm	-77.01	-76.87	-77.95	-76.12	-77.28	-76.27	-73.53	-74.06	-74.02
	※ 5	dBm	-	-	-	-	-	-	-	-	1st Limit ≤ 4 nW (-54 dBm)
	※ 5	dBm	-	-	-	-	-	-	-	-	2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 5	dBm	-	-	-	-	-	-	-	-	3rd
	※ 6	dBm	-59.34	-59.54	-60.83	-64.23	-64.94	-66.70	-58.12	-58.44	-59.83
	※ 6	dBm	-	-	-	-	-	-	-	-	1st Limit ≤ 20 nW (-47 dBm)
Spurious Emission Intensity	※ 5	nW	0.0199	0.0206	0.0160	0.0244	0.0187	0.0236	0.0443	0.0393	0.0396
	※ 5	nW	0.0199	0.0206	0.0160	0.0244	0.0187	0.0236	0.0443	0.0393	0.0396
	※ 5	nW	-	-	-	-	-	-	-	-	1st Limit ≤ 4 nW (-54 dBm)
	※ 5	nW	-	-	-	-	-	-	-	-	2nd RBW : 100 kHz ; VBW : 100 kHz
	※ 5	nW	-	-	-	-	-	-	-	-	3rd
	※ 6	nW	1.1641	1.1117	0.8260	0.3776	0.3206	0.2138	1.5417	1.4324	1.0398
Spurious Emission Intensity	※ 6	nW	1.1641	1.1117	0.8260	0.3776	0.3206	0.2138	1.5417	1.4324	1.0398
	※ 6	nW	-	-	-	-	-	-	-	-	1st Limit ≤ 20 nW (-47 dBm)
	※ 6	nW	-	-	-	-	-	-	-	-	2nd RBW : 1 MHz ; VBW : 1 MHz
	※ 6	nW	-	-	-	-	-	-	-	-	3rd

※ 1: Frequency Band 1 (30 MHz ≤ f ≤ 2387 MHz)

※ 4: Frequency Band 4 (2496.5 MHz ≤ f < 12.5 GHz)

※ 2: Frequency Band 2 (2387 MHz < f ≤ 2400 MHz)

※ 5: Frequency Band 5 (30 MHz ≤ f < 1000 MHz)

※ 3: Frequency Band 3 (2483.5 MHz ≤ f < 2496.5 MHz)

※ 6: Frequency Band 6 (1000 MHz ≤ f < 12.5 GHz)

8. Carrier Sense Capability

Test Voltage	V	Normal Voltage (5V) Port 1			Normal Voltage (5V) Port 2			Normal Voltage (5V) Port Total			Remarks
Test Frequency	MHz	2422	2442	2462	2422	2442	2462	2422	2442	2462	
Mini. Antenna Gain	dB	1	1	1	1	1	1	1	1	1	
Carrier Level	dBm	-	-	-	-	-	-	-50.75	-50.60	-49.46	Pin = 22.79+Gr-20*log(freq_MHz) [dBm]
Result	Good/Fail	Good	Good	Good	Good	Good	Good	Good	Good	Good	

Power Supply Voltage Fluctuation Test

Voltage Fluctuation Test	Normal Voltage	High Voltage + 10% of Normal Voltage	Low Voltage - 10% of Normal Voltage
Input DC Power	5	5.5	4.5
Output DC Power	3.26	3.27	3.25
Voltage Variation (%)	-	0.306748	-0.306748

Note: Voltage Variation (%) = (Output High or Low Voltage - Output Normal Voltage)/Output Normal Voltage X 100
 During the input supply voltage to the EUT from the external power source is varied by +/- 10%, if output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/- 1%. Exempt extremely high and low supply voltage condition tests, EUT only operated in normal voltage to test all regulations.